

SCALA PROGRAMMING MIND MAP

(Complete)

Scala



└─ 4. Object-Oriented Concepts

- └─ Classes & Objects
- └─ Constructors
- └─ Case Classes
- └─ Traits
- └─ Inheritance
- └─ Companion Objects
- └─ Abstract Classes

└─ 5. Functional Programming

- └─ Immutability
- └─ Pure functions
- └─ map, flatMap, filter pipeline
- └─ Pattern Matching
- └─ Partial Functions
- └─ Higher-Kinded Types (Option, Either)
- └─ Typeclasses (implicit behavior)

└─ 6. Error Handling

- └─ try/catch/finally
- └─ Try, Success, Failure
- └─ Option (Some/None)
- └─ Either (Right/Left)

└─ 7. Advanced Scala

- └─ Implicits (implicit vals, defs)
- └─ Extension Methods
- └─ Pattern Matching Advanced
- └─ Generics
- └─ Enums (Scala 3)
- └─ Recursion & Tail Recursion
- └─ Collections Performance

└─ 8. Scala + Spark Essentials

- └─ SparkSession creation
- └─ DataFrame → Dataset conversion (case classes)
- └─ UDFs

- | |— Joins, filters
- | |— Window functions
- | |— Broadcast joins
- |
- |— 9. Tools & Ecosystem
 - |— sbt
 - |— IntelliJ setup
 - |— REPL
 - |— File I/O

CODE SNIPPETS FOR EVERY TOPIC

1 SCALA BASICS

Variables

```
val name: String = "Dani"      // immutable
var age: Int = 30              // mutable
age = age + 1
```

Conditionals

```
if (age > 18) println("Adult")
else println("Minor")
```

Loops

```
for (i <- 1 to 5) println(i)
```

2 FUNCTIONS

Function definition

```
def add(a: Int, b: Int): Int = a + b
```

Anonymous function (lambda)

```
val square = (x: Int) => x * x
```

Higher-order functions

```
def operate(a: Int, b: Int, f: (Int, Int) => Int): Int = f(a, b)  
operate(10, 20, _ + _)
```

Currying

```
def multiply(a: Int)(b: Int) = a * b  
multiply(5)(2)
```

3 COLLECTIONS

Immutable List

```
val nums = List(1,2,3,4)
```

map, filter, reduce

```
nums.map(_ * 2)  
nums.filter(_ % 2 == 0)  
nums.reduce(_ + _)
```

groupBy

```
val grouped = List("apple", "ant", "bat").groupBy(_.charAt(0))
```

4 OOP

Class + Constructor

```
class Person(val name: String, val age: Int)
```

```
val p = new Person("Arun", 28)
```

Case class

```
case class Employee(id: Int, name: String)
```

Trait + Inheritance

```
trait Animal { def speak(): Unit }  
class Dog extends Animal { def speak() = println("Bow Bow") }
```

```
new Dog().speak()
```

Companion object

```
class Counter(val value: Int)  
object Counter {  
  def apply(v: Int): Counter = new Counter(v)  
}  
val c = Counter(10)
```

5 FUNCTIONAL PROGRAMMING

Pattern matching

```
val x = 2
x match {
  case 1 => println("One")
  case 2 => println("Two")
  case _ => println("Other")
}
```

Option

```
val data: Option[String] = Some("Scala")
data.getOrElse("No value")
```

Either (Right = success)

```
def safeDivide(a: Int, b: Int): Either[String, Int] =
  if (b == 0) Left("Div by 0") else Right(a / b)
```

6 ERROR HANDLING

Try / Success / Failure

```
import scala.util.{Try, Success, Failure}

val result = Try(10 / 0)

result match {
  case Success(v) => println(v)
  case Failure(e) => println(e.getMessage)
}
```

7 ADVANCED SCALA

Implicits (auto behavior)

```
implicit val defaultMultiplier = 2

def multiply(x: Int)(implicit m: Int) = x * m

multiply(10)    // uses implicit 2
```

Generics

```
def first[A](list: List[A]): A = list.head
```

Tail recursion

```
@annotation.tailrec
def fact(n: Int, acc: Int = 1): Int =
  if (n <= 1) acc else fact(n - 1, n * acc)
```

8 SCALA + SPARK (CORE CONCEPTS)

SparkSession

```
val spark = SparkSession.builder()
  .appName("App")
  .master("local[*]")
  .getOrCreate()
```

DataFrame → Dataset

```
case class Person(id: Int, name: String)
val df = Seq((1,"a"), (2,"b")).toDF("id","name")
val ds = df.as[Person]
```

UDF

```
val toUpper = udf((s: String) => s.toUpperCase)
df.withColumn("upper", toUpper($"name"))
```

Window function

```
val w = Window.partitionBy("dept").orderBy($"salary".desc)
df.withColumn("rank", rank().over(w))
```

Broadcast join

```
large.join(broadcast(small), "id")
```

9 TOOLS

sbt build example

```
ThisBuild / scalaVersion := "2.12.18"

libraryDependencies += Seq(
  "org.apache.spark" %% "spark-core"   % "3.5.1",
  "org.apache.spark" %% "spark-sql"    % "3.5.1"
)
```
