

```

# Modificato da Vic 2023-05-23

# At the moment this script does:
# Deploy master & workers
# Deploy Docker Registry
#
# N.B. Need to manually select the Network Interface at Runtime

## Variables

VAGRANTFILE_VERSION = "2"
#BASEBOX = "ubuntu/xenial64"
BASEBOX = "debian/bullseye64"
MEMORY = "512"
CPUS = 2
INTERNAL_MANAGER_IP = "10.133.7.101"
WORKERS = 1
# aggiungo l'ultima (terza) cifra per formare l' IP
INTERNAL_WORKER_IP = "10.133.7.11"

#####
## Scripts

# VIENE USATO
# Install Docker Script with convenience script
# Lavoro come utente vagrant che
$install_docker_script = <<SCRIPT
echo "Preparing machine..."
who
apt-get update && \
apt-get install -y curl && \
echo "Installing Docker..." && \
curl -fsSL https://get.docker.com -o get-docker.sh && \
sh ./get-docker.sh
rm -f get-docker.sh
sudo groupadd docker
sudo usermod -aG docker $USER
sudo usermod -aG docker vagrant
SCRIPT

# VIENE USATO
#Allow_insecure_registry
$allow_insecure_registry = <<SCRIPT
echo "Configure insecure registries for docker daemon..."
sudo tee /etc/docker/daemon.json <<<'{"insecure-registries":
["127.0.0.1:5000", "'#{INTERNAL_MANAGER_IP}':5000"] }'
sudo chmod 644 /etc/docker/daemon.json
sudo systemctl reload docker
SCRIPT

# VIENE USATO
# Install utilities for test and debugging sush as ifconfig
and jq
# Lavoro come utente vagrant che
$install_utilities_script = <<SCRIPT
echo "Install utilities..."
who

```

```

apt-get update && \
apt-get install -y jq
SCRIPT

## Deploy

Vagrant.configure(VAGRANTFILE_VERSION) do |config|
  #Common setup
  config.vm.box = BASEBOX
  config.vm.synced_folder ".", "/vagrant", disabled: false
  config.vm.provision "shell", inline:
$install_docker_script, privileged: true
  config.vm.provision "shell", inline:
$allow_insecure_registry, privileged: true
  config.vm.provision "shell", inline:
$install_utilities_script, privileged: true
  config.vm.provider "virtualbox" do |vb|
    vb.memory = MEMORY
    vb.cpus = CPUS
  end

  ## VIC: non uso piu' la cache esterna per i pacchetti APT
  #   config.vm.provision "shell", inline: <<-SHELL
  #     echo 'Acquire::http::Proxy
"http://192.168.99.1:3142/";' >> /etc/apt/apt.conf
  #   # echo 'Acquire::http::Proxy
"http://192.168.99.1:53142/";' >> /etc/apt/apt.conf
  #     chmod 644 /etc/apt/apt.conf
  #     apt-get update -y
  #   SHELL
  ##   config.vm.provision 'shell', reboot: true
  ##   config.vm.provision 'shell', inline: <<-SHELL
  ##     echo 'reboot done'
  ##   SHELL

  # Setup Manager Nodes
  config.vm.define "manager" do |manager|
    # nat network ?
    manager.vm.network :public_network, type: "dhcp"
    # internal network
    manager.vm.network :private_network, ip:
"#{INTERNAL_MANAGER_IP}",
      virtualbox__intnet: true
    manager.vm.hostname = "manager"
    manager.vm.network :forwarded_port, guest: 61000,
host: 61000
    #
    # questi commentati fanno inizializzazione dello swarm
manager e creano registry
    #manager.vm.provision "shell", inline: $swarm_init
    #manager.vm.provision "shell", inline:
$swarm_token_for_worker
    #manager.vm.provision "shell", inline: $registry_deploy
  end

  #Setup Woker Nodes
  (1..WORKERS).each do |i|

```

```

        config.vm.define "worker0#{i}" do |worker|
          worker.vm.network :private_network, ip:
"#{INTERNAL_WORKER_IP}#{i}",
            virtualbox____intnet: true
          worker.vm.hostname = "worker0#{i}"
          #
          # questo commentato fa il join dei worker
          #worker.vm.provision "shell",inline:
$swarm_worker_join
        end
      end
    end
  end
end

```