FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

Mr. Ali Reza Hemani
Fatimiyah Hospital
Britto Road
Soldier Bazar
Karachi:

Date: 30-03-2026
Ref: 786/110/FT/1428/KHI.

Subject: QUOTATION FOR HDU EQUIPMENT

Dear Sir,

With reference to the above, we are pleased to quote our best Quoted prices, under the following terms and conditions:

Supplier/

1. **Manufacturer:** Shenzhen Comen Medical Instruments Co., Ltd.
2. **Origin:** CHINA.
3. **Prices:** Prices are quoted in PKR.
4. **Validity:** Prices are valid for 30 days.

Delivery: Ready Stock. Immediate Delivery

Monitor C-80 5 Nos.

Infusion Pump ME300 3 Nos.

Syringe Pump M300 5 Nos.

5. **Payments:** 50% advance 50% at the time of delivery.
6. **Warranty:** 01years warranty for manufacturing fault will be provided.
7. **Installation:** Installation and Demonstration of the instrument will be carried out by our factory trained engineer at site FREE OF CHARGE.

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

8. **Training:** Operational/Application training at site to the end user will be Provided FREE OF CHARGE.

10. **Spare Parts:** The Spare Parts and Probes shall be made available for a minimum period of 10 years from the date of supply/installation

S. NO	DESCRIPTION	MODEL	QT'Y	UNIT PRICE
01	INFUSION PUMP	ME-600 COMEN	01	120,000-00
02	Multi-parameter Patient Monitor with 5 Parameters • COMEN SPO2 • NIBP • TEMPERATURE • ECG • BATTERY BACKUP	C80 COMEN	01	320,000-00
03	SYRINGE PUMP	M300 COMEN	01	120,000-00

Rawalpindi Office:
301-1st Floor, Zahoor Plaza, Lane # 3,
Near Askari Bank, Peshawar Road,
Rawalpindi. Ph: +92-51-5174278-79
Fax: +92-51-5174277

Lahore Regional Office:
40-Edward Road,
(Syed Moj Darya), Lahore.
Ph: +92-42-37350012-13,
+92-42-37324358

Faisalabad Office:
P8, 1st Floor, Street No 1-A,
Opposite GC University,
Allama Iqbal Road, Faisalabad.
Ph: +92-41-2600096,

Multan Office:
Office # 21-A, 1st Floor,
Dost Medical Complex,
Nishter Road, Multan.
Ph: +92-61-4500770

Karachi Office:
A-89, Block No 1,
KDA Scheme No 24,
Gulshan-e-Iqbal, Karachi
Ph: 92-21-34810306

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

TECHNICAL SPECIFICATION OF INFUSION PUMP ME-600

Standard Configuration

Physical Characteristics

- Dimensions: <208mm×150mm×90mm (L*W*H)
- Weight ≤1.5kg (Including battery)
- Screen Size: 3" Segmented LCD Display, 240×128 pixels
- Classification: Type CF, Defibrillation-proof, Class I, EN1789 Certified

Operating Conditions

- Temperature: 5~40°C
- Humidity: 15%~95% (non-condensing)
- Pressure: 57.0~106.0kPa

Storage Conditions

- Temperature: -20~+55°C
- Humidity: 10%~95% (non-condensing)
- Pressure: 57.0~106.0kPa

Power

- Power requirement: 100-240V~, 50/60Hz±1Hz
- Applied Input Power: 0.5A~0.3A
- Battery Type: Rechargeable Lithium-ion battery
- Battery Capacity: Standard 7.2V — 2550mAh
- Battery Charging Time: 2550mAh, Not more than 4 hours to full charge when powered off
- performance: Up to 5 hours of continuous working (at 25ml/h)

Functional

- Working modes:

Rawalpindi Office:
301-1st Floor, Zahoor Plaza, Lane # 3,
Near Askari Bank, Peshawar Road,
Rawalpindi. Ph: +92-51-5174278-79
Fax: +92-51-5174277

Lahore Regional Office:
40-Edward Road,
(Syed Moj Darya), Lahore.
Ph: +92-42-37350012-13,
+92-42-37324358

Faisalabad Office:
P8, 1st Floor, Street No 1-A,
Opposite GC University,
Allama Iqbal Road, Faisalabad.
Ph: +92-41-2600096,

Multan Office:
Office # 21-A, 1st Floor,
Dost Medical Complex,
Nishter Road, Multan.
Ph: +92-61-4500770

Karachi Office:
A-89, Block No 1,
KDA Scheme No 24,
Gulshan-e-Iqbal, Karachi
Ph: 92-21-34810306

- Rate Mode, Time Mode, Drip Mode, Weight Mode, Sequential mode, First dose mode, Ramp mode, Micro mode, Intermittent Mode, Dose Time Mode
- Infusion system: Peristaltic

Indicators

- Hardware Indicators: Battery status indicator
- AC Power indicator
- Alarm Light bar indicator
- On-Screen Indicators:
- Infusion related information: Selected drug, Mode, Left Vol, Volume, Rest Time, Infusion Rate, Alarm status, Battery status, Syringe brand and size, Running (Infusion Status) Bar, WIFI Icon Dynamic Pressure System (DPS)

TECHNICAL SPECIFICATION OF SYRINGE PUMP M300

Standard Configuration

Physical Characteristics

Dimensions:	<312mm×128mm×133mm (L*W*H)
Weight	≤1.6kg (Including battery)
Screen Size:	3” Segmented LCD Display, 240×128 pixels
Classification:	Type CF, Defibrillation-proof, Class I, EN1789 Certified

Operating Conditions

Temperature:	5~40°C
Humidity:	15%~95% (non-condensing)
Pressure:	57.0~106.0kPa

Storage Conditions

Temperature:	-20~+55°C

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

Humidity: 10%~95% (non-condensing)

Pressure: 57.0~106.0kPa

Power

Power requirement: 100-240V~, 50/60Hz±1Hz
Applied Input Power: 0.5A~0.3A
Battery Type: Rechargeable Lithium-ion battery
Battery Capacity: Standard 7.2V − 2550mAh
Battery Charging Time: 2550mAh, Not more than 4 hours to full charge when powered off
performance: Up to 6 hours of continuous working (at 50ml/h)

Functional

Working modes:
Rate Mode, Time Mode, Drip Mode, Weight Mode, Sequential mode, First dose mode, Ramp mode, Micro mode, Intermittent Mode, Dose Time Mode
Supported infusions:

Blood products, Medication and drugs, Enteral/Parenteral nutrition

ml/h~2000 ml/h, step: 1 ml/h
VTBI range: 0.10~9999ml
VTBI steps: At 0.10 ml~99.9ml, step: 0.01 ml
At 100.0 ml~999.9ml, step: 0.1 ml
At 1000 ml~9999 ml, step: 1 ml
Time range: 00:00:01~99:59:59 (h:m:s); Step: 1s

Alarms:
Compliance: IEC60601-1-8
Alarm levels: P1 to P4
Alarm volume: Max: 65db (At 1m distance)
Min: 45db (At 1m distance)
Occlusion Alarm:
Range: 150~900mmHg (P1-P4)
Accuracy: ±20% or ±125mmHg,
whichever is greater
Unit settings: mmHg, kPa, bar, psi
EBIS: 3 Levels Selectable Empty Bottle Inspection Sensitivity (EBIS)

Features
Syringe selection:
Brands selectable upon Infusion Set installation: JieRui, BD Supports up to 3 user-defined custom Syringe Brands.

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

Syringe Parameters: 5ml, 10ml, 20ml, 30ml, 50/60ml
Accumulated Volume Range: 0.10~9999ml

Safety Standards Certification

- CE Certificate
- ISO 13485:2016

TECHNICAL SPECIFICATION OF PATIENT MONITOR C-80

Standard Configurations:

- **Patient Monitor: C80:** Display: 12.1-inches color TFT screen
- **Parameters:** 5-lead ECG, HR, RESP, NIBP, Comen SpO2, 2-TEMP, PR
- 01 x Rechargeable Lithium-ion battery (4400mAh)
- Power Cord

Accessories:

- 12Pin 5-Lead Clip Connector ECG Cable/Anti-Defibrillation/IEC
- Electrodes (Adult), 12pcs/pack
- Comen Adult Reusable Analog SpO2 sensor (10ft, 12pin)
- Adult NIBP Tube (white) 2M
- Adult NIBP Cuff

Technical Specifications:

Physical Characteristics:

Product Size:	347mm*291mm*165mm
Weight:	3.9kg
Display:	12.1" color TFT screen
Resolution:	800*600
Waveform Display:	8 waveforms
IP grade	IPX1

Operation Environment:

Working Temperature	5-40°C

Rawalpindi Office:
301-1st Floor, Zahoor Plaza, Lane # 3,
Near Askari Bank, Peshawar Road,
Rawalpindi. Ph: +92-51-5174278-79
Fax: +92-51-5174277

Lahore Regional Office:
40-Edward Road,
(Syed Moj Darya), Lahore.
Ph: +92-42-37350012-13,
+92-42-37324358

Faisalabad Office:
P8, 1st Floor, Street No 1-A,
Opposite GC University,
Allama Iqbal Road, Faisalabad.
Ph: +92-41-2600096,

Multan Office:
Office # 21-A, 1st Floor,
Dost Medical Complex,
Nishter Road, Multan.
Ph: +92-61-4500770

Karachi Office:
A-89, Block No 1,
KDA Scheme No 24,
Gulshan-e-Iqbal, Karachi
Ph: 92-21-34810306

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

Humidity:	≤93%
Power Supply	100-240V~, 50/60Hz□}1Hz
Battery Type:	Rechargeable Lithium-ion battery
Battery Capacity:	2200mAh
Battery Recharging Time:	Maximum 5.5 hours for charging;
Battery backup:	2 hours for continuous working

Data storage

Alarm Event Recall:	200 groups
Wave Recall:	6 hours (8 waves)
NIBP Recall:	2000 groups
Trend Graph:	160 hours
Trend Table:	160 hours
Power-off storage:	Yes
Alarm:	User-adjustable High and Low 3-level Limits; Prioritized audible and visual alarm

Respiration:

Method:	RA-LL Impedance Method
RR measurement Range	Adult: 0-120 rpm
Accuracy:	Pediatric/Neonate:0-150 rpm 7~150rpm: □}2rpm or 2%, whichever is greater 0-6rpm: unspecified
Resolution:	1 rpm
RESP Apnea	10s-60s (Adu); 10s-40s (Ped/Neo)
Alarm:	Audible and visual alarm; alarm events reviewable
Sweep Speed:	6.25,12.5,25mm/s
Gain Selection:	X0.25, X0.5, X1, X2, X4

ECG:

Lead Type:	CardioTecTM 5-leads ECG Analysis, 12-Lead and 3-leads electable
Lead selection	12-Lead I; II; III; aVR; aVL; aVF; V1-V6. 5-lead: I; II; III; aVR; aVL; aVF; V 3-lead: I; II; III
Waveform 5-lead:	2 -channel
3-lead:	1 -channel
Gain Selection:	X0.125, X0.25, X0.5, X1, X2, X4, auto

NIBP:

Method	Automatic oscillation

FRIENDS TRADERS

Head Office:
Peshawar Medical Centre, Soekarno,
Shoba Chowk, Kyhber Bazar, Peshawar.
Ph: +92-91-2211052, 2215660
Fax: 091-2592058
Email: globetradersint@gmail.com
NTN # 0713026-7

Deals in
- Electro Medical & Surgical Equipments
- Pathology items, X-Ray Machines
- Ultrasound Machines, Research Equipments
- Diagnostic Laboratory, General Lab Articles
- Glass Ware & Kits
- Universities/Colleges/Schools Equipments & Chemicals
- General Order Suppliers etc.

Ref No.: _____ Date _____

Work mode:	Manual / Automatic/Continual (5min, not applicable to neonates)
Measurement time:	Adjustable(1-480min)
Maximum measurement time	Adu/Ped: 120s; Neo: 85s
Measurement Unit:	mmHg / kPa selectable
Measurement types:	Systolic, Diastolic, Mean

COMEN SpO2:

Measurement & alarm Range	0~100%
Resolution:	1%
Accuracy:	±2% (70~100%, Adu/Ped, nonmotion) ±3% (70-100%, Neo, non-motion) Unspecified (1-69%)

Temperature (Dual Channel)

Range:	0-50°C
TEMP sensor:	Skin/rectal TEMP sensor
Resolution:	0.1°C
Accuracy:	±0.1°C (exclusive of error of sensor)
Channel:	T1, T2, TD (Temperature Difference)

Certification

- CE Certified
- FDA Certified

For Friends Traders