

FoodLoop API documentation

Public clients call the **API gateway** only (<http://localhost:8080>). Envelope: { success, message, data }.
Authenticated routes: Authorization: Bearer JWT.

Auth /api/auth

Method	Path	Auth	Purpose
POST	/api/auth/register	No	Provider or Organization. Admin rejected.
POST	/api/auth/login	No	Returns accessToken
POST	/api/auth/logout	Yes	Client discards token
GET	/api/auth/me	Yes	Current user
GET	/api/auth/admin/users	Admin	List users
PATCH	/api/auth/admin/users/:id	Admin	Activate/deactivate

Food /api/foods

Method	Path	Auth	Purpose
POST	/api/foods	Provider	Create Available listing
GET	/api/foods	Yes	Search/filter
GET	/api/foods/:id	Yes	Details
PATCH	/api/foods/:id	Provider/Admin	Update quantity and fields
POST	/api/foods/:id/claim	Verified org	Available → Reserved
POST	/api/foods/:id/collect	Claiming org	Reserved → Collected

Organizations /api/organizations

Method	Path	Auth	Purpose
POST	/api/organizations	Organization	Create profile
GET/PATCH	/api/organizations/profile	Organization	Own profile
GET	/api/organizations	Yes	Search verified

POST	/api/organizations/:id/verify	Admin	Verify
------	-------------------------------	-------	--------

Matcher /api/matching

POST /score, /find, /impact — FoodMatcher, WasteAnalyzer, SustainabilityCalculator.

AI /api/ai

POST /recommend, /rag/query, /agent. Tools: find_available_food, find_organizations, calculate_match_score, generate_match_recommendation.

Full tables: docs/api-documentation.md.