LOWER COLUMBIA RIVER GRP OCTOBER 2015

Barrett Slough (OR) L&C-2.3

Position - Location: 46° 8.239', -123° 52.084' 46° 8' 14.3", -123° 52' 5.1" 46.13731, -123.86807 Astoria

Strategy Objective: Exclusion: Keep oil out of Lewis & Clark River.

Implementation: Deploy 300' of boom across entrance to slough as backup to L&C-1.2, Lewis and Clark River strategy. Adjust angle of boom, quantity and

placement of anchors, based on conditions of the day.

Staging Area: Remote: Stage and launch at East Mooring Basin

Site Safety: Slips, trips, and falls. Water hazards.

Field Notes: Access by boat from launch at East Mooring Basin. Low flow only.

Watercourse: Slough - Lewis & Clark River

Resources at Risk: Foraging Shorebirds and Seabirds, National Park, Wintering Waterfowl



Recommended Equipment

2	Each	Anchor - Danforth (or other appropriate type)
300	Feet	Boom - B3 (River Boom) or equivalent
2	Each	Shore Connect System (posts, driver, anchor, chain, line)
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator	
2	Laborer	
1	Supervisor	

APPENDIX 4A 181