

NW entrance to Red Slough (OR)**LCR-34.4M**

Position - Location: 46° 14.456', -123° 28.728' 46° 14' 27.4", -123° 28' 43.7" 46.24094, -123.47880 Skamokawa

Strategy Objective: Exclusion : Prevent oil from entering Red Slough.

Implementation: Launch workboat from BL-LCR-33.5R with 800ft. boom. Deploy boom across the NW entrance to Red Slough and anchor at AP-1 and AP-2 using shoreside anchor posts. Anchor along boom length as necessary for conditions. Close tide gates by contacting USFWS through Wahkiakum County Sheriff.

Staging Area: Remote: Stage at SA-LCR-33.5R, Skamokawa Vista Park

Site Safety: Slips, trips, and falls. Water hazards.

Field Notes: Between Welch and Tenasillahe Islands. Boat access only.

Watercourse: Slough - Columbia River

Resources at Risk: Emergent Wetlands

**Recommended Equipment**

7 Each	Anchor - Danforth (or other appropriate type)
2 Each	Anchoring System(s)- Shoreside
800 Feet	Boom - B3 (River Boom) or equivalent
1 Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
3	Laborer
1	Supervisor