LOWER COLUMBIA RIVER GRP OCTOBER 2015

## Welch Island sloughs (OR)

Implementation:

## LCR-33.2M

Position - Location:	46° 15.366', -123° 29.146'	46° 15' 22.0", -123° 29' 8.8"	46.25610, -123.48577	Skamokawa
----------------------	----------------------------	-------------------------------	----------------------	-----------

Strategy Objective: Exclusion: Prevent oil from entering Welch Island sloughs.

Launch workboat from BL-LCR-33.5R, Skamokawa Vista Park, with 400ft. boom. Deploy boom across the entrance to the slough on the northwest corner of Welch Island. Anchor at AP-1 and AP-2 using shoreside anchor posts. Anchor along boom length as necessary for

conditions.

Staging Area: Remote: Stage at Skamokawa Vista Park, SA-LCR-33.5R

**Site Safety:** Slips, trips, and falls. Water hazards.

Field Notes: Boat access only from Skamokawa Vista Park

Watercourse: Slough - Columbia River

Resources at Risk: National Wildlife Refuge, Sensitive Wetland Habitat



## **Recommended Equipment**

3	Each	Anchor - Danforth (or other appropriate type)	
2	Each	Anchoring System(s)- Shoreside	
400	Feet	Boom - B3 (River Boom) or equivalent	
1	Each	Workboat(s) - of adequate size for type and amount of boom	

## **Recommended Personnel**

1 Boat Operator	
2 Laborer	
1 Supervisor	

APPENDIX 4A 231