LOWER COLUMBIA RIVER GRP OCTOBER 2015

Coal Creek Slough (WA)

LCR-55.9R

Position - Location: 46° 11.377	7', -123° 6.981' 46° 11' 2	2.6", -123° 6' 58.9" 46.18961	., -123.11635 Longview
--	----------------------------	-------------------------------	------------------------

Strategy Objective: Exclusion: Prevent oil from entering Coal Creek Slough.

Implementation: Launch workboat with 500ft. boom from Willow Grove boat launch, BL-LCR-57.8R. Deploy boom across mouth of Coal Creek Slough.

Anchor to AP-1 and AP-2 using natural anchor points or shoreside anchor posts. Anchor every 100-150ft. along boom length or as

necessary for conditions. It may be necessary to tend boom due to vessel traffic in the area.

Staging Area: Remote: Stage at SA-LCR-57.8R, Willow Grove County Park

Site Safety: Slips, trips, and falls. Water hazards. Frequent boat traffic in Coal Creek Slough. Highway 4 is very busy and lacks shoulders.

Field Notes: Boat access only. Site is at the mouth of Coal Creek Slough.

Watercourse: River - With Tidal Influence - Columbia River

Resources at Risk: Slough and Marsh Habitat, Wetland Habitat



Recommended Equipment

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
500	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1 Boat Operator	
2 Laborer	
1 Supervisor	

APPENDIX 4A 319