

Slaughters Dike (OR)**LCR-64.4L**

Position - Location: 46° 7.098', -122° 59.417' 46° 7' 5.9", -122° 59' 25.0" 46.11830, -122.99029 Rainier

Strategy Objective: Collection : Prevent oil from moving downstream.

Implementation: Launch workboat from Rainier City Marina or beach onsite with 600 ft. boom. Deploy boom at an angle upriver to collect oil and anchor at AP-1 using shoreside anchor posts. Anchor at AP-2 using Danforth or other anchor and every 100-150ft. along boom length or as necessary for conditions. Recover with a vac truck staged on site at Slaughters Dike.

Staging Area: Remote: Stage at SA-LCR-67.1L, Rainier City Marina. Launch at same BL-LCR-67.1L or from beach onsite.

Site Safety: Slips, trips, and falls. Recreational boat traffic and pillings in river.

Field Notes: Good vehicle access with sandy beach for recovery.

Watercourse: River - With Tidal Influence - Columbia River

Resources at Risk: Downstream Resources

**Recommended Equipment**

5	Each	Anchor - Danforth (or other appropriate type)
1	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Vac Truck or Skimmer and Storage
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor