LOWER COLUMBIA RIVER GRP OCTOBER 2015

Red Slough - NW Tenasillahe Island (OR)

LCR-34.7M

Position - Location: 46° 14.114', -123° 28.645' 46° 14' 6.9", -123° 28' 38.7" 46.23524, -123.47741 Skamokawa

Strategy Objective: Exclusion: Prevent oil from entering slough on west end of Tenasillahe Island.

Implementation: Launch workboat from BL-LCR-33.5R with 600ft. boom. Deploy boom across the SW entrance to Red Slough and anchor at AP-1 and AP-

2 using shoreside anchor posts. Anchor along boom length as necessary for conditions. Close tide gates by contacting USFWS through

Wahkiakum County Sheriff (360) 795-3911.

Staging Area: Remote: Stage at SA-LCR-33.5R, Skamokawa Vista Park

Site Safety: Slips, trips, and falls. Water hazards.

Field Notes: Boat access only between Welch and Tenasillahe Islands (OR).

Watercourse: Slough - Columbia River

Resources at Risk: Emergent Wetlands



Recommended Equipment

5	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
3	Laborer
1	Supervisor

APPENDIX 4A 243