

Goat Island - S end (OR)**LCR-81.8L**

Position - Location: 45° 55.554', -122° 48.933' 45° 55' 33.2", -122° 48' 56.0" 45.92590, -122.81556 Longview

Strategy Objective: Exclusion : Prevent oil from entering slough behind Goat Island.

Implementation: Launch workboat from Woodland Bottoms boat launch, BL-LCR-82.1R, with 900ft. boom. Deploy boom across the south end of the slough behind Goat Island. Anchor to AP-1 and AP-2 using natural anchors or shoreside anchor posts and anchor every 100-150ft. along boom length or as necessary for conditions.

Staging Area: Remote: Stage at Woodland Bottoms, SA-LCR-82.1R

Site Safety: Water hazards. Slips, trips, and falls.

Field Notes: Boat access only. Water is shallow with moving sand bars. Amount of boom needed will vary greatly depending on flow conditions.

Watercourse: Slough - Goat Island Slough

Resources at Risk: Geese (Summer), Waterfowl (Wintering)

**Recommended Equipment**

8 Each	Anchor - Danforth (or other appropriate type)
2 Each	Anchoring System(s)- Shoreside
900 Feet	Boom - B2 (Contractor Boom) or equivalent
1 Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor