LOWER COLUMBIA RIVER GRP OCTOBER 2015

John Slough (OR) LCR-55.4L

Position - Location: 46° 10.154', -123° 8.776' 46° 10' 9.2", -123° 8' 46.6" 46.16923, -123.14627 Clatskanie

Strategy Objective: Exclusion: Prevent oil from entering John Slough.

Implementation:

Launch workboat with 200ft. boom and shallow-water skiff from Port Westward boat launch, BL-LCR-53.8L. Use shallow-water skiff to deploy boom across Judson Slough. Anchor to AP-1 and AP-2 using shoreside anchor posts. Anchor along boom length as necessary for conditions.

Staging Area: Remote: Stage at Port Westward boat launch, SA-LCR-53.8L. Launch from same BL-LCR-53.8L.

Site Safety: Water hazard, slips, trips, falls.

Field Notes: Best access to this strategy is by boat, but there is limited vehicle access from Kallunki Rd. Water is very shallow in this area. Strategy

may not be feasible at low water.

Watercourse: Slough - John Slough

Resources at Risk: Wetland Habitat



Recommended Equipment

1	Each	Anchor - Danforth
2	Each	Anchoring System(s)- Shoreside
200	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom
1	Each	Workboat(s) - (jon boat)

Recommended Personnel

2 Boat Operator
2 Laborer
1 Supervisor

APPENDIX 4A 311