LOWER COLUMBIA RIVER GRP OCTOBER 2015

Carrolls Channel - S End (WA)

LCR-71.5M

Strategy Objective: Collection: Collect and recover oil at south end of Carrolls Channel.

Implementation:

From BL-LCR-72.7R, launch workboat to the south end of Cottonwood Island with two 700ft. lengths of boom. Angle BM-1 upriver into main channel to collect oil, and BM-2 across Carrolls Channel to enhance collection. Anchor at AP-1 and AP-3 using shoreside anchor posts. Anchor at AP-2 and AP-4, and every 100-150ft. along boom length or as appropriate for conditions. Collect oil in collection pocker using portable skimmer and storage.

Staging Area: Remote: Stage at SA-LCR-72.7R, Sportsmen's Club

Site Safety: Shallow water and pillings. Recreational and commercial boat traffic.

Field Notes: Boat access only. Large beach area.

Watercourse: River - With Tidal Influence - Carrolls Channel

Resources at Risk: Downstream Habitat, Wetland Habitat



Recommended Equipment

12	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
1400	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Skimmer (appropriately sized) with Portable Storage
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor

APPENDIX 4A 345