

**Grizzly Slough (OR)****LCR-27.9L**

**Position - Location:** 46° 12.198', -123° 34.000' 46° 12' 11.9", -123° 33' 60.0" 46.20330, -123.56667 Astoria

**Strategy Objective:** Exclusion : Prevent oil from entering Grizzly Slough.

**Implementation:** From BL-LCR-17.7L, launch shallow-water skiff and workboat with 500ft. boom to the mouth of Grizzly Slough (on interior of Blind Slough). Using skiff to pull boom from workboat, deploy boom across the mouth of the slough and anchor at AP-1, AP-2 using natural anchor points or shoreside anchor posts. Anchor along boom length as necessary for conditions.

**Staging Area:** Remote: Stage at SA-LCR-17.7L Tongue Point, launch from same BL-LCR-17.7L.

**Site Safety:** Slips, trips, and falls. Water hazards.

**Field Notes:** Boat access only through Blind Slough, just downstream of swing bridge.

**Watercourse:** Slough - Columbia River

**Resources at Risk:** Sensitive Wetland Area

**Recommended Equipment**

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
500	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom
1	Each	Workboat(s) - (jon boat)

**Recommended Personnel**

2	Boat Operator
2	Laborer
1	Supervisor