

Wallace Island Slough - SW end (OR)

LCR-48.6M

Position - Location: 46° 8.243', -123° 15.852' 46° 8' 14.6", -123° 15' 51.1" 46.13738, -123.26420 Westport

Strategy Objective: Exclusion : Prevent oil from entering slough on SW end of Wallace Island.

Implementation: Launch workboat with 500ft. boom and shallow-water skiff from Westport boat launch, BL-LCR-43.8L. Using shallow-water skiff, deploy boom across the entrance to the channel on the southwest end of Wallace Island. Anchor to AP-1 and AP-2 using shoreside anchor posts or natural anchors. Anchor along boom length as necessary for conditions.

Staging Area: Remote: Stage at Westport boat ramp, SA-LCR-43.8L. Launch from same BL-LCR-43.8L.

Site Safety: Shallow water, slips, trips, falls, water hazard.

Field Notes: Boat access only. Water is very shallow in this area and at low water booming may not be feasible or necessary.

Watercourse: Slough - Wallace Island Slough

Resources at Risk: Mudflat Habitat, Whitetail Deer Habitat, Whitetail Deer Habitat



Recommended Equipment

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
500	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom
1	Each	Workboat(s) - (jon boat)

Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor