

## Outer Skipanon Waterway (OR)

LCR-10.9L

**Position - Location:** 46° 10.901', -123° 54.473' 46° 10' 54.1", -123° 54' 28.4" 46.18169, -123.90788 Warrenton

**Strategy Objective:** Collection, Deflection : Divert oil to shore for collection.Strategy will work well with a NW wind and a flood tide.

**Implementation:** Launch boat at Warrenton Marina BL-SKPR-1.4. Angle 600 ft of boom into current to deflect oil to collection point on south shoreline at sandy beach. Should be able to get a vac truck to the water, bring bolt cutters in case gate is locked.

**Staging Area:** Remote: Stage + launch at Warrenton Marina BL-SKPR-1.4, approximately 1 mile upriver

**Site Safety:** Slips, trips, and falls. Water hazards.

**Field Notes:** Boat can only reach site during high tide.

**Watercourse:** River - Without a Dam - Skipanon River

**Resources at Risk:** Salmon Concentrations and Habitat



## Recommended Equipment

5	Each	Anchor - Danforth (or other appropriate type)
600	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Shore Connect System (posts, driver, anchor, chain, line)
1	Each	Vac Truck or Skimmer and Storage (if collection)
1	Each	Workboat(s) - of adequate size for type and amount of boom

## Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor