

**Blind Slough Net Pens (OR)****LCR-29.0L**

**Position - Location:** 46° 12.166', -123° 32.661' 46° 12' 10.0", -123° 32' 39.6" 46.20277, -123.54434 Astoria

**Strategy Objective:** Exclusion : Prevent oiling of net pens.

**Implementation:** From BL-LCR-17.7L, Crew 2 launch workboat with 500ft. boom. Crew 1 drive to net pens on Penttila Rd. Crew 2 place boom around the net pens and pass line attached to boom to Crew 1. Crew 1 anchor both ends of boom to the shore at AP-1 and AP-4 to the north of the pens. Crew 2 anchor to AP-2 and AP-3 using Danforth or other appropriate anchors. Anchor along boom length as appropriate for conditions.

**Staging Area:** Remote: Stage at SA-LCR-17.7L Tongue Point, launch from same BL-LCR-17.7L.

**Site Safety:** Slips, trips, and falls. Water hazards.

**Field Notes:** Site is fish net pens on Blind Slough, just west of bridge. Land access from dock at 43201 Penttila Ln, Astoria, OR, 97103

**Watercourse:** Slough - Columbia River

**Resources at Risk:** Fish Pens

**Recommended Equipment**

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
500	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

**Recommended Personnel**

1	Boat Operator
4	Laborer
1	Supervisor