LOWER COLUMBIA RIVER GRP OCTOBER 2015

Clifton Channel (OR) LCR-38.2L

Position - Location: 46° 12.473', -123° 27.152' 46° 12' 28.4", -123° 27' 9.1" 46.20789, -123.45253 Cathlamet

Strategy Objective: Collection, Deflection: Collect oil/Prevent oil from continuing downstream.

Implementation: Deploy 500 ft of boom from Clifton for collection of oil that enters the channel. Boom needs to be tended, current is 2-4 knots, strong

winds are common. Collect using skimmer and portable storage.

Staging Area: Remote: Stage at SA-LCR-38.6R, Elochoman Slough Marina

Site Safety: Slips, trips, and falls. Water hazards. Strong current through Channel.Log rafts may be present in this area.

Field Notes: Vehicle access from Clifton Road and railroad access along bank.

Watercourse: River - With Tidal Influence - Columbia River

Resources at Risk: Emergent Wetlands



Recommended Equipment

4	Each	Anchor - Danforth (or other appropriate type)		
1	Each	Anchoring System(s)- Shoreside		
500	Feet	Boom - B3 (River Boom) or equivalent		
1	Each	Skimmer (appropriately sized) with Portable Storage		
1	Each	Workboat(s) - of adequate size for type and amount of boom		

Recommended Personnel

1	Boat Operator	
3	Laborer	
1	Supervisor	

APPENDIX 4A 259