

Steamboat Slough - (WA)**LCR-33.7R**

Position - Location: 46° 15.998', -123° 27.223' 46° 15' 59.9", -123° 27' 13.4" 46.26664, -123.45372 Skamokawa

Strategy Objective: Collection, Diversion : Divert oil out of main channel to collection point.

Implementation: Crew 2 launch workboat from BL-LCR-33.5 with 1000 ft of boom. Meet Crew 1 at hotel at mouth of slough on slough right. Crew 1 remain on shore and use line-throwing gun or other means to transfer line attached to boom to Crew 2. Crew 1 anchor to AP-1 at Skamokawa Inn using shoreside anchor posts. Crew 2, deploy boom in a chevron formation, anchor at AP-2 and AP-3 to create diversion and collection angles. Collect oil using vac truck staged at parking area at hotel.

Staging Area: Onsite: Stage at parking lot for hotel. Launch boat from Skamokawa Vista Park, BL-LCR-33.5R.

Site Safety: Slips, trips, and falls. Use caution navigating around pilings and other potential submerged debris.

Field Notes: Site at hotel with docks and parking area for staging vac truck. Notify hotel operator of any response actions on this property.

Watercourse: Slough - Steamboat Slough

Resources at Risk: Shorebird Concentrations, Wetland Habitat, Whitetail Deer Habitat, Wildlife Refuge

**Recommended Equipment**

9 Each	Anchor - Danforth (or other appropriate type)
1 Each	Anchoring System(s)- Shoreside
1000 Feet	Boom - B2 (Contractor Boom) or equivalent
1 Each	Line throwing gun(s) or device(s)
1 Each	Vac Truck or Skimmer and Storage
1 Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
4	Laborer
1	Supervisor