LOWER COLUMBIA RIVER GRP OCTOBER 2015

## Welch Island sloughs (OR)

## LCR-33.3M

Position - Location:	46° 15.184′, -123° 29.081′	46° 15' 11.1", -123° 29' 4.8"	46.25307, -123.48468	Skamokawa
----------------------	----------------------------	-------------------------------	----------------------	-----------

Strategy Objective: Exclusion: Prevent oil from entering Welch Island sloughs.

Implementation: Launch workboat from Skamokawa Vista Park, BL-LCR-33.5R with 400ft. boom. Deploy boom across the west entrance of the slough

that runs through the middle of Welch Island. Anchor to AP-1 and AP-2 using shoreside anchor posts. Anchor along boom length as

necessary for conditions.

Staging Area: Remote: Stage at Skamokawa Vista Park, SA-LCR-33.5R

**Site Safety:** Slips, trips, and falls. Water hazards.

Field Notes: Boat access only from Skamokawa Vista Park.

Watercourse: Slough - Columbia River

Resources at Risk: National Wildlife Refuge, Sensitive Wetland Habitat



## Recommended Equipment

3	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
400	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

## **Recommended Personnel**

1	Boat Operator
2	Laborer
1	Supervisor

APPENDIX 4A 233