

Swash Lake (OR)**LCR-7.5L**

Position - Location: 46° 12.653', -123° 58.432' 46° 12' 39.2", -123° 58' 25.9" 46.21088, -123.97387 Warrenton

Strategy Objective: Exclusion : Prevent oil from entering tidal creeks or Swash Lake.

Implementation: Deploy if tidal conditions allow; keep workboat outside of lagoon and use shallow-water skiff to deploy 500' of boom across mouth of creek and anchor at AP-1 and AP-2 using shoreside anchor posts, do not anchor to historic pilings. Anchor every 100-150ft. along boom length or as necessary for conditions.

Staging Area: Remote: Stage at SA-LCR-8.7L Hammond Marina, launch at same BL-LCR-8.7L.

Site Safety: Shallow water with pilings. Slips, trips, and falls. Water hazards.

Field Notes: Creek connects Jetty Lagoon to Swash Lake to the south. Mouth of creek is very shallow at low water and may not be accessible except for high water. Pilings and jetty to NE of strategy.

Watercourse: Creek - Swash Lake

Resources at Risk: Waterfowl and Shorebird Concentrations, Wetland Habitat

**Recommended Equipment**

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
500	Feet	Boom - B3 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom
1	Each	Workboat(s) - (jon boat)

Recommended Personnel

2	Boat Operator
3	Laborer
1	Supervisor