LOWER COLUMBIA RIVER GRP OCTOBER 2015

Abernathy Creek (WA) LCR-54.2R

Position - Location: 46° 11.455′, -123° 10.	14' 46° 11' 27.3", -123° 10' 2.6"	46.19092, -123.16740	Clatskanie
--	-----------------------------------	----------------------	------------

Strategy Objective: Exclusion: Prevent oil from entering Abernathy Creek.

Implementation:

Launch workboat with 100ft. boom and shallow-water skiff from Port Westward boat launch, BL-LCR-53.8L. Use shallow-water skiff to boom off mouth of creek. Anchor at AP-1 and AP-2 to large boulders and trees- do not use anchor posts in this area. Anchor along boom length as necessary for conditions. Minimize disturbance of shoreline and back-beach areas around creek mouth. Keep vehicles on established roads. Notify Environmental Unit if deploying this strategy.

Staging Area:	Remote: Stage at Port Westward boat launch, SA-LCR-53.8L. Launch from same BL-LCR-53.8L.
Stuging Area.	remote. Stage at Port Westward boat iduntif, SA-LCR-33.6L. Eduntif from Same BL-LC

Slips, trips, and falls. Water hazards. Heavy vehicle traffic on WA-4.

Field Notes: Strategy site has limited vehicle access but is best accessed via boat. Do not use stakes or anchor posts in this area.

Watercourse: River - With Tidal Influence - Columbia River

Resources at Risk: Herons and Other Wading Birds, Salmon Concentrations and Habitat, Sensitive Resources Nearby, Sensitive Shoreline and Back-Beach,



Recommended Equipment

2	Each	Anchor - Danforth (or other appropriate type)
300	Feet	Boom - B3 (River Boom) or equivalent
2	Each	Bridle(s) - Piling (appropriately sized for boom)
1	Each	Workboat(s) - of adequate size for type and amount of boom
1	Each	Workboat(s) - (jon boat)

Recommended Personnel

2 Boat Operator
2 Laborer
1 Supervisor

APPENDIX 4A 303