LOWER COLUMBIA RIVER GRP OCTOBER 2015

Cook Slough (OR) YOR-3.6L

Position - Location: 46° 9.713', -123° 49.869' 46° 9' 42.8", -123° 49' 52.2" 46.16188, -123.83116 Astoria

Strategy Objective: Exclusion: Prevent oil from travelling through tidegate on Cook Slough during incoming tide.

Implementation: From Wireless Rd., hand launch boat to deploy 100ft. of boom in a chevron configuration on either side of tidegate on Cook Slough.

Anchor at AP-1 and AP-2 using shoreside anchor posts. Anchor at AP-3 using Danforth or other appropriate anchor.

Staging Area: Onsite: Stage onsite from Wireless Road.

Site Safety: Slips, trips, and falls. Water hazards.

Field Notes: Site is accessed through private property. Make contact with land owner before deploying strategy.

Watercourse: Slough - Cook Slough

Resources at Risk: Wetland Habitat



Recommended Equipment

1	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
100	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - (hand-launch)

Recommended Personnel

1 Boat Operator	
2 Laborer	
1 Supervisor	

APPENDIX 4A 547