

Fisher's Landing (WA)**LCR-115.0R**

Position - Location: 45° 35.213', -122° 30.257' 45° 35' 12.8", -122° 30' 15.4" 45.58689, -122.50429 Fairview

Strategy Objective: Exclusion : Prevent oil moving downstream from impacting shore at this site.

Implementation: Launch workboat from BL-LCR-118.5L, Port of Camas-Washougal, with 600ft. boom. Anchor to shore at AP-1 upstream of promontory using natural anchor points. Anchor at AP-2 downstream of the promontory and anchor to shore using available trees or natural anchor points. Anchor apex at AP-3 using Danforth or other appropriate anchor and anchor along boom length every 100-150ft. or as appropriate for conditions. Contact Environmental Unit for guidance before deploying this strategy.

Staging Area: Remote: Stage from Chinook Landing Marine Park, SA-LCR-118.5L. Launch from same BL-LCR-118.5L.

Site Safety: Water hazards, slips, trips, falls.

Field Notes: Site is at rocky promontory. Sensitive resources exist at this site. Use only trees or driftwood for natural anchors. Do not anchor using boulders or anchor posts. Contact Environmental Unit for guidance.

Watercourse: River - Below a Dam - Columbia River

Resources at Risk: Fish and Wildlife Resources, Sensitive Resources

**Recommended Equipment**

4	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B3 (River Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator
2	Laborer
1	Supervisor