LOWER COLUMBIA RIVER GRP OCTOBER 2015

Clatskanie River - W side (OR)

LCR-49.8L

Position - Location: 46	5° 8.505', -123° 13.832'	46° 8' 30.3", -123° 13' 49.9"	46.14176, -123.23053	Clatskanie
-------------------------	--------------------------	-------------------------------	----------------------	------------

Strategy Objective: Collection: Divert oil to shoreline for collection.

Implementation:

Launch workboat from Port Westward boat launch, BL-LCR-53.8L with 600ft. boom. Anchor boom upstream of the Clatskanie River mouth at AP-1, angled into main channel of the Columbia River at AP-2 to divert oil to shore for collection. Anchor at AP-1 to pilings or using shoreside anchor posts. Extend boom N to anchor at AP-2 using Danforth or other anchor. Anchor every 100-150ft. along boom length or as necessary for conditions. Collect oil using vac truck at private property.

Staging Area:	Remote: Stage at Port Westward boat launch, BL-LCR-53.8L. Launch from same BL-	LCR-53.8L.
---------------	--	------------

Site Safety: Water hazards, slips, trips, falls.

Field Notes: Contact property owner before deploying. Site is at the confluence of Clatskanie River with Lower Columbia River and is surrounded by private agricultural property. May also be referred to as Beaver Slough. Strategy works together with exclusion at LCR-49.7L.

Watercourse: River - With Tidal Influence - Clatskanie River

Resources at Risk: Osprey Nest(s), Salmon Concentrations and Habitat, Wetlands



Recommended Equipment

5	Each	Anchor - Danforth (or other appropriate type)
1	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Skimmer (appropriately sized) with Portable Storage
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1	Boat Operator	
2	Laborer	
1	Supervisor	

APPENDIX 4A 297