LOWER COLUMBIA RIVER GRP OCTOBER 2015

## **Puget Island/ Welcome Slough (WA)**

## LCR-41.3M

**Position - Location:** 46° 10.301', -123° 24.327' 46° 10' 18.0", -123° 24' 19.6" 46.17168, -123.40544 Cathlamet

Strategy Objective: Exclusion: Prevent oil from entering Welcome Slough.

Implementation: From BL-LCR-41.8M, launch workboat to mouth of Welcome Slough with 600ft of boom. Deploy boom in a chevron formation. Anchor

to AP-1 and AP-2 using shoreside anchor posts. Anchor to AP-3 using Danforth or other acceptable anchor, and anchor every 100-150ft.

along boom length or as appropriate for conditions.

Staging Area: Remote: Stage at Svenson Park Boat Launch, SA-LCR-41.8M

Site Safety: Slips, trips, and falls. Water hazards. Possible recreational vessel traffic in the area.

Field Notes: Mouth of Welcome Slough, which has many private homes, docks, and recreational vessels.

Watercourse: Slough - Welcome Slough

**Resources at Risk:** Economic Resource



## **Recommended Equipment**

5	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

## **Recommended Personnel**

1 Boat Operator	
2 Laborer	
1 Supervisor	

APPENDIX 4A 269