LOWER COLUMBIA RIVER GRP OCTOBER 2015

Clatskanie River - E side (OR)

LCR-49.7L

Position - Location:	46° 8.361′, -123° 13.860′	46° 8' 21.7", -123° 13' 51.6"	46.13935, -123.23099	Clatskanie
----------------------	---------------------------	-------------------------------	----------------------	------------

Strategy Objective: Exclusion: Prevent oil from entering the Clatskanie River.

Implementation: Launch workboat from Port Westward boat launch, BL-LCR-53.8L with 600ft. boom. Deploy boom across the mouth of the Clatskanie

River. Anchor at AP-1 and AP-2 using shoreside anchor posts or natural anchors. Anchor every 100-150ft. along boom length or as necessary for conditions.

Remote: Stage at Port Westward boat launch, SA-LCR-53.8L. Launch from same BL-LCR-53.8L.

Site Safety: Water hazard, slips, trips, falls.

Staging Area:

Field Notes: Site is at the mouth of the Clatskanie River at the Columbia River. May also be referred to as Beaver Slough. Strategy works together

with collection at LCR-49.6L.

Watercourse: River - With Tidal Influence - Clatskanie River

Resources at Risk: Osprey Nest(s), Salmon Concentrations and Habitat, Wetlands



Recommended Equipment

5	Each	Anchor - Danforth (or other appropriate type)
2	Each	Anchoring System(s)- Shoreside
600	Feet	Boom - B2 (Contractor Boom) or equivalent
1	Each	Workboat(s) - of adequate size for type and amount of boom

Recommended Personnel

1 B	Boat Operator
2 L	Laborer
1 S	Supervisor

APPENDIX 4A 295