

**Inner Skipanon Waterway (OR)****LCR-10.8L**

**Position - Location:** 46° 10.786', -123° 54.562' 46° 10' 47.2", -123° 54' 33.7" 46.17977, -123.90937 Warrenton

**Strategy Objective:** Exclusion : Keep oil out of inner waterway.

**Implementation:** Launch boat at Warrenton Marina BL-SKPR-1.4. Deploy 800' of boom across waterway using shoreside connector systems on either side and Danforth type anchors every 100-150' depending on conditions of the day. Strategy will work well with a NW wind and a flood tide.

**Staging Area:** Remote: Stage + launch at Warrenton Marina SA-SKPR-1.4, approximately 1 mile upriver

**Site Safety:** Slips, trips, and falls.

**Field Notes:** Access via sandy spit collection points. Low flow only.

**Watercourse:** River - Without a Dam - Skipanon River

**Resources at Risk:** Salmonid Concentrations and Habitat

**Recommended Equipment**

7 Kit	Anchoring System(s) - (anchor, lines, floats)
800 Feet	Boom - B2 (Contractor Boom) or equivalent
2 Each	Shore Connect System (posts, driver, anchor, chain, line)
1 Each	Workboat(s) - of adequate size for type and amount of boom

**Recommended Personnel**

1	Boat Operator
3	Laborer
1	Supervisor