

Cluster Command - Breakdown

```
gcloud dataproc clusters create ads-cluster1
--enable-component-gateway
--bucket adurukansonmez-5132
--region us-central1
--zone us-central1-f
--master-machine-type n1-standard-2 --master-boot-disk-size 30
--num-workers 2 --worker-machine-type n1-standard-2 --worker-boot-disk-size 30
--image-version 2.0-ubuntu18
--optional-components JUPYTER
--scopes 'https://www.googleapis.com/auth/cloud-platform'
--max-idle 14400s
--project adurukansonmez-5132-project
--initialization-actions gs://goog-dataproc-initialization-actions-us-central1/hue/hue.sh
```

Cluster Command

```
gcloud dataproc clusters create ads-cluster1 --enable-component-  
gateway --bucket adurukansonmez-5132 --region us-central1 --zone us-  
central1-f --master-machine-type n1-standard-2 --master-boot-disk-  
size 30 --num-workers 2 --worker-machine-type n1-standard-2 --  
worker-boot-disk-size 30 --image-version 2.0-ubuntu18 --optional-  
components JUPYTER --scopes  
'https://www.googleapis.com/auth/cloud-platform' --max-idle 14400s -  
-project adurukansonmez-5132-project --initialization-actions  
gs://goog-dataproc-initialization-actions-us-central1/hue/hue.sh
```