

1. ★ API with Express Server - LaunchX
 1. Dependencies
 2. Routes
2. End-point: localhost:3000/v1/explorers
 1. Method: GET
 2. Body (raw)
 3. Output
4. End-point: localhost:3000/v1/explorers/1
 1. Method: GET
5. End-point: localhost:3000/v1/explorers
 1. Method: POST
 2. Body (raw)
 3. Output
6. End-point: localhost:3000/v1/explorers/:id
 1. Method: PUT
 2. Body (raw)
 3. Output
7. End-point: localhost:3000/v1/explorers/1
 1. Method: DELETE
 2. Output

★ API with Express Server - LaunchX

Requerimientos

```
API Express Server testing all HTTP Methods
```

Dependencies

Dependencies

- Express

Scripts

- npm start - to run express Server

Routes

Route	Method	Expected
/v1/explorers	GET	All Explorers
/v1/explorers/:id	GET	Specific explorer
/v1/explorers/	POST	Create explorer
/v1/explorers/	PUT	Update explorer
/v1/explorers/	DEL	Delete explorer

This endpoints are from Express API LaunchX, to test HTTP methods with test enviroment.

End-point: localhost:3000/v1/explorers

Method: GET

```
localhost:3000/v1/explorers
```

Body (raw)

Output

Object array with all users.

```
1  [
2    {
3      "id": 1,
4      "name": "Dann1"
5    },
6    {
7      "id": 2,
8      "name": "Dann2"
9    },
10   {
11     "id": 3,
12     "name": "Dann3"
13   },
14   {
15     "id": 4,
16     "name": "Dann4"
17   }
18 ]
```

End-point:
localhost:3000/v1/explorers/1

Method: GET

localhost:3000/v1/explorers/1

End-point: localhost:3000/v1/explorers

Method: POST

localhost:3000/v1/explorers

Body (raw)

```
{  
  "name": "dann"  
}
```

Output

End-point:
localhost:3000/v1/explorers/:id

Method: PUT

localhost:3000/v1/explorers/1

Body (raw)

```
{"name": "danno"}
```

Output

End-point:
localhost:3000/v1/explorers/1

Method: DELETE

localhost:3000/v1/explorers/1

Output

.....