

Edges

Edge detection: local operation to determine intensity changes

Good edge detector:

Understand the difference between:

1. Variance caused by image **noise**
2. Variance caused by **textures**
3. Variance caused by **true edges**

Edge detection

1. Differential methods: gradient, laplacian
2. Template methods: roberts, prewit, sobel, kirsch
3. Optimisation methods: canny

Edges and derivatives

1st derivative: $[-1 \ 1]$

$$f'(x) = \lim_{h \rightarrow 0} \frac{f(x+h) - f(x)}{h} \approx f(x+1) - f(x) \quad (h=1)$$

mask: $[-1 \ 1]$

Backward difference, forward difference, central difference

2st derivative: $[1 \ -2 \ 1]$

$$f''(x) = \lim_{h \rightarrow 0} \frac{f'(x+h) - f'(x)}{h} \approx f'(x+1) - f'(x) = f(x+2) - 2f(x+1) + f(x) \quad (h=1)$$

• This approximation is **centered** about $x+1$; by replacing $x+1$ by x we obtain:

$$f''(x) \approx f(x+1) - 2f(x) + f(x-1)$$

mask: $[1 \ -2 \ 1]$

1st derivative: edge is well detected, but **location** is **imprecise**,

- **ramp edge** yield a **weak** response
- Impulse response is a “whip”

S_3				12	12	12	12	15	18	21	24	24	24
S_3	\otimes	M		0	0	0	3	6	6	6	3	0	0

(c) S_3 is an upward ramp

2nd derivative: “double whip” amplifies and **locates** the step edge

Derivative based edge detectors are **sensitive to noise**

Gradient filters

- The magnitude of gradient provides information about the strength of the edge
- The direction of gradient is **perpendicular** to the direction of the edge

$$\nabla f(x, y) = \begin{bmatrix} G_x \\ G_y \end{bmatrix} = \begin{bmatrix} \frac{\partial f(x, y)}{\partial x} \\ \frac{\partial f(x, y)}{\partial y} \end{bmatrix} \quad \begin{aligned} \frac{\partial f}{\partial x} &= \frac{f(x+h_x, y) - f(x, y)}{h_x} = f(x+1, y) - f(x, y), & (h_x = 1) \\ \frac{\partial f}{\partial y} &= \frac{f(x, y+h_y) - f(x, y)}{h_y} = f(x, y+1) - f(x, y), & (h_y = 1) \end{aligned}$$

Roberts: gradient across diagonals, fast, do not have a clear center

-1	0	0	-1
0	1	1	0

Prewitt: simpler to implement

-1	-1	-1	-1	0	1
0	0	0	-1	0	1
1	1	1	-1	0	1

Sobel: a weight of **2** for **smoothing**, superior **noise-suppression** than prewitt

-1	-2	-1	-1	0	1
0	0	0	-2	0	2
1	2	1	-1	0	1

Laplacian filters

Isotropic, **very sensitive to noise**


$$\nabla^2 f(x, y) = \frac{\partial^2 f(x, y)}{\partial x^2} + \frac{\partial^2 f(x, y)}{\partial y^2}$$

$$\frac{\partial^2 f(x, y)}{\partial x^2} \cong f(x+1, y) + f(x-1, y) - 2f(x, y)$$

$$\frac{\partial^2 f(x, y)}{\partial y^2} \cong f(x, y+1) + f(x, y-1) - 2f(x, y)$$

$$\nabla^2 f = [f(x+1, y) + f(x-1, y) + f(x, y+1) + f(x, y-1)] - 4f(x, y)$$

0	1	0
1	-4	1
0	1	0




Properties of Laplacian

1. Isotropic
2. Cheaper to implement
3. Does **not** provide information about **edge direction**
4. Sensitive to noise

Unsharp masking

Mach bands — a phenomenon in human vision, the true brightness on the left, perceived on the right



Unsharp masking create **artificial mach band**

Unsharp masking (过程):

1. **Blurring** the original
2. **Subtracting** the blurred image from the original
3. **Adding** the mask to the original

Is — blurring, I-Is — details, I+(I-Is) — improve image details

Laplacian of Gaussian (LoG)

De-noise should be done first, gaussian **smooth** it

Convolution is **associative** —> the **sequence** of laplacian and Gaussian does not matter

The laplacian of Gaussian

$$\nabla^2 G(r) = \left[\frac{r^2 - s^2}{s^4} \right] e^{-\frac{r^2}{2s^2}}$$

Marr-Hildreth method: different variance of gaussian —> zero-crossing

Approximation of the LoG operator: The LoG = DoG — **difference of gaussians**

DoG: difference of two differently sized gaussians

LoG response — zero crossings

LoG response	Result
0	At a long distance from the edge
>0	One side of the edge
<0	Another side of the edge
0	On the edge itself

Canny edge detector

Canny — the first derivative of the Gaussian closely approximates the operator that optimizes the product of SNR and localization

Flow Chart

1. Smooth by gaussian convolution
2. Differential operators along x and y axis
3. **Non-maximum suppression** — find peaks in the image gradient
4. **Hysteresis** thresholding locates edge strings

Non-maxima suppression

Check if gradient magnitude at pixel location (i, j) is **local maximum** along gradient direction

作用: thinning → narrowing the edge

Hysteresis thresholding: two threshold t_l , t_h

$$\begin{array}{ll} \|\nabla f(x, y)\| \geq t_h & \text{definitely an edge} \\ t_l \leq \|\nabla f(x, y)\| < t_h & \text{maybe an edge, depends on context} \\ \|\nabla f(x, y)\| < t_l & \text{definitely not an edge} \end{array}$$

- High threshold — start edge curves
- Low threshold — continue them

Multi-scale processing

Multi-scale processing: determine which structures (edges) are **most significant** by considering **the range of scales** over which they occur

Interesting scale — scales at which important structures are present

The choice of σ depends on desired behavior

- large σ detects large scale edges
- small σ detects fine features

Image segmentation approaches

- Thresholding
- Region based segmentation

Thresholding

- Global Thresholding
- Adaptive Thresholding — subdivision

Region based segmentation

- Region growing
- Region splitting

Region growing:

Start from some pixels (**seeds**) representing distinct **image regions** and to form them, until they cover the entire image. Stop until no more pixels satisfy the criteria for inclusion in that region.

Region splitting

1. First there is a large region (the entire image)
2. A **predicate** is used to determine if the region is **uniform**
3. **If not**, then the method requires the region be split into two regions
4. Then each of these two regions is independently tested the **predicate**
5. This procedure continues until **all regions are uniform**

Summary

Good edge detector: Variance created by noise, texture, true edge

1st derivative, 2nd derivative

Roberts, Prewitt, Sobel (slightly noise-suppression)

Laplacian:

1. Isotropic
2. Easy to implement
3. No information for edge direction
4. Sensitive to noise

Unsharp masking

Machband

1. Blurring image
2. Subtract the blurring image from the original image create this mask
3. Add the mask to the original image to improve details

LoG

0 — far distance from edge, on the edge itself

$>0 <0$ — edge (one side)

DoG = difference of gaussian

Canny edge detection

1. Apply the gaussian to smooth the image
2. Differential operators apply one and y axis
3. Non-maximum suppression
4. Hysteresis thresholding (high: create the edge, low: continue them)

Multi-scale processing

Interesting scale: the scale that offers most significant edges

Segmentation

- Thresholding: global, adaptive
- Region-based segmentation: region growing, region splitting

Region growing: start from several pixels (seeds), the choice of seeds will influence the result. Then grow from this seeds, after each grow, judge whether the growth of the seeds should be continue by criteria. It will stop until it covers the entire image.

Region splitting

1. First start from a large region (entire image)
2. A predicate is used to determine whether the region is uniform
3. If not, then split the region into two new regions
4. Then each of these two regions should be tested by the predicate
5. Stop when all the regions are uniform

Practice

a) This question is about **Edge Detection**.

[12 marks]

i) Give the mask for the first-order derivative approximation of an image $f(x, y)$, $G_y = \frac{\partial}{\partial y} f(x, y)$.
(3 marks)

ii) For a piece of image [3,4,4,3,10,10,11,11,12], show the result of the convolution with the mask and indicate where the edges would be detected and why. Use replicate border extension for the convolution.
(5 marks)

iii) Given an input image, describe four steps to perform edge detection in the Canny edge detector.
(4 marks)

(1)

$$G_y = \frac{\partial f(x, y)}{\partial y} = \lim_{h \rightarrow 0} \frac{f(x, y+h) - f(x, y)}{h} \approx f(x, y+h) - f(x, y)$$

Assume the horizontal axis is y axis, the mask should be [-1, 1]

(2)

[3 4 4 3 10 10 11 11 12]

↓ after replica border

[3 3 4 4 3 10 10 11 11 12 12]

Apply the mask [-1, 1] on the sequence, the result is:

[0 1 0 -1 7 0 1 0 1 0]

According the results, we find that there is a value 7 which is a large number and can be detected as the edge. Look back to the original sequence, we find that the corresponding position is between 3 and 10.

(3)

- First, smoothing the image by convolution with the Gaussian filter
- Second, apply the differential operators along x and y axis to the image, add them up to create $|G_x| + |G_y|$
- Third, use non-maximum suppression to narrow the edges. Check whether it is the local maximum along gradient
- Fourth, use Hysteresis thresholding locates edge strings

a) This question is about **Edge Detection**.

[10 marks]

- i) Derive the mask for the second-order derivative approximation of an image $f(x, y)$, $G_{xx} = \frac{\partial^2}{\partial x^2} f(x, y)$. Note that x and y are row index and column index, respectively.

(3 marks)

- ii) For a piece of image $[0, 1, 0, 1, 8, 7, 6, 7, 7]$, show the result of the convolution with the mask of the first-order derivative and indicate where the edges would be detected and why. Use replicate border extension for the convolution.

(5 marks)

- iii) Having Laplacian operator, why do we still need the operators of Laplacian of Gaussian and Difference of Gaussians? Explain in your own words.

(2 marks)

(1)

$$G_{xx} = \frac{\partial^2}{\partial x^2} f(x, y) = \lim_{h \rightarrow 0} \frac{\frac{\partial}{\partial x} f(x+h, y) - \frac{\partial}{\partial x} f(x, y)}{h}$$

$$\approx \frac{\partial}{\partial x} f(x+1, y) - \frac{\partial}{\partial x} f(x, y)$$

$$\approx f(x+2, y) - f(x+1, y) - (f(x+1, y) - f(x, y))$$

$$= f(x+2, y) - 2f(x+1, y) + f(x, y)$$

Therefore the mask should be $\begin{bmatrix} 1 \\ -2 \\ 1 \end{bmatrix}$

(2)

$[0 \ 1 \ 0 \ 1 \ 8 \ 7 \ 6 \ 7 \ 7]$

↓ replica border extension

$[0 \ 0 \ 1 \ 0 \ 1 \ 8 \ 7 \ 6 \ 7 \ 7 \ 7]$

↓ $[-1, 1] \Rightarrow$ first order derivative mask

$[0 \ 0 \ 1 \ 1 \ 7 \ 1 \ 7 \ 1 \ 0 \ 0]$

According to the result, we notice that a large value 7 represent the edge occurs. Look back to the original sequence the corresponding position is between 1 and 8.

(3)

Laplacian filter is very sensitive to noise. To make it more robust to noise, we can use Gaussian filter to smooth the image, so we create the combination of Gaussian and laplacian which is LoG operator. DoG is the difference of Gaussian which is an approximation of LoG.