

Web security: web basics

Tariq Elahi ¹
School of Informatics
University of Edinburgh

¹slides from Myrto Arapinis

Web applications

The web has changed the way we live our lives:

- ▶ online banking,
- ▶ online shopping,
- ▶ social networking,
- ▶ entertainment,
- ▶ education,
- ▶ news,
- ▶ ...


Web applications

The web has changed the way we live our lives:

- ▶ online banking,
- ▶ online shopping,
- ▶ social networking,
- ▶ entertainment,
- ▶ education,
- ▶ news,
- ▶ ...

and has brought new classes of security and privacy concerns

Web applications



Client
(HTML, JavaScript)

\longleftrightarrow HTTP \longleftrightarrow



Google

Server
(PHP)

\longleftrightarrow



Database
(SQL)

URLs

A web browser identifies a website with a uniform resource locator (URL).

`Protocol://host:port/path?arg1=val1&arg2=val2#statement`

This naming scheme allows referring to content on distant computers in a simple and consistent manner:

- Protocol: protocol to access the resource (http, https, ftp, ...)
- host: domain or IP address of the server storing the resource
- FilePath: path to the resource on the host
- Resources can be static (file.html) or dynamic (do.php)
- URLs for dynamic content usually include arguments to pass to the process (arg1, arg2)

HTTP requests

GET request

```
GET / HTTP/1.1
Host: www.inf.ed.ac.uk
User-Agent: Mozilla/5.0
           (X11; Ubuntu; Linux x86_64; rv:29.0)
           Gecko/20100101 Firefox/29.0
Accept: text/html,application/xhtml+xml,
        application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: https://www.google.com
Connection: keep-alive
```

- After establishing a TCP connection to the web server, the browser sends HTTP requests to that server
- HTTP requests begin with a request line (GET or POST command)
- An HTTP request consist of the headers section, and the message body

HTTP responses

```
HTTP/1.1 200 OK
Server: Apache
Cache-control: private
Set-Cookie: JSESSIONID=B7E2479EC28064DF84DF4E3DBEE9C7DF;
           Path=/
Content-Type: text/html; charset=UTF-8
Date: Wed, 18 Mar 2015 22:36:30 GMT
Connection: keep-alive
Set-Cookie: NSC_xxx.fe.bd.vl-xd=ffffffffc3a035...423660; path=/
Content-Encoding: gzip
Content-Length: 4162
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0
    Strict//EN" "http://www.w3.org/TR/xhtml1/DTD/
    xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml"
    xml:lang="en" lang="en">
<head>
<title> Informatics home | School of Informatics </title>
...
```

- The main body of a web page is encoded using **HTML**.
- HTML provides a structural description of a document using special tags: `<header></header>`, `<body></body>`, `<div></div>`, `<a>`
- HTML includes a mechanism called **forms** to allow users to provide input to a website in the form of variables represented by name-value pairs.
- Forms can submit data either using the GET (name-value pairs encoded in the URL) or the POST method (name-value pairs encoded in the message body).

```
<form method="POST" action="login.php">  
  FirstUsername: <input type="text" name="username">  
  Password: <input type="password" name="password">  
  <input type="submit" value="submit">  
</form>
```


Dynamic content


- Pages with dynamic content can change after their delivery to the client browser, eg. in response to user interaction or other conditions.
- To provide **dynamic content**, scripting languages such as **Javascript** were introduced.
- To indicate to a browser that Javascript is being used, we use **<script>** and **</script>** tags:
 - Javascript allows programmers to define **functions**
 - Javascript includes several **standard programming constructs** such as **for**, **while**, **if/then/else**, ...
 - Javascript also **handles events**, eg. user clicks on a link, user hovers mouse pointer over a portion of the page

Javascript - example

```
<html>
  <body>
    <p id="p1">Hello World!</p>

    <script>
      document.getElementById("p1").innerHTML =
                                                "New text!";
    </script>
  </body>
</html>
```

Webpage rendering



- The **Document Object Model (DOM)** is a means to represent and access the content of a page.
- Scripts can alter/manipulate the content of a page by accessing/updating the DOM of the page.

How is state managed in HTTP sessions

HTTP is stateless: when a client sends a request, the server sends back a response but the server does not hold any information from previous requests

The problem: in most web applications a client has to access various pages before completing a specific task and the client state should be kept along with those pages. How does the server know if two requests come from the same browser?

Example: the server doesn't require a user to log in at each HTTP request

The idea: insert a token into the page when it is requested and get that token passed back with the next request

Two main approaches to maintain a session between a web client and a web server

- ▶ use hidden fields
- ▶ use cookies

Hidden fields (1)

The principle

Include an HTML form with a hidden field containing a session ID in all the HTML pages sent to the client. This hidden field will be returned back to the server in the request.

Example: the web server can send a hidden HTML form field along with a unique session ID as follows:

```
<input type="hidden" name="sessionid" value="12345">
```

When the form is submitted, the specified name and value are automatically included in the GET or POST data.

Hidden fields (2)

Disadvantages of this approach

- ▶ it requires careful and tedious programming effort, as all the pages have to be dynamically generated to include this hidden field
- ▶ session ends as soon as the browser is closed

Advantage of this approach

All browsers support HTML forms

Cookies (1)

- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments

Cookies (1)

- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments
- ▶ The browser automatically includes the cookie in all its subsequent requests to the originating host of the cookie

Cookies (1)

- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments
- ▶ The browser automatically includes the cookie in all its subsequent requests to the originating host of the cookie
- ▶ Cookies are only sent back by the browser to their originating host and not to any other hosts. Domain and path specify which server (and path) to return the cookie

Cookies (1)

- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments
- ▶ The browser automatically includes the cookie in all its subsequent requests to the originating host of the cookie
- ▶ Cookies are only sent back by the browser to their originating host and not to any other hosts. Domain and path specify which server (and path) to return the cookie
- ▶ A server can set the cookie's value to uniquely identify a client. Hence, cookies are commonly used for session and user management

Cookies (1)

- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments
- ▶ The browser automatically includes the cookie in all its subsequent requests to the originating host of the cookie
- ▶ Cookies are only sent back by the browser to their originating host and not to any other hosts. Domain and path specify which server (and path) to return the cookie
- ▶ A server can set the cookie's value to uniquely identify a client. Hence, cookies are commonly used for session and user management
- ▶ Cookies can be used to hold personalised information, or to help in on-line sales/service (e.g. shopping cart)...

Cookies (1)



- ▶ A cookie is a small piece of information that a server sends to a browser and is then stored inside the browser. A cookie has a name and a value, and other attributes such as domain and path, expiration date, version number, and comments
- ▶ The browser automatically includes the cookie in all its subsequent requests to the originating host of the cookie
- ▶ Cookies are only sent back by the browser to their originating host and not to any other hosts. Domain and path specify which server (and path) to return the cookie
- ▶ A server can set the cookie's value to uniquely identify a client. Hence, cookies are commonly used for session and user management
- ▶ Cookies can be used to hold personalised information, or to help in on-line sales/service (e.g. shopping cart)...

Main limitation

Users may disable cookies in their browser

Cookies (2)

Cookies are set on the client's system when the server uses the Set-Cookie field in the HTTP header of its response:




A cookie has several attributes:

```
Set-Cookie:  name=value[; expires=date]
             [; domain=dom][; path=p][; Secure][; HttpOnly]
expires : (when to be deleted)
domain : (when to send) } scope
path   : (when to send)
Secure : (only over SSL)
HttpOnly : (only over HTTP)
```

Frames

- Embed an “inner” webpage within an “outer” webpage
- `<iframe src="URL"></iframe>`
- The outer webpage specifies the size and position of the inner webpage within the outer webpage

```
<iframe width="560" height="315"  
src="https://www.youtube.com/embed/owsfdh4gxyc"  
frameborder="0" allowfullscreen></iframe>
```



Web security: security goals

Security goals

Web applications should provide the same security guarantees as those required for standalone applications

1. visiting `evil.com` should not infect my computer with malware, or read and write files
Defenses: Javascript sandboxed, avoid bugs in browser code, privilege separation, *etc*
2. visiting `evil.com` should not compromise my sessions with `gmail.com`
Defenses: same-origin policy – each website is isolated from all other websites
3. sensitive data stored about `gmail.com` should be protected

Threat model

Web attacker

- ▶ controls evil.com
- ▶ has valid SSL/TLS certificates for evil.com
- ▶ victim user visits evil.com

Network attacker

- ▶ controls the whole network: can intercept, craft, send messages

A Web attacker is weaker than a Network attacker