```
//@version=6
indicator("XAUUSD Pre-Market Journal Pro", overlay=true, max_labels_count=100)

//=====================================================
// 1. SETTINGS
//=====================================================
string grpSession = "Session & Range"
string grpMacro   = "Macro Data"
string grpVol     = "Volatility & Futures"
string grpManual  = "Manual Journal Inputs"
string grpRisk    = "Risk Controls"
string grpDisplay = "Display"

tradeBias = input.string("Long", "Trade Bias",
    options=["Long", "Short"], group=grpRisk)

asiaSession = input.session("0000-0900", "Asian Session",
    group=grpSession)
sessionTZ = input.string("Africa/Nairobi", "Session Timezone",
    group=grpSession)
adrLength = input.int(20, "ADR Lookback", minval=2,
    group=grpSession)
rangeLimit = input.float(50.0, "Range Ratio Threshold (%)",
    minval=1, maxval=100, group=grpSession)
```

```
dxySymbol = input.symbol("ICEUS:DXY", "DXY Symbol",
    group=grpMacro)
yieldSymbol = input.symbol("TVC:US10Y", "US 10Y Yield Symbol",
    group=grpMacro)

gvzSymbol = input.symbol("CBOE:GVZ", "GVZ Symbol",
    group=grpVol)
gcSymbol = input.symbol("COMEX:GC1!", "Gold Futures Symbol",
    group=grpVol)
rvolLength = input.int(20, "Futures Volume Baseline",
    minval=2, group=grpVol)
rvolLimit = input.float(1.5, "Relative Volume Threshold",
    minval=0.1, step=0.1, group=grpVol)

newsRisk = input.bool(false, "High-Impact News Near Entry?",
    group=grpManual)
newsDetails = input.string("None entered", "News Event / Time",
    group=grpManual)
oiWalls = input.string("Not entered", "CME Call/Put OI Walls",
    group=grpManual)
optionsExpiry = input.bool(false, "Options Expiry Today?",
    group=grpManual)

brokerSpread = input.float(0.20, "Current Broker Spread ($)",
    minval=0, step=0.01, group=grpRisk)
maxSpread = input.float(0.30, "Maximum Allowed Spread ($)",
```

```
    minval=0.01, step=0.01, group=grpRisk)
requireSweep = input.bool(true, "Require Directional Liquidity Sweep?",
    group=grpRisk)

showAsiaLevels = input.bool(true, "Show Asian High/Low",
    group=grpDisplay)
showMarkers = input.bool(true, "Show Sweep Markers",
    group=grpDisplay)
showDashboard = input.bool(true, "Show Journal Dashboard",
    group=grpDisplay)

//=====================================================
// 2. ASIAN SESSION HIGH / LOW
// Recommended chart timeframe: 5m or 15m.
//=====================================================
inAsia = not na(time(timeframe.period, asiaSession, sessionTZ))
asiaStart = inAsia and not inAsia[1]

var float asiaHigh = na
var float asiaLow = na

if asiaStart
   asiaHigh := high
   asiaLow := low
else if inAsia
   asiaHigh := math.max(nz(asiaHigh, high), high)
```

```
    asiaLow := math.min(nz(asiaLow, low), low)

// Require price to breach the level and close back inside.
// Previous-bar checks reduce repeated sweep signals.
asiaHighSweep = not inAsia and not na(asiaHigh) and
    high > asiaHigh and close < asiaHigh and
    (na(high[1]) or high[1] <= asiaHigh)

asiaLowSweep = not inAsia and not na(asiaLow) and
    low < asiaLow and close > asiaLow and
    (na(low[1]) or low[1] >= asiaLow)

// Low sweep = potential bullish setup.
// High sweep = potential bearish setup.
bullSweep = asiaLowSweep
bearSweep = asiaHighSweep

sweepAligned = tradeBias == "Long" ? bullSweep : bearSweep

//=====================================================
// 3. PREVIOUS DAILY RANGE / 20-DAY ADR
//=====================================================
[prevDayHigh, prevDayLow, adr] = request.security(
    syminfo.tickerid,
    "D",
    [high[1], low[1], ta.sma(high - low, adrLength)[1]],
```

```
    gaps=barmerge.gaps_off,
    lookahead=barmerge.lookahead_on)

prevRange = prevDayHigh - prevDayLow
rangeRatio = not na(adr) and adr > 0 ?
    prevRange / adr * 100.0 : na

rangeCompressed = not na(rangeRatio) and rangeRatio < rangeLimit

//=====================================================
// 4. DXY MOMENTUM: 15-MINUTE AND 1-HOUR
// Corrected: each timeframe uses its own data request.
//=====================================================
[dxy15, dxy15Past] = request.security(
    dxySymbol,
    "15",
    [close, close[4]],
    ignore_invalid_symbol=true)

[dxy1h, dxy1hPast] = request.security(
    dxySymbol,
    "60",
    [close, close[3]],
    ignore_invalid_symbol=true)

dxyDataOK = not na(dxy15) and not na(dxy15Past) and
```

```
    not na(dxy1h) and not na(dxy1hPast)

dxyBull = dxyDataOK and dxy15 > dxy15Past and
    dxy1h > dxy1hPast

dxyBear = dxyDataOK and dxy15 < dxy15Past and
    dxy1h < dxy1hPast

//=====================================================
// 5. US 10-YEAR YIELD MOMENTUM
//=====================================================
[yieldNow, yieldPast] = request.security(
    yieldSymbol,
    "60",
    [close, close[3]],
    ignore_invalid_symbol=true)

yieldDataOK = not na(yieldNow) and not na(yieldPast)

yieldRising = yieldDataOK and yieldNow > yieldPast
yieldFalling = yieldDataOK and yieldNow < yieldPast

// General macro alignment, not a guaranteed gold-price predictor.
macroAligned = tradeBias == "Long" ?
    (dxyBear and yieldFalling) :
    (dxyBull and yieldRising)
```

```
//=====================================================
// 6. GVZ VOLATILITY REGIME
//=====================================================
[gvzNow, gvzSma] = request.security(
    gvzSymbol,
    "D",
    [close, ta.sma(close, 20)],
    ignore_invalid_symbol=true)

gvzDataOK = not na(gvzNow) and not na(gvzSma)

gvzExpansion = gvzDataOK and gvzNow > gvzSma
gvzCompression = gvzDataOK and gvzNow < gvzSma

//=====================================================
// 7. COMEX GOLD FUTURES RELATIVE VOLUME
// Compares the current bar with the average bar volume
// on the selected chart timeframe.
//=====================================================
[gcVolume, gcVolumeSma] = request.security(
    gcSymbol,
    timeframe.period,
    [volume, ta.sma(volume, rvolLength)],
    ignore_invalid_symbol=true)
```

```
gcDataOK = not na(gcVolume) and
    not na(gcVolumeSma) and gcVolumeSma > 0

gcRvol = gcDataOK ? gcVolume / gcVolumeSma : na
gcHighRvol = gcDataOK and gcRvol >= rvolLimit

//=====================================================
// 8. FIVE-POINT SCORECARD
//=====================================================
scoreMacro = macroAligned ? 1 : 0
scoreGVZ = gvzExpansion ? 1 : 0
scoreRange = rangeCompressed ? 1 : 0
scoreSweep = sweepAligned ? 1 : 0
scoreRVOL = gcHighRvol ? 1 : 0

totalScore = scoreMacro + scoreGVZ + scoreRange +
    scoreSweep + scoreRVOL

//=====================================================
// 9. RISK GATES AND FINAL DECISION
//=====================================================
spreadBlocked = brokerSpread > maxSpread
newsBlocked = newsRisk
sweepBlocked = requireSweep and not sweepAligned

// Fail closed if a core data feed is unavailable.
```

```
dataUnavailable = not dxyDataOK or not yieldDataOK or
    not gvzDataOK or not gcDataOK or na(adr)

decision = spreadBlocked or newsBlocked or sweepBlocked or
    dataUnavailable ? "NO-GO" :
    totalScore >= 4 ? "GO - FULL RISK" :
    totalScore >= 3 ? "GO - HALF RISK" :
    "NO-GO"

decisionColor = decision == "GO - FULL RISK" ? color.green :
    decision == "GO - HALF RISK" ? color.orange :
    color.red

//=====================================================
// 10. CHART LEVELS AND SWEEP MARKERS
//=====================================================
plot(showAsiaLevels ? asiaHigh : na,
    title="Asian High", color=color.red,
    linewidth=1, style=plot.style_linebr)

plot(showAsiaLevels ? asiaLow : na,
    title="Asian Low", color=color.aqua,
    linewidth=1, style=plot.style_linebr)

plotshape(showMarkers and bullSweep,
    title="Bullish Asian Low Sweep",
```

```
    style=shape.triangleup,
    location=location.belowbar,
    color=color.lime,
    size=size.small,
    text="LOW SWEEP")

plotshape(showMarkers and bearSweep,
    title="Bearish Asian High Sweep",
    style=shape.triangledown,
    location=location.abovebar,
    color=color.red,
    size=size.small,
    text="HIGH SWEEP")

//=====================================================
// 11. DASHBOARD HELPER FUNCTIONS
//=====================================================
statusText(bool condition) =>
   condition ? "PASS" : "FAIL"

statusColor(bool condition) =>
   condition ? color.new(color.green, 75) :
    color.new(color.red, 75)

fmt(float value) =>
   na(value) ? "N/A" : str.tostring(value, "#.##")
```

```
//=================================================
// 12. JOURNAL DASHBOARD
//=================================================
var table dash = table.new(
    position.top_right, 2, 17,
    border_width=1, frame_color=color.gray)

if barstate.islast and showDashboard
   table.cell(dash, 0, 0, "XAUUSD JOURNAL",
       bgcolor=color.navy, text_color=color.white)
   table.cell(dash, 1, 0, tradeBias + " BIAS",
       bgcolor=color.navy, text_color=color.white)

   table.cell(dash, 0, 1, "News / Event")
   table.cell(dash, 1, 1,
       newsRisk ? "BLOCKED: " + newsDetails : newsDetails,
       bgcolor=newsRisk ? color.red : color.new(color.gray, 80),
       text_color=color.white)

   table.cell(dash, 0, 2, "DXY 15m / 1h")
   table.cell(dash, 1, 2,
       not dxyDataOK ? "N/A" :
       dxyBull ? "Bullish" :
       dxyBear ? "Bearish" : "Mixed / Ranging")
```

```
table.cell(dash, 0, 3, "US10Y 1h")
table.cell(dash, 1, 3,
    not yieldDataOK ? "N/A" :
    yieldRising ? "Rising" :
    yieldFalling ? "Falling" : "Neutral")

table.cell(dash, 0, 4, "GVZ / 20 SMA")
table.cell(dash, 1, 4,
    fmt(gvzNow) + " / " + fmt(gvzSma) +
    (gvzExpansion ? " EXPANSION" :
    gvzCompression ? " COMPRESSION" : ""))

table.cell(dash, 0, 5, "CME OI Walls")
table.cell(dash, 1, 5, oiWalls)

table.cell(dash, 0, 6, "Options Expiry")
table.cell(dash, 1, 6,
    optionsExpiry ? "YES" : "NO")

table.cell(dash, 0, 7, "Asian High / Low")
table.cell(dash, 1, 7,
    fmt(asiaHigh) + " / " + fmt(asiaLow))

table.cell(dash, 0, 8, "Prev Range / ADR")
table.cell(dash, 1, 8,
    fmt(prevRange) + " / " + fmt(adr))
```

```
table.cell(dash, 0, 9, "Range Ratio")
table.cell(dash, 1, 9,
    fmt(rangeRatio) + "%" +
    (rangeCompressed ? " COMPRESSED" : ""))

table.cell(dash, 0, 10, "GC Futures RVOL")
table.cell(dash, 1, 10,
    fmt(gcRvol) + "x",
    bgcolor=statusColor(gcHighRvol))

table.cell(dash, 0, 11, "Broker Spread")
table.cell(dash, 1, 11,
    "$" + fmt(brokerSpread),
    bgcolor=statusColor(not spreadBlocked))

table.cell(dash, 0, 12, "Aligned Sweep")
table.cell(dash, 1, 12,
    sweepAligned ? "YES" : "NO",
    bgcolor=statusColor(sweepAligned))

table.cell(dash, 0, 13, "Macro Alignment")
table.cell(dash, 1, 13,
    statusText(macroAligned),
    bgcolor=statusColor(macroAligned))
```

```
    table.cell(dash, 0, 14, "Data Quality")
    table.cell(dash, 1, 14,
        dataUnavailable ? "MISSING DATA" : "CORE DATA OK",
        bgcolor=dataUnavailable ? color.red :
        color.new(color.green, 75),
        text_color=color.white)

    table.cell(dash, 0, 15, "Score")
    table.cell(dash, 1, 15,
        str.tostring(totalScore) + " / 5")

    table.cell(dash, 0, 16, "DECISION")
    table.cell(dash, 1, 16,
        decision,
        bgcolor=decisionColor,
        text_color=color.white)

//=====================================================
// 13. ALERTS
//=====================================================
alertcondition(bullSweep,
    title="Bullish Asian Low Sweep",
    message="XAUUSD: Asian low swept and candle closed back above the level.")

alertcondition(bearSweep,
    title="Bearish Asian High Sweep",
```

```
    message="XAUUSD: Asian high swept and candle closed back below the level.")


alertcondition(decision == "GO - FULL RISK",
    title="Journal: Full-Risk Candidate",
    message="XAUUSD journal score meets the full-risk candidate threshold. Verify risk conditions.")


alertcondition(decision == "GO - HALF RISK",
    title="Journal: Half-Risk Candidate",
    message="XAUUSD journal score meets the half-risk candidate threshold. Verify risk conditions.")
```