

Danny Tan
Hw05
Dt1462

```
1)
perform_if ( start iterator, end iterator, boolean functor, void functor)
count = 0
for start iterator to end iterator -1
    if Boolean functor of iterator value is true
        void functor of iterator value
        increase count
return count
```

preconditions: must give two iterators (beginning and ending of a range) and two functors, where one returns a Boolean and the other returns a void

postconditions: returns an int that is greater or equal to 0

$O(n)$

2)

```

                                myRecFunc( 4 )
                        myRecFunc( 2)
myRecFunc(1)  myRecFunc(1)  myRecFunc(2)  myRecFunc(1)
myRecFunc(0)  myRecFunc(0)  myRecFunc(0)  myRecFunc(0)
```

4: 2: 1: 0: 0:

1: 0: 0:

*

2: 1: 0: 0:

1: 0: 0:

*

running time: $O(n \log n)$

3)

```
myRecFunc( 4 )
myRecFunc( 2)
myRecFunc(1)
myRecFunc(0)
```

4: 2: 1: 0:

running time: $O(\log n)$

4) fib(3) is 5 function call
 fib (4) is 9 function call
 fib (5) is 15 function call

5)
 It prints out
 8,9,-11,2,0,3
 -11,8,9,2,0,3
 -11,2,8,9,0,3
 -11,0,2,8,9,3
 -11,0,2,3,8,9

The content is changing


6)
 It prints out
 8,9,-11,2,0,3
 -11,8,9,2,0,3
 -11,8,9,2,0,3
 -11,8,9,0,2,3
 -11,0,2,3,8,9

The content is changing


7)
 -11 8 3 2 0 9
 -11 0 2 9 8 3
 -11 0 2 3 8 9

The content is changing

8)
 mergeSort



quicksort:



9)

insertionSort : $O(n)$

mergeSort : $O(n \log n)$

quicksort: $O(n \log n)$

10) average time is $O(n)$

11) When $k = i+1$ is called no recursive function will be called, recursion only happens when $k \leq 1$ or when $k > i + 1$