PGDAY ISRAEL 2026 · TEL AVIV

When the planner's misestimation inflates your cloud bill

Spotting query planner issues before they appear

Andrei Lepikhov
PostgreSQL contributor · 25 October 2026

CHAPTER 1

Origins of the idea


31 December 2023

From Xxxxxxxx X. Xxxxxxx ⟨xxxxxxxxxxxxxx@xxxxxx.com⟩

Subject **Segmentation fault caused by Postgrest - reateplan.c:6178 - prepare_sort_from_pathkeys**

```
2023-12-31 03:23:12.048 PST [17763] LOG: server process (PID 19014) was
terminated by signal 11: Segmentation fault
2023-12-31 03:23:12.048 PST [17763] DETAIL: Failed process was running:
      with recursive
      pks_fks as (
        -- pk + fk referencing col
        select
          contype::text as contype,
          conname,
          array_length(conkey, 1) as ncol,
          conrelid as resorigtbl,
          col as resorigcol,
          ord
        from pg_constraint
        left join lateral unnest(conkey) with ordinality as _(col, ord)
        where contype IN ('p', 'f')
```

12 January 2024



The query plan is a great source of savings on your cloud bill.

It requires no extra hardware or watts — just a little thought and careful tuning.

CHAPTER 2

Blind spot

Is it easy to spot an optimisation problem?

One production ERP database ...

Example query

```
SELECT T1.Fld100343RRef,
 (CAST(CAST((T16.Fld100345_ * T1.Fld100346_) AS NUMERIC(28,8)) /
 (T16.Fld100346_ * T1.Fld100345_) AS NUMERIC(28,8)))
FROM (SELECT T15._Fld100344RRef AS Fld100344RRef,
 T15._Fld100343RRef AS Fld100343RRef, T15._Fld100346 AS Fld100346_,
 T15._Fld100345 AS Fld100345_
FROM (SELECT T3._Fld100343RRef AS Fld100343RRef,
 T3._Fld100344RRef AS Fld100344RRef, MAX(T3._Period) AS MAXPERIOD_
FROM _InfoRg100342 T3
WHERE ((T3._Fld2488 = CAST(0 AS NUMERIC))) AND (T3._Period <=
 '2023-12-04 12:49:02'::timestamp AND (EXISTS(SELECT 1
FROM pg_temp.tt3319 T4
LEFT OUTER JOIN _Reference101 T5
 ON (T4._Q_001_F_007RRef = T5._IDRRef) AND (T5._Fld2488 = CAST(0 AS NUMERIC))
LEFT OUTER JOIN _Reference395 T6
 ON (T4._Q_001_F_005RRef = T6._IDRRef) AND (T6._Fld2488 = CAST(0 AS NUMERIC))
LEFT OUTER JOIN _Reference366X1 T7
 ON (T4._Q_001_F_006RRef = T7._IDRRef) AND (T7._Fld2488 = CAST(0 AS NUMERIC))
WHERE ((1=1 OR 1=0) AND (T4._Q_001_F_001RRef =
 '\216@\030f\332\261R\333\021\356\222\212\342\004z\226'::bytea) AND
 (T5._Fld53293RRef = '\214\2150\271\351\244\310\000B<\227\003{~\356e'::bytea)
 AND ((T7._Fld59861RRef <> '\201F\nu\257Q\301Fp\027O\211\214\001{'::bytea)
 OR (T7._Fld59861RRef = '\201F\nu\257Q\301Fp\027O\211\214\001{'::bytea)))
 AND ((T3._Fld100343RRef = T5._Fld53297RRef) AND
 (T3._Fld100344RRef = T6._Fld101340RRef))
UNION ALL SELECT 1
FROM pg_temp.tt3319 T8
LEFT OUTER JOIN _Reference101 T9
 ON (T8._Q_001_F_007RRef = T9._IDRRef) AND (T9._Fld2488 = CAST(0 AS NUMERIC))
LEFT OUTER JOIN _Reference101 T10
 ON (T9._Fld53299RRef = T10._IDRRef) AND (T10._Fld2488 = CAST(0 AS NUMERIC))
LEFT OUTER JOIN _Reference395 T11
 ON (T8._Q_001_F_005RRef = T11._IDRRef) AND (T11._Fld2488 = CAST(0 AS NUMERIC))
LEFT OUTER JOIN _Reference366X1 T12
 ON (T8._Q_001_F_006RRef = T12._IDRRef) AND (T12._Fld2488 = CAST(0 AS NUMERIC))
WHERE ((1=1 OR 1=0) AND (T8._Q_001_F_001RRef =
 '\216@\030f\332\261R\333\021\356\222\212\342\004z\226'::bytea) AND
 (T9._Fld53293RRef = '\214\2150\271\351\244\310\000B<\227\003{~\356e'::bytea)
```

Statistics

- ~ 49500 distinct `queryids`
- ~ 560 queries longer than 1s.
- query text: 33 – 126 000 chars
- execution time: 1 ms – 26 s
- calls: 1 – 5 075
- blocks read: 0 – 3.5 M (≈27 GB)
- plan nodes: 1 – 195
- *never executed* nodes: 0 – 52

Closing the blind spot in query statistics

pg_stat_statements

calls	[10 000 000]
mean_exec_time	[100.0]
total_exec_time	[1 000 000 000]
rows	[10 000 000]
shared_blks_read	[50 000 000]

278 hours of execution time, near the top of any ranking by total time.

What we need:

- Plan quality
- Filter efficiency
- Join method choice
- Missing indexes
- work_mem impact
- …

pg_qualstats, online_advisor, pg_stat_advisor, pganalyze ...

Assessing the instance's potential

1. Estimation error (rows estimated / rows actual)
   is it worth manipulating table statistics?
2. Scan and join filter activity
   do we have enough indexes?
3. SubPlans' share of the execution time
   is it time to rewrite the queries?
4. Spilling of intermediate results
   should queries get more memory?
5. Plan stability
   would a generic plan be a better idea?

Postgres extension pg_track_optimizer

executor finishes a query → estimated vs actual rows, per node → running stats in shared memory → one view: `pg_track_optimizer`

11

metrics per query [ID]

0 restarts

to start tracking: shared memory via the DSM registry, no preload needed

QueryID

Modified Query ID to reduce the number of different entries

Persistent


flushed to disk on backend exit, loaded back after a restart

CHAPTER 3

Domain specifics


Nuance 1: Queries are different

Two joins over a filtered scan



6 nodes · 2 joins · 226 ms

GROUP BY over a scan



2 nodes · 0 joins · 1.4 ms

Nuance 2: Parameter might be in undefined state

```
PREPARE q(int, bool) AS
  SELECT o.id, p.id FROM orders o
    JOIN customers c ON c.id = o.cust JOIN payments p ON p.cust = c.id
  WHERE $1;
```



Nuance 3: statistics' stochastic nature

```
-- 40 times, the data never change
ANALYZE t;
-- actual: 10000 rows every time
EXPLAIN SELECT * FROM t WHERE x = 77;
```

77 made it into the MCV list

≈ 10 000 rows

Bitmap Heap Scan

21 runs of 40

77 missed the MCV list

≈ 60 rows, **off by ×170**

Index Scan

19 runs of 40

Two design decisions in pg_track_optimizer

Dimensionless metrics:

per plan node, units cancel out:

- $r = \frac{\textit{node time}}{\textit{total time}}$
- $f = \frac{\textit{filtered rows}}{\textit{actual rows}}$
- $b = \frac{\textit{local blocks}}{\textit{total blocks}}$
- $e = \left| \ln \frac{\textit{actual rows}}{\textit{estimated rows}} \right|$

Custom `RStats` type:

a distribution, not a number:

`(count, mean, min, max, stddev)`

- Updated in place on every execution (Welford): the plan is unstable, not just wrong.
- The same code path for each parameter.
- Aggregate on statistic column.

```
CREATE FUNCTION pg_track_optimizer(OUT dboid Oid,
                                   OUT avg_error rstats, ...);
CREATE VIEW pg_track_optimizer(avg_min, avg_cnt, ...);
```

CHAPTER 4

How it works

How does it work in practice?

Test bed: **the Join Order Benchmark**

Leis et al., *How Good Are Query Optimizers, Really?*, PVLDB 2015


113
queries over real IMDb data

17
tables joined in the deepest query

Scans
many of them, including parameterised ones

Room
plenty of it, for the planner to go wrong

Cardinality estimation error



per-node error:

$$e = \left| \ln \frac{actual}{estimated} \right|$$

How to average across plan nodes:

- execution time-based
- cost-based
- no weighting

How the estimation error criteria work

TOP-10 by average error **V/S** TOP-10 by time-weighted error

```
SELECT queryid, query, avg_avg AS avg_err, twa_avg AS twa_err
FROM
  (SELECT queryid, query, avg_avg, twa_avg FROM pg_track_optimizer
   ORDER BY avg_avg DESC LIMIT 10) AS avg
JOIN
  (SELECT queryid FROM pg_track_optimizer
   ORDER BY twa_avg DESC LIMIT 10) AS twa
USING (queryid);
```

```
       queryid         |     query      | avg_err | twa_err
-----------------------+----------------+---------+---------
 -6836119621424365027 | /* 28a.sql */  |    3.91 |    2.16
  3631768377448547020 | /* 29c.sql */  |    3.77 |    2.51
 -8544699698054799639 | /* 22d.sql */  |    3.48 |    2.09
  4682104415514032107 | /* 7c.sql */   |    3.48 |    2.18
(4 rows)
```

A look inside 28a.sql

12.	0.000	0.000	↓ 15,866.0		1	→ Nested Loop (cost=673,574.16..713,608.92 rows=1 width=65) (actual rows=15,866.00 loops=1)
13.	0.000	0.000	↓ 2,641,497.5		1	→ Parallel Hash Join (cost=673,573.73..713,604.75 rows=2 width=69) (actual rows=5,282,995.00 loops=1) Hash Cond: (mk.movie_id = t.id)
14.	0.000	0.000	↓ 4.0		1	→ Parallel Seq Scan on movie_keyword mk (cost=0.00..35,789.82 rows=1,130,982 width=8) (actual rows=4,523,930.00 loops=1)
15.	0.000	0.000	↓ 47,805.0		1	→ Parallel Hash (cost=673,573.72..673,573.72 rows=1 width=61) (actual rows=47,805.00 loops=1) Buckets: 65,536 (originally 1024) Batches: 1 (originally 1) Memory Usage: 5,368kB
16.	0.000	0.000	↓ 47,805.0		1	→ Nested Loop (cost=611,718.06..673,573.72 rows=1 width=61) (actual rows=47,805.00 loops=1) Join Filter: (t.id = mi.movie_id)
17.	0.000	0.000	↓ 18,042.0		1	→ Nested Loop (cost=611,717.63..673,566.96 rows=3 width=40) (actual rows=54,126.00 loops=1)
18.	0.000	0.000	↓ 7,874.1		1	→ Parallel Hash Join (cost=611,717.20..673,551.17 rows=7 width=28) (actual rows=55,119.00 loops=1) Hash Cond: (pi.person_id = ci.person_id)
19.	0.000	0.000	↓ 94.7		1	→ Parallel Hash Join (cost=1.84..61,811.22 rows=6,553 width=4) (actual rows=620,526.00 loops=1) Hash Cond: (pi.info_type_id = it3.id)
20.	0.000	0.000	↓ 4.0		1	→ Parallel Seq Scan on person_info pi (cost=0.00..59,792.74 rows=740,474 width=8) (actual rows=2,963,664.00 loops=1)
21.	0.000	0.000	↑ 1.0		1	→ Parallel Hash (cost=1.83..1.83 rows=1 width=4) (actual rows=1.00 loops=1) Buckets: 1,024 Batches: 1 Memory Usage: 40kB
22.	0.000	0.000	↑ 1.0	- 112	1	→ Parallel Seq Scan on info_type it3 (cost=0.00..1.83 rows=1 width=4) (actual rows=1.00 loops=1) Filter: ((info)::text = 'trivia'::text) Rows Removed by Filter: 112

```
->  Parallel Hash Join (rows=6553) (actual rows=620526)
      Hash Cond: (pi.info_type_id = it3.id)
      ->  Parallel Seq Scan on person_info pi (rows=740474) (actual rows=2963664)
      ->  Parallel Hash (rows=1) (actual rows=1.00)
            ->  Parallel Seq Scan on info_type it3 (rows=1) (actual rows=1)
                  Filter: ((info)::text = 'trivia'::text)
                  Rows Removed by Filter: 112
```

⇒ The x4 scan error grows throughout the join tree.

Filter factors: scans and joins

Scans

$$f_{scan} = \max_{scans}\left(\frac{\textit{removed by filter}}{\textit{actual rows}} \times \frac{\textit{node time}}{\textit{total time}}\right)$$

Joins

$$f_{join} = \max_{joins}\left(\frac{\textit{removed by join filter}}{\textit{actual rows}} \times \frac{\textit{node time}}{\textit{total time}}\right)$$

```
Hash Join  (actual time=234.671 rows=289 loops=1)
  Hash Cond: (o.customer_id = c.id)
  Join Filter: (o.amount > c.credit_limit)
  Rows Removed by Join Filter: 47542
  ->  Seq Scan on orders o  (actual time=98.341 rows=47831 loops=1)
        Filter: (status = 'completed')
        Rows Removed by Filter: 952169
  ->  Hash  (actual time=42.110 rows=100000 loops=1)
        ->  Seq Scan on customers c  (actual time=21.543 rows=100000)
```

How the filter criteria work

```
SELECT queryid, query, avg_avg AS avg_err, sf_avg
FROM pg_track_optimizer
ORDER BY sf_avg DESC LIMIT 5;
```


```
       queryid        |     query      | avg_err | sf_avg
----------------------+----------------+---------+---------
  7987931480126446697 | /* 15b.sql */ |    1.60 | 1459.35
 -4244378222084090458 | /* 23a.sql */ |    1.75 | 1424.58
 -6679854959453081533 | /* 15a.sql */ |    1.95 | 1406.36
 -1139306376856509831 | /* 23b.sql */ |    1.48 | 1403.23
 -4904731422305343909 | /* 15c.sql */ |    2.69 | 1342.81
(5 rows)
```



How the filter criteria work


```
SELECT queryid, query, avg_avg AS avg_err, sf_avg
FROM pg_track_optimizer
ORDER BY sf_avg DESC LIMIT 5;
```

```
       queryid        |      query      | avg_err | sf_avg
----------------------+-----------------+---------+---------
  7987931480126446697 | /* 15b.sql */ |    1.60 | 1459.35
 -4244378222084090458 | /* 23a.sql */ |    1.75 | 1424.58
 -6679854959453081533 | /* 15a.sql */ |    1.95 | 1406.36
 -1139306376856509831 | /* 23b.sql */ |    1.48 | 1403.23
 -4904731422305343909 | /* 15c.sql */ |    2.69 | 1342.81
(5 rows)
```




```
->  Parallel Hash Join (actual rows=354.20 loops=5)
      Hash Cond: (mi.info_type_id = it1.id)
      ->  Parallel Seq Scan on movie_info mi (actual rows=354.20 loops=5)
            Filter: ((note ~~ '%internet%'::text) AND (info ~~ 'USA:% 200%'::text))
            Rows Removed by Filter: 2966790
      ->  Parallel Hash (actual rows=0.20 loops=5)
```

Effect of the indexes found



JOB, 113 queries: plain time / time with the new indexes, best to worst

Join filtering EXPLAIN can’t see




```
SELECT * FROM big
  JOIN small USING (x);
```


Hash Join

```
Hash Join (actual rows=1000.00 loops=1)
  Hash Cond: (big.x = small.x)
  ->  Seq Scan on big (actual rows=10000000.00 loops=1)
  ->  Hash (actual rows=100.00 loops=1)
        ->  Seq Scan on small (actual rows=100.00 loops=1)
Execution Time: 332.203 ms
```

Nested Loop

```
Nested Loop (actual rows=1000.00 loops=1)
  Join Filter: (big.x = small.x)
  Rows Removed by Join Filter: 999999000
  ->  Seq Scan on big (actual rows=10000000.00 loops=1)
  ->  Materialize (actual rows=100.00 loops=10000000)
        ->  Seq Scan on small (actual rows=100.00 loops=1)
Execution Time: 20799.413 ms
```

Join filtering EXPLAIN can’t see




```
SELECT * FROM big
  JOIN small USING (x);
```

```
CREATE INDEX idx ON big (x);
```

Hash Join

```
Hash Join (actual rows=1000.00 loops=1)
  Hash Cond: (big.x = small.x)
  ->  Seq Scan on big (actual rows=10000000.00 loops=1)
  ->  Hash (actual rows=100.00 loops=1)
        ->  Seq Scan on small (actual rows=100.00 loops=1)
Execution Time: 332.203 ms
```

Nested Loop

```
Nested Loop (actual rows=1000.00 loops=1)
  ->  Seq Scan on small (actual rows=100.00 loops=1)
  ->  Index Scan using idx on big
        (actual rows=10.00 loops=100)
        Index Cond: (x = small.x)
        Index Searches: 100
Execution Time: 0.187 ms
```

Spilling of intermediate results

Who spills:

- Hash Join
- Hash Aggregate
- Window Aggregate
- Sort
- Materialize
- CTE /Recursive CTE

Who doesn't spill:

- INTERSECT/EXCEPT (Hashed)
- Memoize
- Hashed SubPlan
- BitmapScan

How the spilling criterion works

Rank queries by how much they spill, then see if memory actually matters

```
SELECT queryid, LEFT(query,13) AS query,
  ROUND((temp_avg*8192/1024/1024)
    ::numeric,0) AS spill_mb
FROM track_data
ORDER BY CASE WHEN blks_avg = 0 THEN 0
  ELSE temp_avg/blks_avg END DESC
LIMIT 5;
```

```
      queryid          |    query     | spill_mb
-----------------------+--------------+----------
 -4733402157366146115 | /* 8c.sql */  |      598
 -3437698612165670854 | /* 8d.sql */  |      381
  4682104415514032107 | /* 7c.sql */  |     2678
  1798119524484989875 | /* 10c.sql */ |      179
 -3013169471333993680 | /* 16c.sql */ |       91
(5 rows)
```

Same query, only work_mem changes

```
SET work_mem = '1MB';
Execution Time: 1841 ms

SET work_mem = '4MB';
Execution Time: 1405 ms

SET work_mem = '64MB';
Execution Time: 950 ms
```

What a bigger `work_mem` changes

- **Hash Join** → **Nested Loop + Memoize**
- Incremental Sort + Merge Append → Sort + Append
- Merge Append + Sort → Sort + Append
- **Group Aggregate + Sort** → **Hash Aggregate**
- Index Scan → Sort + Seq Scan
- Index Scan → Incremental Sort + Index Scan
- **Hash Join** → **Merge Join**
- → Materialize

CHAPTER 5

Outcomes

(the shortest one)

The useful bits

1. Track accumulated average error

   On tuned system growth or spike in average error means loosing efficiency

2. Watch SCAN and JOIN Filter factors

   The most critical metrics that expose missed indexes

3. Combine these metrics with `pg_stat_statements`

   It might highlight queries that deserve GENERIC/CUSTOM plan changeover

Questions?

Andrei Lepikhov
PostgreSQL contributor

lepihov@gmail.com
github.com/danolivo



pg_track_optimizer on GitHub