

<p>gtags mode (gtags.el) gtags or global -u to update</p> <p>C-] Goto [Reference or Definition]. C-c t Goto definition. gtags-find-tag M- . Goto definition. gtags-find-tag. C-c r Goto reference. gtags-find-reference C-c s Goto Symbols M- ; Cycle to next result. w w -next-gtag C- t Go back in tag stack. (Previous location) M- * gtags-pop-stack, jumps back to/from stack..</p> <p>C-c P Find file, with tab completion. Can't remember dir. C-c g Grep Mouse-2 gtags-find-tag-by-event. Goto tag under cursor.</p> <p>Help M-x apropos Show functions matching text C-h a Show bound functions matching text, with binding. C-h b Show All bindings for major mode C-h c Show function for key C-h k Show function for key, with related incremental. C-h k C-s - show cmds valid in search mode.</p> <p>C-h w Show binding for function. Forgot what keys to use...</p> <p>C-h f Describe a function C-h m Describe minor modes. Show key cmds by mode C-h v What is variables purpose and value C-h t Emacs tutorial M-x describe-bindings Show key cmds</p> <p>Misc M-x shell Start a shell buffer M-x M- Execute shell-command-on-region M-x auto-fill-mode - word wrap M-x load-file Reload .emacs M-x load-theme Emacs 24 color theme system emacs -debug-init debug your .emacs. Cursor to end of function, then C-x C-e to eval.</p> <p>Org mode M-x org-info C- c . Insert timestamp M- RET New heading/item at current level/TAB - visibility on/off M- Left/Right Promote/Demote heading/item M-S-RET Left/Right Promote/Demote subtree</p> <p>Server mode emacsclient to attach C-x C-c Closes the client frame/Xwindow C-x # Saves file, tells client to exit unless pending edit reqsts.</p>	<p>Progammig C-x w p highlight until disabled. highlight-phrase C-c h highlight symbol w hile at point. highlight-symbol.el</p> <p>C-c C-c Comment block. C- M- \ Re-indent region C- M- q Re-indent sexp/block</p> <p>M- m Goto line start. Indent start, not col 0.. C-x - (minus) Shrink font., C-x + to magnify. C-c C-n; p Move NextPrev across next preprocessor conditional. Set mark at starting point. C-c C-u Move up preprocessor</p> <p>M-x c macro-expand Show in new buffer</p> <p>funcs: compile, gdb, emerge-files, show-paren-mode emerge-files-with-ancestor, ediff-buffers C- x ` next-error</p> <p>Commonly used C- / Undo. Also C-x u; C- _ M- / Autocomplete word</p> <p>C- k Kill line, to kill ring. C- w Kill / cut region C- M- k Kill sexp forward M- w Save region w/o cutting. C- y yank last kill M- Del Delete to start of word</p> <p>C- s Search, incremental. C- r Reverse search, incremental C- s C- s Search for next. C- s C- w Search word from start of point. underbars break... C- c o Show Occur-ences in window. Custom.</p> <p>M- % Query/Replace C- M- s Regex search, incremental.</p> <p>C- g Quit the current command. M-x revert-buffer Remove edits. F4 mapping.</p> <p>Motion C-M- <> for balanced expressions by convention C- M- a, e Function. Start, End. repeat for next function</p> <p>C- M- f, b sexp/brackets. Forw ard (Backw ards) Vs. % custom % - sexp/brackets -Matching:, backw ard or forw ard.. C- c l goto-line (custom) normal is M-g g C- l Put current line in center of window. C- Left/Right Move to next word M- f, b are same</p>	<p>Windows / Buffers & Frames (X windows) C-x b Pick buffer quickly from minibuffer. Incremental typing C-x C-b Pick buffer from full-screen list.</p> <p>C-x 4 b Open buffer in new Window C-x 5 b Open buffer in new Frame C-x 5 f Open file in new Frame. Tab completion.</p> <p>C- x 2 Split Vertical current buffer. Also custom M-4 C- x 3 Split Horizontal current buffer</p> <p>C- x 1 Close all but current w indow C- x 0 Close current w indow C- x k Kill buffer. Opens next buffer w indow (s)</p> <p>C- x o Switch to Other buffer. Shift- left/right/up/down Switch to other buffer C- x 5 o Switch to Other Frame M- b balance-w indow s</p> <p>C- pgdn / pgup Buffer cycle in w indow . custom C-x Left/Right Buffer cycle in w indow . Default</p> <p>M-x view -buffer Read only mode</p> <p>Regions Mark, Point = start, end of region Mark ring per buffer, Mark is set for yank, insert, motion. C-SPC Set mark to current location. C-x C-x Sw ap mark & point, Jump to mark. C-u C-spc Cycle through mark ring. Jump back to mark. C-x -h Make entire buffer the region M- h Make current paragraph the region. repeat to grow .</p> <p>Registers list-register.el helpers C-x r s r Copy region to register named r C-x r i r Insert text from register</p> <p>Rectangles C-x r r Copy rectangle to register C-x r k Kill rectangle C-x r y Yank rectangle C-x r t Prefix rectangle lines with string M-x view -register</p> <p>Custom Re-maps C-x C-m Easier than M-x, esp if capslock is mapped to ctrl M- b Balance-w indow s F4 Refresh-file</p>

