```
public class ClassRankingSystem {

    public static void main(String[] args) {
        String[] names = {"Jawo", "Jovelyn", "Sandra", "Grace"};
        int[][] rawQuizData = {
            {85, 90, 83, 92},
            {76, 80, 79, 85},
            {95, 92, 98, 91},
            {85, 95, 82, 92}
        };

        Student[] students = new Student[names.length];
        for (int i = 0; i < names.length; i++) {
            students[i] = new Student(names[i], rawQuizData[i]);
        }

        bubbleSortByAverage(students);

        printLeaderboard(students);

        String searchName = "Grace";
        int rank = findStudentRank(students, searchName);
        if (rank != -1) {
            System.out.println("\nSearch Result: " + searchName + " is ranked #" + rank);
        } else {
            System.out.println("\nSearch Result: Student " + searchName + " not found.");
        }
    }

    public static void bubbleSortByAverage(Student[] students) {
        int n = students.length;
        for (int i = 0; i < n - 1; i++) {
            for (int j = 0; j < n - i - 1; j++) {
                if (students[j].getAverage() < students[j + 1].getAverage()) {
                    Student temp = students[j];
                    students[j] = students[j + 1];
                    students[j + 1] = temp;
                }
            }
        }
    }

    public static void printLeaderboard(Student[] students) {
        System.out.println("=== CLASS LEADERBOARD ===");
```

```
        System.out.printf("%-6s | %-10s | %-8s\n", "Rank", "Name", "Average");
        System.out.println("--------------------------------");

        int currentRank = 1;
        for (int i = 0; i < students.length; i++) {
            if (i > 0 && students[i].getAverage() < students[i - 1].getAverage()) {
                currentRank = i + 1;
            }
            System.out.printf("#%-5d | %-10s | %-8.2f\n", currentRank, students[i].name,
students[i].getAverage());
        }
    }

    public static int findStudentRank(Student[] sortedStudents, String targetName) {
        int currentRank = 1;
        for (int i = 0; i < sortedStudents.length; i++) {
            if (i > 0 && sortedStudents[i].getAverage() < sortedStudents[i - 1].getAverage()) {
                currentRank = i + 1;
            }
            if (sortedStudents[i].name.equalsIgnoreCase(targetName)) {
                return currentRank;
            }
        }
        return -1;
    }
}

class Student {
    String name;
    int[] quizzes;
    private double average;

    public Student(String name, int[] quizzes) {
        this.name = name;
        this.quizzes = quizzes;
        this.average = calculateAverage();
    }

    private double calculateAverage() {
        int sum = 0;
        for (int score : quizzes) {
            sum += score;
        }
        return (double) sum / quizzes.length;
```

```
    }

    public double getAverage() {
        return this.average;
    }
}
```

