








Blockchain Applications

Lecture 8: Machine Learning, AI and Their Limits; Exam Review



Daniel Traian PELE

Bucharest University of Economic Studies
IDA Institute Digital Assets
Blockchain Research Center
Master Blockchain for Business (MBB), FABIZ
26 November 2026

Opening: Does Machine Learning Forecast Crypto Better?

> *"Even when no exploitable forecasting relation exists, looking long enough and hard enough at a given set of data will often reveal one or more forecasting models that look good, but are in fact useless."*
>
> — *White (2000)*

- Direction of Bitcoin, 2020–2026: machine learning (ML) is right on 51.3% to 51.7% of days, against a base rate of 50.6%
  - XGBoost (extreme gradient boosting) fits 78% of past days and 51% of new ones
- 810 trading rules: the best rule of 2018–2022 ranks 779th in 2023–2026
  - its deflated Sharpe ratio (DSR), which counts the search, is 0.72: not significant
- Bitcoin value at risk at 1% (VaR 1%), 2024 – October 2026: for the ML and pretrained (foundation) models, no difference in quantile score from GARCH-t is detected
  - GARCH-t: generalised autoregressive conditional heteroskedasticity with Student-t errors (Lecture 4)
  - the pretrained Chronos-2 forecasts without fitting and keeps its rank after its release date

▸ Central chart: 810 Trading Rules

Today's Question and Route

- **Question**: machine learning (ML) and pretrained artificial intelligence (AI) models are now standard tools. Do they forecast crypto returns and crypto risk better than the statistical models of Lectures 2–7, and how do we find out without fooling ourselves?
- **Route**
  - can ML predict the direction of Bitcoin? Logit, random forest, gradient boosting
  - data snooping: what happens when we try 810 trading rules
  - risk forecasts: classical, ML and pretrained (foundation) models for Value-at-Risk
  - the limits of ML and AI in crypto finance
  - exam review: what you should be able to interpret
- From Lecture 7: train, validation and test periods, and a benchmark without the new information; today adds walk-forward refitting, many-rule searches and pretrained models
- Data: EOD Historical Data (EODHD) daily Bitcoin prices and volumes, 2015 – 23 October 2026

Learning Outcomes

- Set up a walk-forward evaluation and explain why in-sample accuracy is not evidence
- Read accuracy, the Brier score, the area under the curve and the Pesaran–Timmermann test against the right benchmark
- Explain data snooping and the deflated Sharpe ratio
- Compare Value-at-Risk forecasts by breach rate and by quantile score, and explain why these can disagree
- Name the specific risks of pretrained models: look-ahead through pretraining, survivorship, reproducibility
- Interpret the main results of Lectures 1–8 in the exam format

Abbreviations

AI artificial intelligence
AUC area under the ROC curve
BTC Bitcoin
CRIX CRypto IndeX; **VCRIX** its volatility index
DM Diebold–Mariano (test)
DSR deflated Sharpe ratio
EODHD EOD Historical Data
ES expected shortfall
ETF exchange-traded fund
EWMA-N exponentially weighted moving average, Normal quantile
GARCH-t generalised autoregressive conditional heteroskedasticity, Student-t errors
HAC heteroskedasticity- and autocorrelation-consistent
HAR heterogeneous autoregressive
HS historical simulation
LLM large language model
LR likelihood ratio (test)
ML machine learning
ROC receiver operating characteristic
MOM(k) k-day momentum rule
MA(s,l) moving-average crossover, s and l days
PSR probabilistic Sharpe ratio
PT Pesaran–Timmermann test
QGBM gradient-boosted quantile trees
QReg linear quantile regression
QS quantile score (pinball loss)
SHAP Shapley additive explanations
SR Sharpe ratio
VaR Value-at-Risk
XGBoost extreme gradient boosting

Reading and Tools

- Optimal shifts of a forecast and calibration diagnostics: Gneiting & Resin (2023)
- Quantile regression: Koenker & Bassett (1978); directional accuracy: Pesaran & Timmermann (1992)
- Data snooping: White (2000); Bailey & López de Prado (2014), *The deflated Sharpe ratio*
- Pretrained forecasting model: Ansari et al. (2025), *Chronos-2: from univariate to universal forecasting*; explanations: Lundberg & Lee (2017)
- Backtesting zones: Basel Committee (2019), MAR32, *Minimum capital requirements for market risk*
- Video units on Quantinar: AI Meets Blockchain, Crypto-Backed P2P Lending
- Software: Python libraries `scikit-learn` (logit, random forest), `xgboost` (gradient boosting), `shap` (explanations), `arch` (GARCH), `statsmodels` (quantile regression), `chronos-forecasting` (Chronos-2)

The Prediction Problem

- Target: tomorrow's direction $y_{t+1} = \mathbb{1}\{r_{t+1} > 0\}$; features x_t known at today's close: returns of the last three days, 5-, 20- and 60-day momentum, 5- and 20-day volatility, volume changes, gaps to the 50- and 200-day averages, day of the week (13 features)
- Three classifiers of increasing flexibility:
  - logistic regression (logit): $P(y_{t+1} = 1 \mid x_t) = \Lambda(\beta_0 + x_t'\beta)$, $\Lambda(u) = 1/(1 + e^{-u})$, with a ridge penalty
  - random forest: average of $B = 500$ trees, each grown on a bootstrap sample with random feature subsets
  - gradient boosting (XGBoost): additive trees, $F_m(x) = F_{m-1}(x) + \eta\, h_m(x)$, each h_m fitted to the gradient of the log-loss; $\eta = 0.05$, 300 trees of depth 3
- Walk-forward design: at origin τ, train on all data up to τ, predict the next 63 days; move τ forward 63 days and refit (40 origins); test 1 January 2020 – 22 October 2026 ($T = 2\,487$ days)
  - origin 1: train to 31 December 2019, predict 1 January – 3 March 2020
  - origin 2: train to 3 March 2020 (now including those 63 realised days), predict 4 March – 5 May 2020
- Each forecast uses only information available before its target day; realised test days later join the training data, which is not leakage

Measuring Predictive Skill

- Accuracy $= T^{-1}\sum_t \mathbb{1}\{\hat{y}_t = y_t\}$ must beat the base rate: Bitcoin rose on 50.6% of test days, so "always up" already scores 50.6%
- Brier score of the probabilities p_t: $\mathrm{BS} = T^{-1}\sum_t (p_t - y_t)^2$; two constant benchmarks
  - ex post: $p_t = \bar{y}$ of the test period gives $\bar{y}(1-\bar{y}) = 0.2500$ (not available at forecast time)
  - from the past only: p_t = share of up days in the training data at each origin (0.526–0.556) gives 0.2510
- Area under the receiver operating characteristic curve (AUC): probability that a random up-day gets a higher p_t than a random down-day; 0.5 = no skill
- Pesaran–Timmermann (PT) test: compares the hit rate $\hat{P}$ with the hit rate expected if forecasts and outcomes were independent, $P^* = \bar{y}\,\hat{\bar{y}} + (1-\bar{y})(1-\hat{\bar{y}})$:

$$\mathrm{PT} = \frac{\hat{P} - P^*}{\sqrt{\widehat{V}(\hat{P}) - \widehat{V}(P^*)}} \overset{a}{\sim} N(0,1)$$

- Trading: long when $p_t > 0.5$, otherwise cash; 10 basis points (bp) cost per change of position; annualised Sharpe ratio (SR) $= \sqrt{365}\,\bar{g}/s_g$
- Sampling error of an annualised SR over Y years: $\mathrm{se} \approx \sqrt{(1 + \mathrm{SR}^2/2)/Y}$, about 0.4 for $Y = 6.8$

Results, 2020–2026


	accuracy (%)		AUC	Brier	PT	share	SR	max. draw-
	in-sample	out-of-sample			(p)	long		down (%)
Always up / buy and hold	–	50.6	0.500	0.2500	–	100%	0.59	76.6
Logit	55.8	51.7	0.525	0.2515	0.03	85%	0.72	68.6
Random forest	64.6	51.6	0.514	0.2514	0.07	78%	0.81	80.0
XGBoost	**78.3**	51.3	0.508	0.2611	0.13	65%	0.63	76.9

- Max. drawdown: largest fall of the strategy's wealth from a previous peak, $1 - e^{-D_{\log}/\mathbf{100}}$ with $D_{\log}$ the fall in cumulative log return (Lecture 2)
- Out-of-sample accuracy is 0.7–1.1 percentage points above the base rate; only the logit passes the PT test at 5% (one-sided)
- Every Brier score is *worse* than both constants (0.2500 ex post, 0.2510 from the past): the raw probabilities do not improve on a constant, although the logit ranks days slightly better than chance (AUC 0.525)
- The more flexible the model, the larger the gap between in-sample and out-of-sample accuracy: XGBoost fits 78% of past days and 51% of new ones (overfitting)
- Sharpe ratios of 0.63–0.81 against 0.59: differences far below one standard error (≈ 0.4); the logit is long 85% of the time, so it is mostly buy-and-hold
- Accuracy by year falls from 55% (2020) to 46–51% (2025–2026): whatever was learnt does not persist
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026

Worked Example: the Pesaran–Timmermann Test for the Logit

- Inputs, $T = 2\,487$ test days: share of up days $\bar{y} = 0.506$; share of "up" forecasts $\bar{\hat{y}} = 0.854$; hit rate $\hat{P} = 1\,287/2\,487 = 0.5175$ (1 092 correct "up" and 195 correct "down")
- Step 1, hit rate if forecasts ignored the outcome: $P^* = \bar{y}\,\bar{\hat{y}} + (1-\bar{y})(1-\bar{\hat{y}}) = 0.506 \times 0.854 + 0.494 \times 0.146 = 0.5044$
- Step 2, variances:
  - $\widehat{V}(\hat{P}) = P^*(1-P^*)/T = 1.005 \times 10^{-4}$
  - $\widehat{V}(P^*) = 0.505 \times 10^{-4}$ (from the formula of Pesaran & Timmermann (1992))
  - standard error $\sqrt{1.005 - 0.505} \times 10^{-2} = 0.00707$
- Step 3, statistic: $\mathrm{PT} = (0.5175 - 0.5044)/0.00707 = 1.85$; one-sided p $= 0.032$: significant at 5%
- Reading: the benchmark is $P^* = 50.4\%$, not 50%; a model that is long 85% of the time earns most of its hits from up days
- The excess hit rate is 1.3 percentage points: about 33 more correct days out of 2 487 than independent forecasts would give
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026


Accuracy Follows the Base Rate



- Bars: out-of-sample accuracy by calendar year; red line: share of up days in that year, the accuracy of "always up"
- Accuracy is high when the market rises (2020: 55–57%, base rate 56.3%) and low when it falls (2022: 48.5–50.4%, base rate 46.3%)
- The models are long 58–95% of days in every year, so their accuracy moves with the base rate
- Each model beats the base rate in only 4 or 5 of the 7 years: no year-by-year evidence of a stable edge
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026

BA_L8_acc_year


Are the Probabilities Calibrated?



- Left: test days grouped by forecast probability p_t (bins of width 0.03 around 0.5); share of up days in each bin against the mean p_t. Calibrated forecasts lie on the dashed line
- Logit: 90% of its p_t lie between 0.475 and 0.607; when it says 0.59 on average, up days are 53%
- XGBoost spreads its p_t from 0.36 to 0.71 (5% and 95% quantiles), but up days are 49% in its lowest bin and 51% in its highest: confident and uninformative, hence the worst Brier score (0.2611)
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026

BA_L8_calib

Overfitting and What the Model Uses



- Shapley additive explanations (SHAP): the prediction is split into feature contributions, $f(x) = \phi_0 + \sum_j \phi_j(x)$, with ϕ_j the average marginal contribution of feature j over all orderings of the features
- The largest contributions come from today's return and 5-day volatility; the day of the week ranks fourth
- SHAP explains the *model*, not the market: a large $|\phi_j|$ for a model with no skill is not evidence that the feature predicts returns
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026

BA_L8_ml_acc ▶ Interactive

Trading the Signals



- The gains over buy-and-hold come in a few episodes (2020–2021, parts of 2022); in between, the curves move in parallel with buy-and-hold
- A strategy that is long 65–85% of the time inherits the market's drawdowns: maximum drawdowns of 69–80% against 77% for buy-and-hold
- The chart plots cumulative log returns: these drawdowns are falls of 116–161 log points (145 for buy-and-hold), which are less than 100% of wealth
- Source: own computation on EODHD daily Bitcoin prices and volumes, 2015 – 23 October 2026; test days 2020–2026

BA_L8_ml_equity ▶ Interactive

Data Snooping: the Deflated Sharpe Ratio and the Reality Check

- Among N rules with no skill, the best one still has a high Sharpe ratio. For N independent rules with true SR $= 0$, the expected maximum is approximately (SR in daily units here, $=$ annualised SR$/\sqrt{365}$)


$$\mathrm{SR}_{\mathbf{0}} = \sqrt{V[\widehat{\mathrm{SR}}_n]}\left[(1-\gamma)\,\Phi^{-\mathbf{1}}\!\left(1-\tfrac{\mathbf{1}}{N}\right) + \gamma\,\Phi^{-\mathbf{1}}\!\left(1-\tfrac{\mathbf{1}}{N\mathrm{e}}\right)\right], \quad \gamma \approx 0.5772$$

- Probabilistic Sharpe ratio (PSR): probability that the true SR exceeds a benchmark SR^*, allowing for skewness $\hat{\gamma}_{\mathbf{3}}$ and kurtosis $\hat{\gamma}_{\mathbf{4}}$ of daily returns over T days:

$$\mathrm{PSR}(\mathrm{SR}^*) = \Phi\left(\frac{(\widehat{\mathrm{SR}} - \mathrm{SR}^*)\sqrt{T-\mathbf{1}}}{\sqrt{\mathbf{1} - \hat{\gamma}_{\mathbf{3}}\widehat{\mathrm{SR}} + \frac{\hat{\gamma}_{\mathbf{4}}-\mathbf{1}}{\mathbf{4}}\widehat{\mathrm{SR}}^{\mathbf{2}}}}\right)$$

- Deflated Sharpe ratio (DSR) $= \mathrm{PSR}(\mathrm{SR}_{\mathbf{0}})$: the benchmark is the best Sharpe ratio expected by chance (Bailey & López de Prado (2014))
- White's (2000) reality check: distribution of the best SR when no rule has skill, by resampling the returns
  - stationary bootstrap: resamples blocks of consecutive days (for example, mean length 20 days) and keeps volatility clustering
  - a simple permutation of the days destroys volatility clustering: a rougher illustration
- Example of a search: 810 rules (560 moving-average crossovers MA(s,l) and 250 momentum rules MOM(k)), selected on 2018–2022, evaluated on 2023 – 23 October 2026


810 Trading Rules



- Best rule in 2018–2022: MOM(2), SR $= 0.84$ against 0.04 for buy-and-hold. In 2023–2026: SR $= 0.45$ against 0.90, rank 779 of 810
- Permutation illustration: the best of 810 rules reaches 0.55 on average and 0.93 at the 95th percentile: $p = 0.095$ for the winner. Reality check (stationary bootstrap): $p = 0.31$
- PSR against zero $= 0.97$, but DSR $= 0.72$ with $N = 810$: once the search is counted, the winner is not significant
- The 810 rules are strongly correlated, so the effective number of trials is smaller: DSR 0.80 for $N = 100$, 0.89 for $N = 10$; still below 0.95
- Rank correlation of in-sample and out-of-sample SR: 0.15; only 12% of the rules beat buy-and-hold after 2022
- Source: own computation on EODHD daily Bitcoin prices, 2018 – 23 October 2026

BA_L8_snoop ▶ Interactive

How Much Does a Search Inflate the Best Sharpe Ratio?



- Left: expected best annualised SR of N rules with no skill, $\mathrm{SR}_{\mathbf{0}}$, using the spread of the 810 in-sample SRs: 0.09 for $N = 2$, 0.29 for 10, 0.46 for 100, 0.58 for 810
- The winner's 0.84 is above $\mathrm{SR}_{\mathbf{0}}$ at every N, but the margin shrinks as the search grows
- Right: the deflated Sharpe ratio of the winner falls below 0.95 from $N = 3$ rules on, and is 0.72 at $N = 810$
- Source: own computation on EODHD daily Bitcoin prices, 2018 – 23 October 2026

BA_L8_dsr

Worked Example: Deflating the Best Sharpe Ratio

- Winner MOM(2), 2018–2022: $T = 1\,826$ days; daily $\widehat{\mathrm{SR}} = 0.0438$ ($\times\sqrt{365} = 0.84$); skewness $\hat{\gamma}_3 = 0.58$, kurtosis $\hat{\gamma}_4 = 11.46$
- Step 1, spread of the 810 daily SRs: $\sqrt{V[\widehat{\mathrm{SR}}_n]} = 0.00953$
- Step 2, Normal quantiles for $N = 810$: $\Phi^{-1}(1 - 1/810) = 3.027$, $\Phi^{-1}(1 - 1/(810e)) = 3.317$
- Step 3, benchmark: $\mathrm{SR}_0 = 0.00953 \times (0.423 \times 3.027 + 0.577 \times 3.317) = 0.00953 \times 3.195 = 0.0304$ (annualised 0.58)
- Step 4, denominator: $\sqrt{1 - 0.58 \times 0.0438 + \frac{11.46-1}{4} \times 0.0438^2} = \sqrt{0.980} = 0.990$
- Step 5, statistic: $(0.0438 - 0.0304)\sqrt{1\,825}/0.990 = 0.578$; DSR $= \Phi(0.578) = 0.72$
- Same steps with $\mathrm{SR}^* = 0$: $0.0438 \times \sqrt{1\,825}/0.990 = 1.89$, PSR $= \Phi(1.89) = 0.97$. The search alone moves the verdict from "significant" to "not significant"
- Source: own computation on EODHD daily Bitcoin prices, 2018 – 23 October 2026

Six Value-at-Risk Models

- q_t: the α-quantile of the return r_t given information to $t-1$ (negative); one-day Value-at-Risk $\mathrm{VaR}_t = -q_t$, a positive loss (Lecture 4); $\alpha = 1\%$ and 5%; returns in %
- Classical (Lecture 4):
  - historical simulation (HS): empirical α-quantile of the last 500 returns
  - EWMA-N: $\sigma_t^2 = 0.94\,\sigma_{t-1}^2 + 0.06\,r_{t-1}^2$, $q_t = \Phi^{-1}(\alpha)\sigma_t$
  - GARCH(1,1)-t: $q_t = \mu + \sigma_t\, t_\nu^{-1}(\alpha)\sqrt{(\nu-2)/\nu}$, refitted every 21 days
- Machine learning:
  - linear quantile regression (QReg, Koenker & Bassett (1978)) on heterogeneous autoregressive (HAR) terms: $q_t = \beta_0 + \beta_1|r_{t-1}| + \beta_2 \mathrm{RV}_{t-1}^{(5)} + \beta_3 \mathrm{RV}_{t-1}^{(22)} + \beta_4 \mathrm{RV}_{t-1}^{(66)} + \beta_5 \min(r_{t-1}, 0)$, with $\mathrm{RV}^{(k)}$ the k-day root mean square return
  - gradient-boosted quantile trees (QGBM): 300 trees minimising the quantile loss on 9 features (returns, volatilities, volume change); rolling 1 500 days
- Pretrained: Chronos-2 (Ansari et al. (2025)), a transformer trained on a large corpus of real and synthetic series; it returns quantiles from 1% to 99% directly. *Zero-shot*: no parameter is fitted to Bitcoin; input = the last 512 daily returns
- Forecasts from 1 June 2022; test 1 January 2024 – 23 October 2026 ($T = 1\,027$ days)

How to Score a Quantile Forecast

- Breach indicator $h_t = \mathbb{1}\{r_t < q_t\}$; breach rate $\bar{h}$ should be close to α
- Kupiec likelihood ratio (LR) test of $\bar{h} = \alpha$; Christoffersen test of independent breaches (Lecture 4)
- Quantile score (QS), also called pinball loss:


$$\mathrm{QS}_\alpha(q, r) = (r - q)\,(\alpha - \mathbb{1}\{r < q\}) \geq 0$$

- The QS is *strictly consistent* for the quantile: its expectation is minimised only by the true conditional quantile. The breach rate is not: the forecast $q_t = -\infty$ on 99% of days and $+\infty$ on 1% has a perfect breach rate and is useless
- Diebold–Mariano (DM) test on the loss difference $d_t = \mathrm{QS}_t^A - \mathrm{QS}_t^B$:

$$\mathrm{DM} = \frac{\bar{d}}{\sqrt{\hat{\Omega}_d / T}} \overset{a}{\sim} N(0,1), \qquad \hat{\Omega}_d = \text{HAC (Newey–West) long-run variance}$$

- Breach rate answers "is the level right on average?"; the mean QS answers "how large is the average loss?", a loss whose expectation is smallest for the true quantile

The Quantile Score: a Graphical Illustration



- Left: the loss of one day. A breach costs 0.99 per percentage point below q; a day above q costs only 0.01 per point
- Right: mean QS of a *constant* 1% quantile over the 1 027 test days. The minimum (0.0827) is at the empirical 1% quantile, -6.48%: the score rewards the true quantile
- A constant $q = -5\%$ (2.6% breaches) scores 0.0912; $q = -10\%$ (0.1% breaches) 0.1057
- GARCH-t scores 0.0803, below every constant: a forecast that follows volatility beats the best fixed one
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_pinball

Worked Example: the Quantile Score of Two Days


- GARCH-t, 1% quantile, $\mathrm{QS}_{\mathbf{0.01}}(q, r) = (r - q)(0.01 - \mathbb{1}\{r < q\})$, returns in %
- Day A, 5 March 2024, no breach: $q = -10.62$ (VaR 10.62%), $r = -6.86$
  - $r - q = 3.76 > 0$, so $\mathbb{1} = 0$: $\mathrm{QS} = 3.76 \times 0.01 = 0.0376$
  - a large loss, but above the forecast: the cost is small and comes from a VaR set too far out
- Day B, 5 February 2026, breach: $q = -8.92$ (VaR 8.92%), $r = -15.23$
  - $r - q = -6.32 < 0$, so $\mathbb{1} = 1$: $\mathrm{QS} = -6.32 \times (0.01 - 1) = 6.25$
  - one day, 166 times the loss of day A
- Mean over the 1 027 test days: 0.0803, a total of 82.5; day B alone is 7.6% of it
- The mean QS is driven by a few breaches; with about 10 breaches expected, differences between models are noisy
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

Bitcoin VaR, 2024 – October 2026

	$\alpha = 1\%$ (10.3 breaches expected)					$\alpha = 5\%$			
model	breach %	Kupiec p	Christ. p	QS	DM p	breach %	Kupiec p	QS	DM p
HS	1.17	0.60	0.59	0.0842	0.45	5.36	0.61	0.2782	0.57
EWMA-N	**2.14**	**0.001**	0.33	0.0880	0.18	5.26	0.71	0.2785	0.18
GARCH-t	0.68	0.28	0.76	**0.0803**	–	5.65	0.35	**0.2748**	–
QReg	0.88	0.68	0.69	0.0822	0.71	3.89	0.09	0.2755	0.92
QGBM	1.07	0.82	0.63	0.0848	0.36	6.13	0.11	0.2875	0.07
Chronos-2	1.27	0.41	0.56	0.0827	0.54	5.16	0.81	0.2773	0.71

- DM p: two-sided test of equal mean QS against GARCH-t
- All models except EWMA-N pass the coverage tests. The best breach rate (QGBM, 1.07%) does not have the lowest QS; GARCH-t has the lowest mean realised QS in this test, with 7 breaches against 10.3 expected
- At 1%, no difference in expected QS from GARCH-t is detected: Chronos-2 minus GARCH-t $= 0.0025$, 95% interval $[-0.0053, 0.0102]$. Not rejecting equality does not show that the models are equally good
- The 5% level gives more breaches and more power; QGBM is the weakest there (p 0.07)
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026


Breaches Day by Day



- Cumulative breaches of each 1% VaR, 1 January 2024 – 23 October 2026; dashed: expected 0.01× days (10.3 at the end); band: 95% binomial range for each day (5 to 17 at the end)
- EWMA-N is above the band on 553 days from 5 August 2024 on and ends with 22 breaches: the Kupiec failure of the table
- HS (April – August 2024) and Chronos-2 (April – October 2024) are above the band on some days; Chronos-2 has 7 breaches in 2024 against 3.7 expected, then returns inside the band
- GARCH-t, QReg and QGBM stay inside the band throughout (7, 9 and 11 breaches)
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_breaches


Breach Rate and Quantile Score Rank Models Differently



- Closest to target: QGBM, HS, Chronos-2. Lowest QS: GARCH-t, QReg, Chronos-2
- A forecast can hit the right breach count while being too high on calm days and too low on volatile days; the QS penalises both
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_var_models ▶ Interactive

VaR Paths of the Tree Model and GARCH-t



- Chart: 1% return quantiles q_t; the VaR is $-q_t$
- On 14 January 2024 the tree model's 1% VaR jumps from 7.3% to 35.4%; GARCH-t moves from 9.9% to 9.4%
- The input: a −7.9% return on 12 January, the day after the spot Bitcoin exchange-traded fund (ETF) launch, then a 52% fall in volume on 13 January, a combination the trees met only in crash periods
- Trees do not extrapolate smoothly: an unusual input lands in an extreme leaf. A risk manager needs bounds or a fallback rule
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_var_paths ▶ Interactive


Pretrained Models and Look-Ahead

- A pretrained model may have seen the test period during training. Chronos-2 was released in October 2025; its training corpus may include Bitcoin prices for 2024–2025. Only forecasts after the release are clean; earlier ones are a retrospective back-test
- Reproducibility: a model name without a fixed version (revision) can load other weights later; a back-test must report the exact version
- A test for look-ahead: score the same model before and after its release date (20 October 2025); 1% VaR, mean QS:

	HS	EWMA-N	GARCH-t	QReg	QGBM	Chronos-2
before release (659 days): QS	0.081	0.083	**0.077**	0.085	0.086	0.082
after release (368 days): QS	0.089	0.097	0.087	**0.077**	0.083	0.084
after release: breach %	0.82	2.17	0.54	1.09	1.09	1.09

- Chronos-2 ranks third in both periods: no sign of an advantage from leaked data, but 368 days and 4 expected breaches cannot prove its absence
- Large language models (LLMs): same problem, stronger; a back-test of an LLM must use dates after its training cut-off
- Other pretrained models: TimesFM 2.5 returns only deciles (10%–90%), so it cannot give a 1% VaR without extrapolation

Rolling Quantile Scores Relative to GARCH-t



- Mean 1% QS of each model minus that of GARCH-t over the last 365 days ($\times 10^{-3}$); below zero = better than GARCH-t; first window ends 30 December 2024
- In the last window (to 23 October 2026) QReg (-9.9), QGBM (-3.4) and Chronos-2 (-2.7) are ahead of GARCH-t; EWMA-N ($+10.3$) and HS ($+2.6$) behind
- Chronos-2 is ahead in 16% of the windows, QReg in 38%; the jumps are single breach days entering or leaving the window
- Differences of ± 0.01 against a mean QS of 0.08 are of the size that one large breach creates
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_qs_roll ▶ Interactive

Limits of Machine-Learning Forecasts in Crypto Markets

1. **Low signal**: daily return direction is close to a coin toss (base rate 50.6%, best accuracy 51.7%); flexibility adds variance, not signal
2. **Non-stationarity**: regimes change (2020–2021 boom, 2022 crash, 2024 ETF era); what is learnt in one regime may not transfer (accuracy by year, HS correction)
3. **Few tail observations**: a 1% quantile from 500 days rests on 5 points; tail models are noisy by construction (Lectures 4 and 6)
4. **Data snooping**: testing many models and reporting the best inflates performance; report the number of trials and deflate
5. **Look-ahead**: pretrained models and LLMs may have seen the test period; features must be known at the forecast time; selection must use only past data (BitMood, Lecture 7)
6. **Survivorship**: today's list of coins excludes the dead ones; results on survivors overstate performance
7. **Explanation $\neq$ cause**: SHAP and feature importances describe the model; causal claims need a design (event study, Lecture 7)

⊡ What ML does well here: flexible quantile forecasts with no detectable loss against GARCH, early-warning classifiers with many features (Lecture 5), text-based sentiment (Lecture 7), when evaluated out of sample with the right score

The Exam: Friday 27 November 2026

- On the course website, 60 minutes; no books, notes or other materials
- Final grade: exam 50%, due-diligence project with Prof. Alon 50%; attendance strongly recommended
- 30 multiple-choice questions, one point each: 15 on Crypto Economics and 15 on Blockchain Analytics, mixed together
- The last 5 questions are about a short case built on real output from the course (tables, charts, tests)
- Each student gets a different set of questions on the screen; no calculation is required and a wrong answer costs nothing
- To choose between the options of a question on output, check three things:
  1. **What is measured**: the statistic and its null hypothesis or benchmark
  2. **What the number says**: direction, size, significance, in the units of the problem
  3. **What it does not say**: the limitation (sample size, regime, multiple testing, look-ahead, association vs cause)
- Preparation: the interpretation exercises at the end of each lecture, the practice quizzes and the practice exam on the course website

Review: Lectures 1–3

- **L1 Blockchains as data**
  - hash rate from difficulty, $\hat{H} = D \cdot 2^{32}/600$: a measure of security cost
  - supply rule: 21 million BTC, halving every 210 000 blocks; issuance inflation 0.82% after 2024
  - concentration: Herfindahl–Hirschman index (HHI) $= \sum s_i^2$; two issuers hold 85% of stablecoins
  - log-linear trends and their standard errors; data-quality checks before any analysis
- **L2 Stylised facts, efficiency, bubbles**
  - annualise with $\sqrt{365}$; heavy tails: Jarque–Bera, quantile–quantile plots
  - volatility clustering: Ljung–Box $Q(m)$ on r_t^2 vs on r_t
  - weak-form efficiency: variance ratio $\mathrm{VR}(k) = \mathrm{Var}(r_t^{(k)})/(k\,\mathrm{Var}(r_t))$, robust test
  - bubbles: log-periodic power law (LPPL), critical time t_c, fit is not forecast; Metcalfe's law $V \propto N^b$
- **L3 Crypto indices: CRIX, VCRIX and index funds**
  - market-value index with a divisor (no jump at rebalancing); survivorship bias; capped weights
  - volatility index VCRIX: 30-day window; tracking error and tracking difference of a replica or a fund

Review: Lectures 4–5

- **L4 Volatility and tail risk**
  - GARCH(1,1): $\sigma_t^2 = \omega + \alpha r_{t-1}^2 + \beta \sigma_{t-1}^2$; persistence $\alpha + \beta$, half-life; Student-t errors
  - VaR and ES; four methods (Normal, HS, EWMA, GARCH-t)
  - backtests: Kupiec (frequency), Christoffersen (independence), Basel traffic light
  - out of sample: what a short new period can and cannot show
- **L5 Stablecoins: depegs**
  - deviation in basis points $d_t = 10^4(P_t - 1)$; breach episodes; power-law tails
  - automated market makers (AMM): constant product $xy = k$ and StableSwap; pool composition as an early signal
  - event-level evaluation of alarms: detection rate, lead time, false alerts, utility

Review: Lectures 6–8

- **L6 The depeg pressure index (DPI)**
  - check loss $\rho_\tau(u) = u(\tau - \mathbb{1}\{u < 0\})$; 5% Quantile Lasso; penalty λ selected by generalised approximate cross-validation (GACV)
  - DPI = average selected penalty: a higher λ means stronger tail co-movement; under pressure fewer, stronger tail links remain
  - in-sample fit vs held-out skill
- **L7 Networks, sentiment and asset classes**
  - correlation distance $d_{ij} = \sqrt{2(1 - \rho_{ij})}$, minimum spanning tree, absorption ratio
  - Diebold–Yilmaz spillovers: total, TO, FROM, NET
  - event study: abnormal and cumulative abnormal returns (AR, CAR), cross-sectional tests
  - factor analysis and classification: are cryptos an asset class?
  - sentiment indices and out-of-sample selection
- **L8 Machine learning, AI and limits**
  - walk-forward evaluation; base rate, Brier, AUC, PT test; in-sample vs out-of-sample
  - data snooping and the deflated Sharpe ratio
  - breach rate vs quantile score; look-ahead in pretrained models

Worked Example: a Model Answer

- **Question**: "Bitcoin 1% VaR, 2024 – October 2026: QGBM has a breach rate of 1.07%, GARCH-t of 0.68%; GARCH-t has the lower mean QS (DM p = 0.36). Which model is better?"
- **What is measured**: the breach rate checks the average level of the 1% VaR; the mean QS is an average loss whose expectation is smallest for the true quantile; the DM test asks whether the mean QS difference is zero
- **What the numbers say**: QGBM is closer to 1% on average; GARCH-t is slightly conservative but has the lowest mean realised QS in this test
- **Why they disagree**: a model can hit 1% on average by being too high on calm days and too low on volatile days; only the QS penalises that
- **What it does not say**: that GARCH-t is better. QGBM minus GARCH-t = 0.0045, 95% interval $[-0.0051, 0.0141]$, DM p = 0.36: no difference detected; 1 027 days hold only about 10 expected breaches

Summary

- Direction of Bitcoin: ML accuracy 51.3–51.7% against a base rate of 50.6%; Brier scores worse than a constant estimated from past data; XGBoost 78% in sample, 51% out of sample
- Trading rules: the best of 810 rules in 2018–2022 ranks 779th afterwards; DSR 0.72 once the search is counted
- VaR: no QS difference from GARCH-t is detected at 1% for the ML and pretrained models; GARCH-t has the lowest mean realised QS, QGBM the breach rate closest to 1%
- Chronos-2 forecasts without fitting and keeps its rank after its release date; look-ahead must still be ruled out by design

Interpretation Exercises

1. A random forest classifies tomorrow's Bitcoin direction with 64.6% accuracy in sample and 51.6% out of sample; 50.6% of days are up days. Which number would you report, and against which benchmark?
2. A model's Brier score is 0.2611 and that of the constant forecast 0.2500. What does this say about the model's probabilities, even if its accuracy exceeds 50%?
3. A consultant shows a momentum rule with Sharpe ratio 0.84 over five years. You learn it is the best of 810 rules tried. Explain the deflated Sharpe ratio of 0.72 to a client.
4. QGBM has a 1% breach rate of 1.07%, GARCH-t of 0.68%; the QS is lower for GARCH-t. Which model is better? Why can the two criteria disagree?
5. A pretrained model released in October 2025 is back-tested on 2024–2025 and beats GARCH. What is your main concern, and how would you address it?

⊡ Good luck in the exam on 27 November!

Appendix: Further Material

Optional material for self-study.

- Correcting a Forecast with Its Own Errors
- Bias against Estimation Cost
- Monte Carlo Comparison of Raw, Half and Full Recalibration
- Recalibrating the Bitcoin Forecasts
- Breach Rate and Loss after Correction
- Recalibration and the Basel Traffic Light

Correcting a Forecast with Its Own Errors

- Forecast errors on a calibration window of n days: $e_t = r_t - q_t$. If the forecast were right, $P(e_t < 0) = \alpha$
- Fitted correction: $\hat{c} = \hat{Q}_\alpha(e_{t-n}, \ldots, e_{t-1})$, the empirical α-quantile of the errors; then $P(e < \hat{c}) \approx \alpha$ on the calibration window
- Corrected forecast with intensity λ:

$$q_t^{(\lambda)} = q_t + \lambda \hat{c}, \qquad \lambda = 0 \text{ (Raw)}, \ \tfrac{1}{2} \text{ (Half)}, \ 1 \text{ (Full)}$$

- Static: $\hat{c}$ fitted once on the 500 errors before the test and kept fixed. Rolling: refitted every day on the last 500 errors
- This is a rolling empirical-quantile correction: Full sets the calibration breach rate to about α (exactly α only up to ties and interpolation)
- It resembles split-conformal calibration, but the conformal coverage guarantee needs exchangeable errors, which a rolling window of a time series does not ensure
- Question: does it lower the QS on *future* days? A breach rate closer to α is not the same thing


Bias against Estimation Cost

- Let δ be the true shift that would minimise the expected QS (the bias of the raw forecast) and $\hat{c} = \delta + \varepsilon$, $V(\varepsilon) = \sigma_Q^2$. With f the density at the quantile, a second-order expansion gives the excess expected loss

$$\Delta(\lambda) \approx \frac{f}{2}\left[(1-\lambda)^2\delta^2 + \lambda^2\sigma_Q^2\right]$$

- Estimation cost under dependence: $\sigma_Q^2 \approx \dfrac{\Omega_h}{nf^2}$, $\Omega_h = \sum_{k=-\infty}^{\infty} \mathrm{Cov}(h_t, h_{t+k})$, the long-run variance of the breach indicator; it falls as $1/n$
- Optimal intensity: $\lambda^* = \dfrac{\delta^2}{\delta^2 + \sigma_Q^2}$ (shrinkage, as in a James–Stein estimator)
- Comparisons:
  - Full beats Raw $\iff \delta^2 > \sigma_Q^2$
  - Half beats Full $\iff \delta^2 < 3\sigma_Q^2$; Half beats Raw $\iff \delta^2 > \sigma_Q^2/3$
  - Half is optimal when $\delta^2 = \sigma_Q^2$
- δ refers to the test period. If the bias changes between calibration and test, the fitted $\hat{c}$ transfers badly, whatever n is

Monte Carlo Comparison of Raw, Half and Full Recalibration



- Design: returns i.i.d. Student-t_5, $\alpha = 1\%$, $n = 500$, raw forecast shifted by δ, 20 000 replications; dashed lines = local theory
- Simulated crossings: Half beats Raw from $\delta/\sigma_Q = 0.65$ (theory 0.58), Half beats Full up to 1.40 (theory 1.73), Full beats Raw from 0.95 (theory 1)
- With no bias, Full still raises the expected QS and gives 1.19% breaches: the 1% empirical quantile of 500 errors rests on 5 observations
- Source: own simulation, Student-t_5 returns, 20 000 replications; no market data


BA_L8_lambda

Recalibrating the Bitcoin Forecasts

$\alpha = 1\%$	$\hat{c}$	$\hat{c}^2/\widehat{\mathrm{se}}^2$	breach % (static)			QS (static)		
			Raw	Half	Full	Raw	Half	Full
HS	1.91	2.18	1.17	2.04	**3.21**	0.0842	0.0893	**0.1058****
EWMA-N	−1.14	0.36	2.14	1.66	0.97	0.0880	0.0831*	0.0816
GARCH-t	−0.06	0.00	0.68	0.68	0.68	0.0803	0.0804	0.0805
QReg	0.63	0.57	0.88	0.97	0.97	0.0822	0.0821	0.0820
QGBM	0.08	0.01	1.07	1.07	1.17	0.0848	0.0848	0.0849
Chronos-2	0.33	0.05	1.27	1.36	1.36	0.0827	0.0833	0.0839

- $\widehat{\mathrm{se}}$: block bootstrap (blocks of 20 days). Stars: DM test against Raw, * 5%, ** 1%
- HS: in mid-2022 – 2023 its 500-day window still held the 2022 crash, so it was too conservative and $\hat{c} > 0$. The correction moved q_t up, i.e. lowered the VaR, just before the more volatile 2024: breaches rise to 3.2% and the QS gets 26% worse. At 5% the same correction gives 14.0% breaches
- EWMA-N: the Normal quantile is too thin; $\hat{c} < 0$ transfers, and both corrections help
- Models with $\hat{c}^2/\widehat{\mathrm{se}}^2$ near zero (GARCH-t, QGBM, Chronos-2): the correction is noise and changes almost nothing
- Rolling daily correction limits the HS damage: QS 0.0908 instead of 0.1058
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

Breach Rate and Loss after Correction



- Left: correction moves breach rates in both directions. Right: QS change against Raw ($\times 10^{-3}$); positive = worse
- Same tool, opposite outcomes: the sign depends on whether the calibration-period bias persists into the test period
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026

BA_L8_recal

Recalibration and the Basel Traffic Light

- Basel backtesting zones for a 1% VaR over 250 days (Basel Committee (2019), MAR32): green 0–4, amber 5–9, red 10+ breaches (amber was "yellow" in the 1996 rules)
- Rule behind them: amber once the binomial probability of the breach count reaches 95%, red at 99.99%. Same rule for a crypto year of 365 days: green 0–6, amber 7–12, red 13+
- Illustration of the zones only: bank capital is computed for the whole trading book, not from a one-asset VaR

	breaches 2024 (366 days)			breaches 2025		mean 1% VaR 2024–2025 (%)	
	Raw	Half	Full	Raw	Full	Raw	Full
HS	6	**10**	**17**	3	**11**	6.3	4.4
EWMA-N	**7**	6	3	**10**	3	5.7	6.8
GARCH-t	2	2	2	3	3	7.1	7.1
QReg	3	4	4	2	2	7.6	7.0
QGBM	3	3	4	4	4	6.5	6.4
Chronos-2	**7**	**8**	**8**	3	3	6.7	6.4

- Bold = amber (7–12) or red (13+). EWMA-N: Full moves amber to green in both years, with a VaR 1.1 points higher (more conservative)
- HS: Full moves green to red in 2024 (17 breaches) with a *lower* VaR: a worse model
- Zone, VaR level and forecast quality (QS) are three different outcomes of the same correction; report all three
- Source: own computation on EODHD daily Bitcoin prices and volumes; test 1 January 2024 – 23 October 2026