



Time Series Analysis and Forecasting

Chapter 0: Fundamentals



Daniel Traian PELE

Bucharest University of Economic Studies

IDA Institute Digital Assets

Blockchain Research Center

AI4EFin Artificial Intelligence for Energy Finance

Romanian Academy, Institute for Economic Forecasting

MSCA Digital Finance

Learning Objectives






By the end of this chapter, you will be able to:

1. **Define** time series and distinguish from cross-sectional and panel data
2. **Decompose** time series into trend-cycle, seasonal, and residual components
3. **Apply** exponential smoothing methods (SES, Holt, Holt-Winters, ETS)
4. **Evaluate** forecasts using MAE, RMSE, MAPE, sMAPE
5. **Implement** train/validation/test splits and cross-validation
6. **Model** seasonality using dummy variables or Fourier terms
7. **Remove** trend and seasonality through appropriate methods
8. **Distinguish** between deterministic and stochastic trends

Chapter Outline


- Motivation
- What is a Time Series?
- Time Series Decomposition
- Exponential Smoothing Methods
- Forecast Evaluation
- Modeling Seasonality
- Handling Trend and Seasonality
- Summary and Quiz

Time Series Are Everywhere



- **Finance:** Stock prices, exchange rates, trading volumes
- **Economics:** GDP, unemployment, inflation rates
- **Business:** Sales, website traffic, customer demand
- **Science:** Temperature, pollution levels, patient vitals


Why Study Time Series?



Key Goal: Forecasting

Use historical patterns to predict future values — critical for business planning, risk management, and policy decisions.

Understanding Time Series Structure



Decomposition

Every time series can be decomposed into interpretable components: trend-cycle, seasonality, and noise.

Definition of a Time Series

Definition 1 (Time Series)

A **time series** is a sequence of observations $\{X_t\}$ indexed by time:

$$\{X_t : t \in \mathcal{T}\}$$

where \mathcal{T} is an index set representing time points.

Key Characteristics

- ▣ **Ordered:** Natural temporal ordering
- ▣ **Dependent:** Consecutive observations correlated
- ▣ **Discrete/Continuous:** $t = 1, 2, 3, \dots$

Notation


- ▣ X_t = observation at time t
- ▣ $\{X_t\}_{t=1}^T$ = series with T observations

Time Series: Visual Illustration

Interpretation

Each point X_t represents an observation at time t . The sequence is ordered and consecutive observations are typically correlated.


 TSA_ch1_def_timeseries



Common Time Series Patterns

Pattern Types

- **Trend:** Long-term increase or decrease
- **Seasonal:** Regular periodic patterns
- **Cyclical:** Medium-term fluctuations (2–10 years)
- **Random:** Unpredictable fluctuations




 TSA_ch1_patterns

Time Series: Visual Definition


Interpretation

Each point X_t represents a measurement at discrete time t . The temporal ordering creates dependence between observations.
Data: S&P 500 (2024).

 TSA_ch1_definition



Types of Data: Comparison




Data Type	Units (N)	Time (T)	Example
Cross-sectional	Many	1	Survey of 1000 households
Time series	1	Many	Daily S&P 500 prices
Panel	Many	Many	GDP of 50 countries, 20 years

Examples of Time Series Data

Real Financial Data

Yahoo Finance (2019–2025), normalized to base 100. Notice different volatility patterns: Bitcoin most volatile, Gold most stable.

 TSA_ch1_examples



Why Decompose a Time Series?

Decomposition separates a time series into interpretable components:

Goals:

- Understand underlying patterns
- Remove seasonality for modeling
- Identify trend direction
- Isolate irregular fluctuations
- Improve forecasting accuracy

Components:


- T_t = **Trend-Cycle**: Long-term movement
- S_t = **Seasonal**: Regular periodic pattern
- ε_t = **Residual**: Random noise

Note: Cyclical component is typically absorbed into T_t

Classical Decomposition Models



- **Additive**: $X_t = T_t + S_t + \varepsilon_t$
- **Multiplicative**: $X_t = T_t \times S_t \times \varepsilon_t$

Time Series Decomposition: Visual Example



Each panel isolates one component, making it easy to see how the long-term trend, the recurring seasonal pattern, and the irregular residual combine to produce the observed series.

The Cyclical Component



Characteristics

- Medium-term fluctuations (2–10 years)
- No fixed period (unlike seasonal)
- Reflects expansions/recessions

In Practice

- Cycle is often combined with trend
- Difficult to identify in short series
- Usually not modeled separately

Additive Decomposition Model

Model

$$X_t = T_t + S_t + \varepsilon_t \quad (1)$$


When to Use

- ▣ Seasonal fluctuations are **constant** over time
- ▣ Variance of the series is **stable**

Properties

- ▣ $\mathbb{E}[\varepsilon_t] = 0$ (zero mean)
- ▣ $\sum_{j=1}^s S_j = 0$ (seasonal sums to zero)
- ▣ Units of S_t same as X_t

Additive Decomposition: US Retail Sales (FRED)



Interpretation

Original = Trend + Seasonal + Residual. Seasonal amplitude stays constant. Data: US Retail Sales (RSXFS) from FRED.

Multiplicative Decomposition Model

Model

$$X_t = T_t \times S_t \times \varepsilon_t \quad (2)$$

When to Use

- Seasonal fluctuations **grow** with series level
- Variance **increases** over time

Properties

- $\mathbb{E}[\varepsilon_t] = 1$ (centered at 1)
- $\frac{1}{s} \sum S_j = 1$ (averages to 1)
- S_t is dimensionless ratio


Tip


Log transform converts multiplicative to additive model: $\log X_t = \log T_t + \log S_t + \log \varepsilon_t$

Multiplicative Decomposition: Real Data

Example

Classic Box-Jenkins airline passengers (1949–1960).
Seasonal amplitude grows with level.

 TSA_ch0_multiplicative



Trend Estimation: Moving Average

Definition 2 (Centered Moving Average)

The **centered moving average** of order $2q + 1$ is:

$$\hat{T}_t = \frac{1}{2q + 1} \sum_{j=-q}^q X_{t+j} \quad (3)$$

For Seasonal Data

- Period s **odd**: simple average
- Period s **even**: $2 \times s$ MA with half-weights

Properties


- Smooths seasonal & random
- Larger window \Rightarrow smoother
- Trade-off: lose endpoints

Centered Moving Average: Visual Illustration

Interpretation

The moving average smooths out short-term fluctuations, revealing the underlying trend.

 TSA_ch0_ma



Classical Decomposition Algorithm

Steps for Multiplicative Decomposition

1. **Estimate Trend:** $\hat{T}_t = MA_s(X_t)$
2. **Detrend:** $D_t = X_t / \hat{T}_t$
3. **Estimate Seasonal:** $\hat{S}_j = \text{mean}(D_t \text{ for season } j)$
4. **Normalize:** Scale so $\frac{1}{s} \sum_{j=1}^s \hat{S}_j = 1$
5. **Compute Residuals:** $\hat{\varepsilon}_t = X_t / (\hat{T}_t \times \hat{S}_t)$

Note


For **additive** decomposition: replace division with subtraction and multiplication with addition.

Seasonal Indices: Interpretation

Interpretation

- $S_t > 1$: above-average activity
- $S_t < 1$: below-average activity
- Airline data shows peak travel in July–August

 TSA_ch0_seasonal



STL Decomposition: A Modern Approach

Definition 3 (STL - Seasonal-Trend decomposition using LOESS)

STL uses locally weighted regression (LOESS): $X_t = T_t + S_t + R_t$

Advantages

- ▣ Any seasonal period
- ▣ Seasonal can change over time
- ▣ Robust to outliers
- ▣ Smooth trend estimates

Key Parameters


- ▣ `period`: Seasonal period
- ▣ `seasonal`: Smoothing window
- ▣ `robust`: Downweight outliers

STL Decomposition: Visual Illustration

Key Insight

STL separates the series into trend, seasonal, and remainder using LOESS.

 TSA_cho_stl



Exponential Smoothing: Overview

Definition

Exponential smoothing produces forecasts based on weighted averages of past observations, with weights decaying exponentially.

Why Exponential Smoothing?

- Simple yet effective
- Recent obs. get higher weights
- Handles trend & seasonality
- Foundation for ETS models

Three Main Methods

1. **SES**: Level only
2. **Holt**: Level + Trend
3. **Holt-Winters**: + Seasonality

Simple Exponential Smoothing (SES)

Model

$$\hat{X}_{t+1|t} = \alpha X_t + (1 - \alpha) \hat{X}_{t|t-1} \quad (4)$$

where $\alpha \in (0, 1)$ is the **smoothing parameter**.

How It Works

- Weights decay exponentially
- Large α : responsive
- Small α : smoother

Level Form


$$\ell_t = \alpha X_t + (1 - \alpha) \ell_{t-1}$$

Simple Exponential Smoothing: Effect of α

Trade-off

Smaller α produces smoother forecasts; larger α follows data more closely.

Q TSA_ch0_ses



Holt's Linear Trend Method

Equations

- ▣ **Level:** $\ell_t = \alpha X_t + (1 - \alpha)(\ell_{t-1} + b_{t-1})$
- ▣ **Trend:** $b_t = \beta^*(\ell_t - \ell_{t-1}) + (1 - \beta^*)b_{t-1}$
- ▣ **Forecast:** $\hat{X}_{t+h|t} = \ell_t + h \cdot b_t$

Parameters

- ▣ α : Level smoothing
- ▣ β^* : Trend smoothing

Components


- ▣ ℓ_t : Estimated level
- ▣ b_t : Estimated trend (slope)

Holt's Method: Visualization

Interpretation

- Holt's method captures both level and trend
- Projects them into the forecast horizon
- α controls level changes
- β^* controls trend changes

 TSA_ch0_holt



Holt-Winters Seasonal Method

Equations (Additive Seasonality)

- ▣ **Level:** $\ell_t = \alpha(X_t - S_{t-s}) + (1 - \alpha)(\ell_{t-1} + b_{t-1})$
- ▣ **Trend:** $b_t = \beta^*(\ell_t - \ell_{t-1}) + (1 - \beta^*)b_{t-1}$
- ▣ **Seasonal:** $S_t = \gamma(X_t - \ell_t) + (1 - \gamma)S_{t-s}$
- ▣ **Forecast:** $\hat{X}_{t+h|t} = \ell_t + h \cdot b_t + S_{t+h-s(k+1)}$

Parameters


- ▣ α : Level smoothing
- ▣ β^* : Trend smoothing
- ▣ γ : Seasonal smoothing
- ▣ s : Seasonal period

Holt-Winters: Capturing Seasonality

Key Feature

Holt-Winters decomposes the series and produces seasonal forecasts with trend.

 TSA_ch0_hw



ETS Framework: Error-Trend-Seasonal

Definition 4 (ETS Models)

The **ETS framework** generalizes exponential smoothing: $\text{ETS}(E, T, S)$

Component	N	A	M
Error (E)	–	Additive	Multiplicative
Trend (T)	None	Additive	Multiplicative
Seasonal (S)	None	Additive	Multiplicative

Examples


- ▣ $\text{ETS}(A, N, N)$ = Simple Exponential Smoothing
- ▣ $\text{ETS}(A, A, N)$ = Holt's Linear Method
- ▣ $\text{ETS}(A, A, A)$ = Holt-Winters Additive

ETS: Exponential Smoothing Illustration

Interpretation

ETS models use exponentially weighted observations for forecasting. Weights decay as observations get older.

 TSA_ch0_ets




ETS Model Selection

Interpretation

The ETS framework provides a systematic way to choose the best model using AIC/BIC.

 TSA_ch0_ets_select

ETS Framework: Error-Trend-Seasonality



Damped Trend Methods

Damping Parameter

Introduces $\phi \in (0, 1)$ to prevent over-projection

Equations

- ▣ **Level:** $\ell_t = \alpha X_t + (1 - \alpha)(\ell_{t-1} + \phi b_{t-1})$
- ▣ **Trend:** $b_t = \beta^*(\ell_t - \ell_{t-1}) + (1 - \beta^*)\phi b_{t-1}$
- ▣ **Forecast:** $\hat{X}_{t+h|t} = \ell_t + \phi \frac{1 - \phi^h}{1 - \phi} b_t$

Key Insight

- ▣ As $h \rightarrow \infty$: forecast \rightarrow constant
- ▣ Prevents unrealistic long-term extrapolation
- ▣ Often best for longer horizons

Forecast Accuracy Metrics

Forecast Error

- $e_t = X_t - \hat{X}_t$ (actual minus predicted)

Scale-Dependent

- $MAE = \frac{1}{n} \sum |e_t|$
- $MSE = \frac{1}{n} \sum e_t^2$
- $RMSE = \sqrt{MSE}$



Scale-Independent

- $MAPE = \frac{100}{n} \sum \left| \frac{e_t}{X_t} \right|$
- $sMAPE = \frac{100}{n} \sum \frac{|e_t|}{(|X_t| + |\hat{X}_t|)/2}$

Which to use?


- Same series: RMSE, MAE
- Compare across series: MAPE, sMAPE

Forecast Evaluation: Visual Example



- ▣ **Top:** Actual values vs. forecasted values – visual assessment of fit
- ▣ **Bottom:** Residuals should be centered around zero with no pattern
- ▣ Good forecasts have small, random residuals with constant variance

Comparing Forecast Methods



Interpretation

- Left: Comparing SES, Holt, and Holt-Winters forecasts
- Right: Error metrics for each method

Residual Diagnostics

Residual Properties

Good forecasts should have residuals that are:

1. **Zero mean:** $\mathbb{E}[e_t] = 0$
2. **Uncorrelated:** $\text{Cov}(e_t, e_{t-k}) = 0$
3. **Constant variance:** $\text{Var}(e_t) = \sigma^2$
4. **Normally distributed**

Diagnostic Tests

Ljung-Box test (autocorrelation):

$$Q = T(T+2) \sum_{k=1}^h \frac{\hat{\rho}_k^2}{T-k} \sim \chi_h^2$$

Jarque-Bera test (normality):

$$JB = \frac{T}{6} \left(S^2 + \frac{(K-3)^2}{4} \right) \sim \chi_2^2$$





S = skewness, K = kurtosis

Residual Diagnostics: Visualization

What to Check

- Time plot (no patterns)
- Histogram (normality)
- ACF (no autocorrelation)
- Q-Q plot (normality)

 TSA_ch0_residuals




Time Series Cross-Validation

Why Not Standard CV?

- Time series have temporal dependence
- Future data cannot predict the past
- Standard k-fold causes data leakage

Rolling Origin CV

1. Train on $\{X_1, \dots, X_t\}$
2. Forecast \hat{X}_{t+h}
3. Increment t , repeat



Train / Validation / Test Split

Three-way split for model development:

Training Set


- Fit model parameters
- Largest portion (60–80%)
- Used for estimation

Validation Set


- Tune hyperparameters
- Compare models
- Select best approach

Test Set

- Final evaluation only
- Never used for tuning
- Unbiased performance



Model Development Workflow



Critical Rule


Never use test set for model selection! This causes *data leakage* and overly optimistic performance estimates.

Real Data: Forecast Comparison

Interpretation

Airline passengers data:
Holt-Winters Multiplicative
performs best for seasonal data.

 TSA_ch0_real_data




Forecast Performance Across Datasets

Interpretation

Different series require different models. Seasonal data needs seasonal methods.

 TSA_ch0_multi_series

Different Series Require Different Models



Modeling Seasonality: Two Approaches

1. Dummy Variables:

$$X_t = \mu + \sum_{j=1}^{s-1} \gamma_j D_{jt} + \varepsilon_t$$

- ▣ $D_{jt} = 1$ if t in season j
- ▣ $s - 1$ parameters
- ▣ Any seasonal pattern

2. Fourier Terms:

$$X_t = \mu + \sum_{k=1}^K [\alpha_k \sin(\cdot) + \beta_k \cos(\cdot)]$$

- ▣ Sinusoidal functions
- ▣ $2K$ parameters
- ▣ Smooth patterns

Trade-off


- ▣ **Dummies:** any pattern, more parameters
- ▣ **Fourier:** smooth, fewer parameters

Dummy Variables vs Fourier Terms

Comparison

- **Dummies:** capture any shape but need $s - 1$ parameters
- **Fourier:** uses $2K$ parameters for smooth patterns

 TSA_ch0_fourier



Choosing Between Dummies and Fourier

Criterion	Dummies	Fourier
Parameters (monthly)	11	2K (often 4–6)
Seasonal pattern	Any shape	Smooth/sinusoidal
Interpretation	Direct (month effects)	Frequency components
High-frequency seasons	Many parameters	Efficient
Multiple seasonality	Complex	Easy (add terms)

Guidelines

- ▣ Use **dummies**: irregular patterns, interpretable coefficients
- ▣ Use **Fourier**: smooth patterns, high-frequency seasonality, multiple periods
- ▣ **Fourier terms** are used in TBATS and Facebook Prophet

Why Remove Trend and Seasonality?

Before modeling, we often need to make series stationary:

Reasons to detrend:

- Stationarity requirement
- Focus on fluctuations
- Avoid spurious regression
- Enable valid inference

Reasons to deseasonalize:

- Reveal underlying trend
- Compare across seasons
- Simplify modeling
- Focus on irregular component

Important

After modeling the detrended/deseasonalized series, we must **reverse the transformation** for forecasting.

Trend Removal Methods

Six Common Detrending Approaches

1. **Differencing:** $\Delta X_t = X_t - X_{t-1}$
2. **Linear regression:** $\hat{T}_t = \hat{\beta}_0 + \hat{\beta}_1 t$
3. **Polynomial:** Higher-order polynomial
4. **HP Filter:** Balance fit vs smoothness
5. **Moving average:** $\hat{T}_t = MA_q(X_t)$
6. **LOESS:** Local polynomial regression

Choice Depends On


- ▣ Nature of trend (deterministic vs stochastic)
- ▣ Purpose (forecasting vs analysis)

Detrending Methods: Comparison

Key Insight

Different methods produce different residuals. Choose based on trend type and analysis goals.

 TSA_ch0_detrending



Hodrick-Prescott (HP) Filter

Definition 5 (HP Filter)

The **HP filter** decomposes X_t into trend τ_t and cycle c_t : $X_t = \tau_t + c_t$, by minimizing:


$$\min_{\{\tau_t\}} \left\{ \sum_{t=1}^T (X_t - \tau_t)^2 + \lambda \sum_{t=2}^{T-1} [(\tau_{t+1} - \tau_t) - (\tau_t - \tau_{t-1})]^2 \right\}$$

Interpretation

- First term: fit to data
- Second term: smoothness penalty
- λ : trade-off parameter

Standard λ Values


- Annual: $\lambda = 6.25$
- Quarterly: $\lambda = 1600$
- Monthly: $\lambda = 129600$

HP Filter: Effect of λ 

Trade-off

- **Small λ :** Trend follows data closely (more flexible)
- **Large λ :** Trend becomes smoother (approaches linear trend)

HP Filter: Business Cycle Extraction



Application

HP filter is widely used in macroeconomics to extract business cycles from GDP and other economic series.

HP Filter: Limitations

Known Issues

- ▣ **End-point problem:** Trend estimates unreliable at endpoints
- ▣ **Spurious cycles:** Can create artificial dynamics
- ▣ **λ choice:** Results sensitive to parameter
- ▣ **Non-stationary:** Assumes trend is smooth

Alternatives

- ▣ **Band-pass filters:** Baxter-King, Christiano-Fitzgerald
- ▣ **Hamilton filter:** Regression-based
- ▣ **Unobserved components:** State-space models

Hamilton (2018) Critique

“Why You Should Never Use the Hodrick-Prescott Filter” — suggests using regression on lagged values instead.

Seasonality Removal Methods

Four Approaches to Remove Seasonality

1. **Seasonal differencing:** $\Delta_s X_t = X_t - X_{t-s}$
2. **Division** (multiplicative): $X_t^{adj} = X_t / \hat{S}_t$
3. **Subtraction** (additive): $X_t^{adj} = X_t - \hat{S}_t$
4. **X-13ARIMA-SEATS:** Government statistical method

Seasonal Period s

- Monthly $\Rightarrow s = 12$
- Quarterly $\Rightarrow s = 4$

Seasonal Adjustment: Visualization

Result

Seasonally adjusted series reveals underlying trend without periodic fluctuations.

 TSA_ch0_seasonal_adj



Deterministic vs Stochastic Trend

Deterministic Trend:


$$X_t = \beta_0 + \beta_1 t + \varepsilon_t$$

- Trend is a function of time
- Detrend by regression
- ε_t is stationary

Stochastic Trend:

$$X_t = X_{t-1} + \varepsilon_t$$

- Random walk component
- Detrend by differencing
- ΔX_t is stationary



Wrong Method = Problems


- Differencing deterministic trend \Rightarrow over-differencing
- Regression on stochastic trend \Rightarrow spurious regression

Example: Deterministic Trend

Key

Use **regression** to remove trend γ
residuals are stationary (ACF
decays quickly).

 TSA_ch0_det_trend




Example: Stochastic Trend (Random Walk)

Key

Use **differencing** to remove trend
➤ differences are stationary
(white noise).

 TSA_ch0_stoch_trend



Summary

What We Learned

- ▣ **Time Series Definition:** Sequence of observations indexed by time
- ▣ **Decomposition:** Trend-Cycle + Seasonal + Residual components
- ▣ **Exponential Smoothing:** SES, Holt, Holt-Winters, ETS framework
- ▣ **Forecast Evaluation:** MAE, RMSE, MAPE; train/validation/test splits

Key Takeaway

- ▣ **Understand Before Modeling:**
 - ▶ Always visualize and decompose your data first
 - ▶ Choose additive vs multiplicative based on variance behavior

Quick Quiz

1. What is the difference between additive and multiplicative decomposition?
2. When should you use Holt-Winters instead of simple exponential smoothing?
3. Why can't we use standard k-fold cross-validation for time series?
4. What does $\alpha = 0.9$ mean in exponential smoothing?
5. How do you distinguish between deterministic and stochastic trend?

Quiz Answers

1. **Additive vs Multiplicative:** Additive when seasonal amplitude is constant; multiplicative when it grows with the level.
2. **Holt-Winters:** When data has both trend AND seasonality. SES only handles level.
3. **Time Series CV:** Standard k-fold ignores temporal order — would use future data to predict the past (data leakage).
4. $\alpha = 0.9$: High weight on recent observations, forecast reacts quickly to changes but is more volatile.
5. **Trend type:** Deterministic — predictable function of time (use regression). Stochastic — random walk component (use differencing).

What Comes Next?

Chapter 1: Stochastic Processes and Stationarity

- ▣ **Stochastic Processes:** Mathematical foundation for time series
 - ▶ Random variables indexed by time
 - ▶ Strict vs weak (covariance) stationarity
- ▣ **Key Processes:** White noise and random walk
 - ▶ Building blocks for ARIMA models
 - ▶ Understanding mean reversion vs unit roots
- ▣ **ACF and PACF:** Tools for model identification
 - ▶ Detecting autocorrelation structure
 - ▶ Choosing AR and MA orders

Questions?