DRIVE SIDE HEEL TOE	CONDITION	COAST SIDE TOE HEEL	CONDITION	ACTION REQUIRED
	Desirable pattern. The drive pattern should be centered on the tooth. There should be some clearance between the pattern and the top of the tooth.		**Desirable pattern.** The coast pattern should be centered on the tooth, but may be slightly toward the toe. There should be some clearance between the pattern and the top of the tooth.	None
	Top toe contact		**Top heel contact**	Backlash correct. Thicker pinion position shim required.
	Root heel contact		**Root toe contact**	Backlash correct. Thinner pinion position shim required.
	Top heel contact		**Top toe contact**	Pinion position shim correct. Decrease backlash.
	Root toe contact		**Root heel contact**	Pinion position shim correct. Increase backlash.

8106361d

Fig. 27 PATTERN INTERPRETATION (GEAR CUT 3 AXIS)

DIFFERENTIAL BEARING PRELOAD CHECK

The final check on the differential assembly before installing the axles is torque to rotate pinion and differential combined. This will verify the correct differential bearing preload.

Torque to rotate the differential and pinion should be the torque to rotate the pinion plus 0.79-1.24 N·m (7-11 in. lbs.).

SPECIFICATIONS - 216FBI

AXLE SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Axle Ratio	4.11
Ring Gear Backlash	0.12-0.20 mm (0.005-0.008 in.)
Pinion Bearing Preload - Original Bearing	1-2 N·m (10-20 in. lbs.)
Pinion Bearing Preload - New Bearing	2.3-4.5 N·m (20-40 in. lbs.)

TORQUE SPECIFICATIONS

DESCRIPTION	N·m	Ft. Lbs.	In. Lbs.
Fill Plug	34	25	-
Drain Plug	34	25	-
Differential Cover Bolts	41	30	-
Bearing Cap Bolts	108	80	-