VEHICLE QUICK REFERENCE

TABLE OF CONTENTS

page

FLUID - CAPACITIES & RECOMMENDED
SPECIFICATIONS
RECOMMENDED FLUIDS, LUBRICANTS AND GENUINE PARTS 1
FUSE LOCATIONS & TYPES
SPECIFICATIONS
FUSE PANEL 2
MAINTENANCE SCHEDULES
DESCRIPTION
MAINTENANCE SCHEDULES 5
MAINTENANCE SCHEDULES – EXPORT . . . 11
REPLACEMENT BULBS
SPECIFICATIONS
REPLACEMENT BULBS — IF EQUIPPED . . . 17
REPLACEMENT BULBS — IF EQUIPPED . . . 17
TRAILER TOWING
SPECIFICATIONS
TRAILER TOWING 17

FLUID - CAPACITIES & RECOMMENDED

SPECIFICATIONS

RECOMMENDED FLUIDS, LUBRICANTS AND GENUINE PARTS

ENGINE

Component	Fluid, Lubricant, or Genuine Part
Engine Coolant	Mopar® Antifreeze/Coolant 5 Year/ 100,000 Mile Formula HOAT (Hybrid Organic Additive Technology)
Engine Oil	API Certified SAE 5W-30 Engine Oil is recommended for the 2.4L engine. API Certified SAE 10W-30 Engine Oil is recommended for the 4.0L engine. Meets the requirements of DaimlerChrysler Material Standard MS-6395.
Spark Plugs	Refer to the Vehicle Emission Control Information label in the engine compartment.
Oil Filter (2.4L Engine)	Mopar® Oil Filter (P/N 4105409AB)
Oil Filter (4.0L Engine)	Mopar® Oil Filter (P/N 05281090)
Fuel Selection	87 Octane

CHASSIS

Component	Fluid, Lubricant, or Genuine Part
Automatic Transmission	Mopar® ATF+4 Automatic Transmission Fluid or equivalent.
Manual Transmission	Mopar® Manual Transmission Lubricant or equivalent (meeting the requirements of DaimlerChrysler Material Standard MS-9224)
Transfer Case	Mopar® ATF+4 Automatic Transmission Fluid or equivalent.
Axle Differential (Front)	Mopar® Gear & Axle Lubricant (SAE 80W-90) (API GL-5) or equivalent. For trailer towing, use Mopar® Synthetic Gear & Axle Lubricant (SAE 75W-140) or equivalent.
Axle Differential (Rear)	**194 RBI (Model 35) and 216 RBI (Model 44)** - Mopar® Gear & Axle Lubricant (SAE 80W-90) (API GL-5) or equivalent. For trailer towing, use Mopar® Synthetic Gear & Axle Lubricant (SAE 75W-140) or equivalent. Models equipped with Trac-Lok require an additive. **Rubicon 216 RBI (Model 44)** - Mopar® Synthetic Gear & Axle Lubricant (SAE 75W-140) or equivalent. Models equipped with Trac-Lok require an additive.
Brake Master Cylinder	Mopar® DOT 3 Brake Fluid, SAE J1703 should be used. If DOT 3, SAE J1703 brake fluid is not available, then DOT 4 is acceptable. Use only recommended brake fluids.