P0172-FUEL SYSTEM 1/1 RICH — Continued

TEST	ACTION	APPLICABILITY
5	Ignition on, engine not running. With the DRBIII®, read the TP Sensor voltage. **NOTE: The throttle must be against the stop.** Is the TP Sensor voltage 0.92 of a volt or less with the Throttle closed? Yes → Go To 6 No → Check for a binding throttle condition. If OK, replace the Throttle Position Sensor. Perform POWERTRAIN VERIFICATION TEST VER - 5.	All
6	With the DRBIII®, read the TP Sensor voltage. While monitoring the DRBIII®, slowly open and close the throttle. Does the voltage increase and decrease smoothly? Yes → Go To 7 No → Replace the Throttle Position Sensor. Perform POWERTRAIN VERIFICATION TEST VER - 5.	All
7	Turn the ignition off. Connect a Vacuum Gauge to a Manifold Vacuum source. Start the engine. Allow the engine to idle. **NOTE: If engine will not idle, maintain a constant RPM above idle.** With the DRBIII® in Sensors, read the MAP Sensor vacuum value. Is the DRB reading within 1″ of the Vacuum Gauge reading? Yes → Go To 8 No → Replace the MAP Sensor. Perform POWERTRAIN VERIFICATION TEST VER - 5. **NOTE: Remove the vacuum gauge before continuing.**	All
8	**NOTE: For this test to be valid, the thermostat must be operating correctly.** **NOTE: This test works best if performed on a cold engine (cold soak)** Ignition on, engine not running. With the DRBIII®, read the ECT Sensor value. If the engine was allowed to sit overnight (cold soak), the temperature value should be a sensible value that is somewhere close to the ambient temperature. **NOTE: If engine coolant temperature is above 82°C (180°F), allow the engine to cool until 65°C (150°F) is reached.** Start the Engine. During engine warm-up, monitor the ECT Sensor value. The temp value change should be a smooth transition from start up to normal operating temp 82°C (180°F). The value should reach at least 82°C (180°F). Did the ECT value increase smoothly and did it reach at least 180°F (82°C)? Yes → Go To 9 No → Replace the Engine Coolant Temperature Sensor. Perform POWERTRAIN VERIFICATION TEST VER - 5.	All