FRONT AXLE - 216FBI (Continued)

DRIVE SIDE HEEL TOE	CONDITION	COAST SIDE TOE HEEL	CONDITION	ACTION REQUIRED
	Desirable pattern. The drive pattern should be centered on the tooth. There should be some clearance between the pattern and the top of the tooth.		**Desirable pattern.** The coast pattern should be centered on the tooth, but may be slightly toward the toe. There should be some clearance between the pattern and the top of the tooth.	None
	Top heel contact		**Top toe contact**	Backlash correct. Thicker pinion position shim required.
	Root toe contact		**Root heel contact**	Backlash correct. Thinner pinion position shim required.
	Top heel contact		**Top heel contact**	Pinion position shim correct. Decrease backlash.
	**Root toe contact**		**Root toe contact**	Pinion position shim correct. Increase backlash.

8106312d

Fig. 26 PATTERN INTERPRETATION (GEAR CUT 2 AXIS)

DRIVE SIDE HEEL TOE	CONDITION	COAST SIDE TOE HEEL	CONDITION	ACTION REQUIRED
	Desirable pattern. The drive pattern should be centered on the tooth. There should be some clearance between the pattern and the top of the tooth.		**Desirable pattern.** The coast pattern should be centered on the tooth, but may be slightly toward the toe. There should be some clearance between the pattern and the top of the tooth.	None
	Top toe contact		**Top heel contact**	Backlash correct. Thicker pinion position shim required.
	Root heel contact		**Root toe contact**	Backlash correct. Thinner pinion position shim required.
	Top heel contact		**Top toe contact**	Pinion position shim correct. Decrease backlash.
	**Root toe contact**		**Root heel contact**	Pinion position shim correct. Increase backlash.

8106361d

Fig. 27 PATTERN INTERPRETATION (GEAR CUT 3 AXIS)