DIAGNOSIS AND TESTING - MASTER CYLINDER/POWER BOOSTER 23
STANDARD PROCEDURE - MASTER CYLINDER BLEEDING 24
REMOVAL 24
INSTALLATION 25
PEDAL
DESCRIPTION 25
OPERATION 25
REMOVAL 25
INSTALLATION 25
POWER BRAKE BOOSTER
DESCRIPTION 26
OPERATION 26
REMOVAL 27
INSTALLATION 27
COMBINATION VALVE
DESCRIPTION 27
OPERATION 27
DIAGNOSIS AND TESTING - COMBINATION VALVE 28
REMOVAL 28
INSTALLATION 28
ROTORS
DIAGNOSIS AND TESTING
DIAGNOSIS AND TESTING - DISC BRAKE ROTOR 28
DIAGNOSIS AND TESTING - BRAKE DRUM IN HAT ROTOR 29
STANDARD PROCEDURE
STANDARD PROCEDURE - DISC ROTOR MACHINING 29
STANDARD PROCEDURE - BRAKE DRUM IN HAT ROTOR MACHINING 30
REMOVAL
REMOVAL - FRONT 30
REMOVAL - REAR 30
INSTALLATION
INSTALLATION - FRONT 31
INSTALLATION - REAR 31
WHEEL CYLINDERS
REMOVAL 31
DISASSEMBLY 31
CLEANING 31
INSPECTION 31
ASSEMBLY 31
INSTALLATION 32
SUPPORT PLATE
REMOVAL 32
INSTALLATION 32
PARKING BRAKE
DESCRIPTION 33
OPERATION 33
DIAGNOSIS AND TESTING - PARKING BRAKE . 33
SHOES
DESCRIPTION 34
OPERATION 34
REMOVAL 34
CLEANING - REAR DRUM IN HAT BRAKE 34
INSPECTION - REAR DRUM IN HAT BRAKE . . 34
INSTALLATION 35
ADJUSTMENTS
ADJUSTMENT - REAR DRUM IN HAT PARK BRAKE (ROTOR REMOVED) 35
ADJUSTMENT - WITH ADJUSTING TOOL . . . 37
CABLES
REMOVAL
REMOVAL - DRUM BRAKES 37
REMOVAL - DISC BRAKES 38
INSTALLATION
INSTALLATION - DRUM BRAKES 38
INSTALLATION - DISC BRAKES 38

BRAKES - BASE

DESCRIPTION

DESCRIPTION - BRAKE SYSTEM

Power assist front disc and rear drum brakes are standard equipment. Disc brake components consist of single piston calipers and ventilated rotors. Rear drum brakes are dual shoe units with cast brake drums.

The parking brake mechanism is lever and cable operated. The cables are attached to levers on the rear drum brake secondary shoes. The parking brakes are operated by a hand lever.

A dual diaphragm vacuum power brake booster is used for all applications. All models have an aluminum master cylinder with plastic reservoir.

All models are equipped with a combination valve. The valve contains a pressure differential valve and switch and a fixed rate rear proportioning valve.

Factory brake lining on all models consists of an organic base material combined with metallic particles. The original equipment linings do not contain asbestos.