TRANSFER CASE - NV231

TABLE OF CONTENTS

page

TRANSFER CASE - NV231
DESCRIPTION 165
OPERATION 166
DIAGNOSIS AND TESTING - TRANSFER CASE - NV231 166
REMOVAL 167
DISASSEMBLY 167
CLEANING 175
INSPECTION 175
ASSEMBLY 179
INSTALLATION 190
SPECIFICATIONS TRANSFER CASE - NV231 190
SPECIAL TOOLS NV231 191
FLUID
STANDARD PROCEDURE - FLUID DRAIN AND FILL 193

page

FRONT OUTPUT SHAFT SEAL
REMOVAL 193
INSTALLATION 193
REAR OUTPUT SHAFT SEAL
REMOVAL 194
INSTALLATION 195
SHIFT LEVER
REMOVAL 196
INSTALLATION 196
ADJUSTMENTS - SHIFT LINKAGE 198
SPEEDOMETER DRIVE ADAPTER
REMOVAL 198
INSTALLATION 198
VEHICLE SPEED SENSOR
DESCRIPTION 199
OPERATION 199
REMOVAL 200
INSTALLATION 200

TRANSFER CASE - NV231

DESCRIPTION

The NV231 is a part-time transfer case with a low range reduction gear system. The NV231 has three operating ranges plus a NEUTRAL position. A low range system provides a reduction ratio for increased low speed torque capability.

The geartrain is mounted in two aluminum case halves attached with bolts. The mainshaft front and rear bearings are mounted in aluminum retainer housings bolted to the case halves.

OPERATING RANGES

Transfer case operating ranges are:

- 2WD (2-wheel drive)
- 4x4 (4-wheel drive)
- 4 Lo (4-wheel drive low range

The 2WD range is for use on any road surface at any time.

The 4x4 and 4 Lo ranges are for off road use only. They are not for use on hard surface roads. The only exception being when the road surface is wet or slippery or covered by ice and snow.

The low range reduction gear system is operative in 4 Lo range only. This range is for extra pulling power in off road situations. Low range reduction ratio is 2.72:1.

SHIFT MECHANISM

Operating ranges are selected with a floor mounted shift lever. The shift lever is connected to the transfer case range lever by an adjustable linkage rod. A straight line shift pattern is used. Range positions are marked on the shifter bezel cover plate.