HEATING & AIR CONDITIONING (Continued)

## SPECIFICATIONS

### HEATING-A/C SYSTEM

*A/C SYSTEM*

| Item | Description | Notes |
|---|---|---|
| A/C Compressor | Denso 10PA17 | ND-8 PAG Oil |
| Freeze–up Control | A/C low pressure switch | Input to PCM, accumulator mounted - cycles A/C clutch off below 172 kPa (25 psi) - cycles back on above 276 kPa (40 psi) |
| Low psi Control | A/C low pressure switch | Input to PCM, opens below 172 kPa (25 psi) - resets above 276 kPa (40 psi) |
| High psi Control | A/C high pressure switch (4.0L engine) | Input to PCM, A/C discarge line mounted - opens at discharge pressure above 3100 - 3375 kPa (450 - 490 psi) - resets at 1860 - 2275 kPa (270 - 330 psi) |
| | A/C pressure transducer (2,4L engine) | Input to PCM, A/C discarge line mounted - opens at discharge pressure above 2971 kPa (431 psi) and below 206 kPa (30 psi) |

| Item | Description | Notes |
|---|---|---|
| Refrigerant Charge Capacity | Refer to the A/C Underhood Specification Label located in the engine compartment | R-134a refrigerant |
| A/C Clutch Coil Draw | 2.0 - 3.7 amps | @ 12V ± 0.5V @ 21° C (70° F) |
| A/C Clutch Air Gap | 0.35 - 0.65 mm (0.014 - 0.026 in) | |