## Symptom:
## P0499-NVLD CANISTER VENT VALVE SOLENOID CIRCUIT HIGH

**When Monitored and Set Condition:**

**P0499-NVLD CANISTER VENT VALVE SOLENOID CIRCUIT HIGH**

When Monitored: Engine running.

Set Condition: The PCM detects an open in the NVLD Canister vent solenoid circuits. One trip Fault.

| POSSIBLE CAUSES |
|---|
| GOOD TRIP EQUAL TO ZERO |
| VEHICLE HISTORY AND SERVICE BULLETIN INVESTIGATION |
| NVLD SOLENOID |
| (K106) NVLD SOL CONTROL CIRCUIT SHORTED TO BATTERY VOLTAGE |
| (K106) NVLD SOL CONTROL CIRCUIT OPEN |
| (Z913) GROUND CIRCUIT OPEN |
| PCM |

| TEST | ACTION | APPLICABILITY |
|---|---|---|
| 1 | Start by reading PCM DTC(s) and record the related Freeze Frame data in any DTC(s) are present.<br>Check the vehicle repair history.<br>If the vehicle has a repair history that pertains to the customer's current complaint, review the repair.<br>Inspect the vehicle for any aftermarket accessories that may have been installed incorrectly.<br>Check for any service bulletin(s) related to the customer's complaint or DTC(s).<br>If a service bulletin applies, follow the instructions per service bulletin.<br>Did the service bulletin repair the customer's complaint?<br>Yes → Testing Complete. Perform POWERTRAIN VERIFICATION TEST VER - 5.<br>No → Go To 2 | All |
| 2 | Check for any related TSBs before continuing.<br>Ignition on, engine not running.<br>With the DRBIII®, read DTCs and record the related Freeze Frame data.<br>Is the Good Trip Counter displayed and equal to zero?<br>Yes → Go To 3<br>No → Refer to the INTERMITTENT CONDITION Symptom (Diagnostic Procedure). Perform POWERTRAIN VERIFICATION TEST VER - 5. | All |