Symptom:

P2503-CHARGING SYSTEM OUTPUT LOW

When Monitored and Set Condition:

P2503-CHARGING SYSTEM OUTPUT LOW

When Monitored: The engine running. The engine speed greater than 1157 RPM.

Set Condition: The battery sensed voltage is 1 volt below the charging goal for 13.47 seconds. The PCM senses the battery voltage turns off the field driver and senses the battery voltage again. If the voltages are the same, the code is set.

POSSIBLE CAUSES
GOOD TRIP EQUAL TO ZERO
BATTERY POSITIVE CIRCUIT HIGH RESISTANCE
CASE GROUND HIGH RESISTANCE
GENERATOR OPERATION
(Z20) GEN GROUND CIRCUIT OPEN
(K125) GEN FIELD CONTROL CIRCUIT SHORTED TO BATTERY VOLTAGE
(K125) GEN FIELD CONTROL CIRCUIT OPEN
(K125) GEN FIELD CONTROL CIRCUIT SHORTED TO GROUND
PCM

TEST	ACTION	APPLICABILITY
1	**NOTE: Inspect the vehicle for aftermarket accessories that may exceed the Generator System output.** Ignition on, engine not running. **NOTE: The battery must be fully charged.** **NOTE: The Generator belt tension and condition must be checked before continuing.** With the DRBIII®, read DTCs and record the related Freeze Frame data. With the DRBIII®, erase DTCs. Start the engine. Allow the idle to stabilize. Ignition on, engine not running. With the DRBIII®, read DTCs. Is the Good Trip Counter displayed and equal to zero? Yes → Go To 2 No → Refer to the INTERMITTENT CONDITION Symptom (Diagnostic Procedure). Perform POWERTRAIN VERIFICATION TEST VER - 3.	All