Symptom:
MODULE NOT CONFIGURED FOR PAB OFF SWITCH

When Monitored and Set Condition:

MODULE NOT CONFIGURED FOR PAB OFF SWITCH

When Monitored: When the ACM is not configured for an ON - OFF switch, the ACM monitors the Passenger Airbag On - Off Switch inputs to determine if a switch is present.

Set Condition: The code will set, if the ACM detects a Passenger Airbag ON - OFF Switch connected to the Airbag Control Module.

POSSIBLE CAUSES
INTERMITTENT CODES PRESENT
ACM NOT CONFIGURED FOR PAB OFF SWITCH
ACM, MODULE NOT CONFIGURED FOR PAB OFF SWITCH
PASSENGER AIRBAG INDICATOR DRIVER CIRCUIT SHORT
PAB MUX SWITCH CIRCUIT SHORT TO GROUND
PAB MUX SWITCH CIRCUIT SHORT TOGETHER
ACM, PAB ON - OFF SWITCH CIRCUIT SHORTED

TEST	ACTION	APPLICABILITY
1	Turn the ignition on. Ensure the battery is fully charged. **NOTE: For the purpose of this test, the AECM and ORC modules will be referred to as an ACM.** SELECT ACTIVE or STORED DTC: ACM - ACTIVE DTC Go To 2 ACM - STORED DTC No problem found at this time. Perform __AIRBAG VERIFICATION TEST - VER 1. **NOTE: When reconnecting Airbag system components, the ignition must be turned off and the battery must be disconnected.**	All
2	Inspect vehicle for a Passenger Airbag On - Off Switch located in the center of the instrument panel. Is this vehicle equipped with a Passenger Airbag On - OFF Switch? Yes → Go To 3 No → Go To 4	All