

Package ‘lrspline’

May 30, 2021

Type Package

Title Low-rank Approximation of Smoothing Splines for Massive Data

Version 0.1.0

Author Danqing Xu

Maintainer Danqing Xu <elisexu0308@gmail.com>

Description Functions for approximating the smoothing spline estimates: (1) Low-rank Approximation via Eigensystem Truncation, (2) Nystrom Methods.

License GPL-3

Encoding UTF-8

LazyData true

Imports assist,
mgcv

RoxygenNote 7.1.1

R topics documented:

generate.eigen.cubic	1
hello	2
lrspline.cubic	2
nystrom.cubic	3

Index	5
--------------	----------

generate.eigen.cubic	<i>Gridpoints and Eigendecomposition of Reproducing Kernal for Cubic Splines</i>
----------------------	--

Description

Generates eigendecomposition from gridpoints from an interval.

Usage

```
generate.eigen.cubic(N = 1000, a = 0, b = 1)
```

Arguments

N	The number of gridpoints. It should be an integer. The default value is 1000.
a	The lower limit of the interval used for gridpoints. The default value is 0.
b	The upper limit of the interval used for gridpoints. The default value is 1.

Value

It returns (and saves) a list of following components:

e	A list of two elements of "values" and "vectors", which refer respectively, the eigenvalues and eigenfunctions of reproducing kernel for cubic splines at the pre-selected gridpoints.
xg	A vector of gridpoints.

Examples

```
## Not run:
eigen_res <- generate.eigen.cubic(N=1000,a=2,b=3)

## End(Not run)
```

hello	<i>Hello, World!</i>
-------	----------------------

Description

Prints 'Hello, world!'.

Usage

```
hello()
```

Examples

```
hello()
```

lrspline.cubic	<i>Low-rank Approximation Based on Eigenspaces for Cubic Smoothing Spline Estimates</i>
----------------	---

Description

Computes a low-rank approximation based on eigenspaces, where estimation utilizes functions for linear mixed effect model (LME).

Usage

```
lrspline.cubic(x, y, xg, e, K = 30, method = "REML", pstd = FALSE)
```

Arguments

x	The values of independent variable. It should be a vector.
y	The values of dependent variable. It should be a vector.
xg	The gridpoints used for approximation of
e	A list of two elements of "values" and "vectors", which refer respectively, the eigenvalues and eigenfunctions of reproducing kernel for cubic splines at the pre-selected gridpoints (must agree with xg).
K	An integer value. The truncation parameter indicates the number of eigenvalues/eigenfunctions used in approximation. The default value is 30.
method	A character string. If "REML" the LME model is fit by maximizing the restricted log-likelihood. If "ML" the log-likelihood is maximized. Defaults to "REML".
pstd	An indicator of whether standard deviation is desired. The default value is FALSE.

Value

A vector(s) of following component(s):

fit	The low-rank approximation of cubic smoothing spline estimate.
pstd	The corresponding posterior standard deviation.

Examples

```
## Not run:
data(eigenM)
x <- runif(1000)
y <- sin(32*pi*x)-8*(x-.5)^2 + rnorm(1000)
lrspline.cubic(x,y,xg,e,K,method="REML",pstd=FALSE)

## End(Not run)
```

nystrom.cubic

Nystrom Approximation for Cubic Smoothing Spline Estimates

Description

Computes a Nystrom approximation based on randomly selected columns of Σ matrix, where estimation utilizes functions for linear mixed effect model (LME).

Usage

```
nystrom.cubic(x, y, p = 30, method = "REML", pstd = FALSE)
```

Arguments

x	The values of independent variable. It should be a vector.
y	The values of dependent variable. It should be a vector.
p	An integer value. The selection parameter indicates the number of columns for random selection and approximation. The default value is 30.
method	A character string. If "REML" the LME model is fit by maximizing the restricted log-likelihood. If "ML" the log-likelihood is maximized. Defaults to "REML".
pstd	An indicator of whether standard deviation is desired. The default value is FALSE.
xg	The gridpoints used for approximation of
e	A list of two elements of "values" and "vectors", which refer respectively, the eigenvalues and eigenfunctions of reproducing kernel for cubic splines at the pre-selected gridpoints (must agree with xg).

Value

A vector(s) of following component(s):

fit	The Nystrom approximation of cubic smoothing spline estimate.
pstd	The corresponding posterior standard deviation.

Examples

```
## Not run:
data(eigenM)
x <- runif(1000)
y <- sin(32*pi*x)-8*(x-.5)^2 + rnorm(1000)
nystrom.cubic(x,y,xg,e,K,method="REML",pstd=FALSE)

## End(Not run)
```

Index

`generate.eigen.cubic`, [1](#)

`hello`, [2](#)

`lrspline.cubic`, [2](#)

`nystrom.cubic`, [3](#)